

राजस्थान राज्य क्रीडा परिषद

सवाई मानसिंह स्टेडियम, जनपथ, जयपुर

कार्यालय दूरभाष नं0 0141-2744283, फैक्स नं0 0141-2740568, ईमेल आईडी-rsscjaipur@gmail.com

क्रमांक : एफ-8/स.अ./मरम्मत कार्य/2025-26/62

दिनांक : \$17/4/2025

निविदा सूचना संख्या 🗷 🗸 / 2025-26

राजस्थान राज्य क्रीडा परिषद, जयपुर की ओर से सवाई मानिसंह स्टेडियम, जयपुर परिसर में ज्योनरी मरम्मत कार्य हेतु राज्य/केन्द्र सरकार के अधिकृत संगठनों के विभागों में पंजीकृत संवेदक, जो कि राजस्थान सरकार के उपयुक्त श्रेणी के संवेदकों के समकक्ष हो, से ई—प्रोक्यूरमेंट प्रक्रिया हेतु आनलाइन निविदा आमंत्रित की जाती है।

निविदा से संबंधित अन्य आवश्यक विवरण वेबसाईट http://sppp.rajasthan.gov.in, http://eproc.rajasthan.gov.in व www.rssc.in पर देखी जा सकती है।

सचिव

Signature valid

Digitally signed by Faindra Singh Designation Secretly Date: 2025.0 7 ...54:19 IST Reason: Appro



RAJASTHAN STATE SPORTS COUNCIL

TENDER DOCUMENT

FOR

Joinery Maintenance Work at Sawai Man Singh Stadium, Jaipur.

NIT NO.

NIT No. 08/2025-26

ESTIMATED COST

Rs. 25.00 Lacs

EARNEST MONEY

Rs. 50,000/-

DATE OF SALE / DOWNLOADING

From Thursday April 17, 2025, 16:00 Hours to

Wednesday April 30, 2025, 13:00 Hours

DATE OF RECEIPT (D.D. &

From Thursday April 17, 2025, 16:00 Hours to

DOCUMENTS)

Wednesday April 30, 2025, 15:00 Hours

DATE OF OPENING OF TENDER

Thursday May 01, 2025 AT 16:00 Hours

COMPLETION PERIOD

1 Year (12 Months)

COST OF TENDER

Rs. 500/- in favour of Secretary, RSSC, Jaipur

PROCESSING FEES

Rs 500/- in favour of MD, RISL, Jaipur

Signature yalid

Digitally signed by Paindra Singh Designation Secretary Date: 2025.0 7 .:54:19 IST

Reason: Appro

Rajasthan State Sports Council. Jaipur

Important Dates of Bids

1. Completion Period	1 Year (12 Months)
2. Date of Issue of Notice Inviting Tender	Thursday April 17, 2025
3. Period and Places of Sale/ Download of	From Thursday April 17, 2025, 16:00 Hours to Wednesday
Bidding Documents -	April 30, 2025, 13:00 Hours
	http://sppp.rajasthan.gov.in, www.rssc.in &
	http://eproc.rajasthan.gov.in
4. Deadline for uploading	From Thursday April 17, 2025, 16:00 Hours to Wednesday
	April 30, 2025, 13:00 Hours
5. Time and Date for Opening of Bids	Thursday May 01, 2025 AT 16:00 Hours
6. Place of Opening of Bids	Rajasthan State Sports Council, SMS Stadium, Jaipur-
	302005
7. Officer Inviting Bids	Secretary, Rajasthan State Sports Council. Jaipur.
	Address: SMS Stadium, Jaipur-302005
8. Earnest money to be deposited	As per NIT

Instructions and information to bidder regarding Fee, EMD etc.

District	Name of Work Package No.	Estimated Cost (Rs.)	Earnest Money	Time Allowed for completion		date of	of documents	
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)
Jaipur	Joinery Maintenance Work at Sawai Man Singh Stadium, Jaipur	25.00 Lacs	Rs. 50,000/-	12 Months	Wednesday April 30, 2025, 13:00 Hours	Thursday May 01, 2025, AT 16:00 Hours	http://sppp.rajasthan.gov.in, http://eproc.rajasthan.gov.in & www.rssc.in	F-1 and Above category for Joinery/ Furnitur e works.

- The Tender Fee and earnest money as mentioned above should be deposited in the appropriate form as per the tender documents in favour of Secretary, Rajasthan State Sports Council. Jaipur payable at Jaipur and Processing Fees Rs 500/- in favour of MD, RISL, Jaipur payable at Jaipur and must be uploaded scan copy of Registration of Firm, Demand Draft of Tender Cost, Processing Fee & Earnest Money and GST Number on the site
- 2. The tender can be viewed and downloaded from web site http://sppp.rajasthan.gov.in, http://eproc.rajasthan.gov.in & www.rssc.in
- The authorized tender documents are available for inspection in the office of Rajasthan State Sports Council, SMS Stadium, Jaipur from all working days.

Annexure A: Compliance with the Code of Integrity and No Conflict of Interest

Any person participating in a procurement process shall-

- (a) Not offer any bribe, reward or gift or any material benefit either directly or indirectly in exchange for an unfair advantage in procurement process or to otherwise influence the procurement process;
- (b) Not misrepresent or omit that misleads or attempts to mislead so as to obtain a financial or other benefit or avoid an obligation;
- (c) Not indulge in any collusion, Bid rigging or anticompetitive behavior to impair the transparency, fairness and progress of the procurement process;
- (d) Not misuse any information shared between the procuring entity and the bidders with an intent to gain unfair advantage in the procurement process;
- (e) Not indulge in any coercion including impairing or harming or threatening to do the same, directly or indirectly, to any party or to its property to influence the procurement process;
- (f) Not obstruct any investigation or audit of a procurement process;
- (g) Disclose conflict of interest, if any; and
- (h) Disclose any previous transgressions with any entity in India or any other country during the last three years or any debarment by any other procuring entity.

Conflict of interest.-

The Bidder participating in a bidding process must not have a Conflict of Interest.

A Conflict of interest is considered to be a situation in which a party has interests that could improperly influence that party's performance of official duties or responsibilities, contractual obligations, or compliance with applicable laws and regulations.

- (i) A bidder may be considered to be in conflict of interest with one or more parties in the bidding process if, including but not limited to:
- (a) Have controlling partners/shareholders in common; or
- (b) Receive or have received any direct or indirect subsidy from any of them; or
- (c) Have the same legal representative for purposes of the bid; or
- (d) have a relationship with each other, directly or through common third parties, that puts them in a position to have access to information about or influence on the bid of another bidder, or influence the decisions of the procuring Entity regarding the bidding process; or
- (e) The bidder participates in more than one bid in a bidding process. Participation by a bidder in more than one bid will result in the disqualification of all bids in which the bidder is involved. However, this does not limit the inclusion of the same subcontractor, not otherwise participating as a bidder, in more than one bid; or
- (f) the bidder or any of its affiliates participated as a consultant in the preparation of the design or technical specifications of the goods, Works or services that are the subject of the Bid; or
- (g) Bidder or any of its affiliates has been hired (or proposed to be hired) by the procuring entity as engineer-in-charge/consultant for the contract.

Annexure B: Declaration by the Bidder regarding Qualifications <u>Declaration by the Bidder</u>

In rel	ation to my/our	Bid	submitted to				for procure	men	ıt
of		in	response	to	their	Notice	inviting	Bid	ls
No	Dated		.I/we		hereby	declare	under Section	7 c	f
Rajas	than Transparenc	ey in I	Public Procure	ement Act.	2012 th	at :			

- 1. I/we possess the necessary professional, technical, financial and managerial resources and competence required by the Bidding Document issued by the Procuring Entry;
- 2. I/we have fulfilled my/our obligation to pay such of the taxes payable to the union and the state government or any local authority as specified in the Bidding Document.
- 3. I/we are not insolvent, in receivership, bankrupt or being wound up, not have my/our affairs administered by a court or a judicial officer, not have my/our business activities suspended and not the subject of legal proceedings for any of the foregoing reasons;
- 4. I/we do not have, and our directors and officers not have, been convicted of any criminal offence related to my/our professional conduct or the making of false statements or misrepresentations as to my/our qualifications to enter into a procurement contract within a period of three years preceding the commencement of this procurement process, or not have been otherwise disqualified pursuant to debarment proceedings;
- 5. I/we do not have a conflict of interest as specified in the Act, Rules and the Bidding Document, which materially affects fair competition;

Date:	Signature of bidder
Place:	Name:
	Designation:
	Address:

Annexure C: Grievance Redressed during Procurement Process

The designation and address of the First Appellate Authority is **Deputy Secretary**, Youth Affairs & Sports Department Govt. of Rajasthan. The designation and address of the Second Appellate Authority is **Principal Secretary**, Youth Affairs & Sports Department Govt. of Rajasthan, Jaipur.

(1) Filing an appeal:-

if any bidder or prospective bidder is aggrieved that any decision, action or omission of the procuring entity is in contravention to the provisions of the Act or the rules or the guidelines issued there under, he may file an appeal to First Appellate authority, as specified in the Bidding document within a period of ten days from the date of such decision or action, omission, as the case may be, clearly giving the specific ground or grounds on which he feels aggrieved:

Provided that after the declaration of a bidder as successful the appeal may be filed only by a bidder who has participated in procurement proceedings:

Provided further that in case a procuring entity evaluates the technical bids before the opening of the financial bids, an appeal related to the matter of financial bids may be filed only by a bidder whose technical bid is found to be acceptable.

- (2) The officer to whom an appeal is filed under Para (1) shall deal with the appeal as expeditiously as possible and shall endeavor to dispose it of within thirty days from the date of the appeal.
- (3) If the officer designated under Para (1) fails to dispose of the appeal filed within the period specified in Para (2), or if the bidder or prospective bidder or the procuring entity is aggrieved by the order passed by the first appellate authority, the bidder or prospective bidder or the procuring entity, as the case may be, may file a second appeal to second appellate authority specified in the bidding document in this behalf within fifteen days from the expiry of the period specified in Para (2) or of the date of receipt of the order passed by the first appellate authority, as the case may be.

(4) Appeals not to lie in certain cases:-

No appeal shall lie against any decision of the procuring entity relating to the following matters, namely:-

- (a) Determination of need of procurement
- (b) Provisions limiting participation of bidders in the bid process
- (c) The decision of whether or not to enter into negotiations
- (d) Cancellation of a procurement process
- (e) Applicability of the provisions of confidentiality

(5) Form of Appeals:-

- (a) An appeal under Para (1) or (3) above shall be in the annexed form along with as many copies as there are respondents in the appeal.
- (b) Every appeal shall be accompanied by an order appealed against, if any, Affidavit verifying the facts stated in the appeal and proof of payment of fee,
- (c) Every appeal may be presented to first appellate authority or second Appellate authority, as the case may be, in person or though registered post Or authorized representative.

(6) Fee for filing Appeal:-

- (a) Fee for first appeal shall be rupees two thousand five hundred and for second appeal shall be rupees ten thousand, which shall be non-refundable.
- (b) The fee shall be paid in the form of bank demand draft or banker's cheque of a scheduled bank in India payable in the name of appellate authority concerned.

(7) Procedure for disposal of Appeal:-

- (a) The first appellate authority or second appellate authority as the case may be, upon filing of appeal, shall issue notice accompanied by copy of appeal, affidavit and documents, if any, to the respondents and fix date of hearing
- (b) On the date fixed for hearing, the first appellate authority of second appellate authority, as the case may be shall-
 - (i) Hear all the parties to appeal present before him; and
 - (ii) Peruse or inspect documents, relevant records or copies thereof relating to the matter.
- (c) After hearing the parties, perusal or inspection of documents and relevant records or copies thereof relating to the matter, the appellate authority concerned shall pass an order in writing and provide the copy of order to the parties to appeal free of cost.
- (d) The order passed under sub-clause (c) above shall also be placed on the state public procurement portal.

Annexure D: Additional Conditions of Contract

1. Correction of arithmetical errors

Provided that a Financial Bid is substantially responsive, the Procuring Entity will correct arithmetical errors during evaluation of Financial Bids on the following basis:

- i. If there is a discrepancy between the unit price and the total price that is obtained by multiplying the unit price and quantity, the unit price shall prevail and the total price shall be corrected, unless in the opinion of the Procuring Entity there is an obvious misplacement of the decimal point in the unit price, in which case the total price as quoted shall govern and the unit price shall be corrected;
- ii. It there is an error in a total corresponding to the addition or subtraction of subtotals, the subtotals shall prevail and the total shall be corrected; and
- iii. If there is a discrepancy between words and figures, the amount in words shall prevail, unless the amount expressed in words is related to an arithmetic error, in which case the amount in figures shall prevail subject to (i) and (ii) above.

If the Bidder that submitted the lowest evaluated Bid does not accept the correction of errors, its Bid shall be disqualified and its Bid Security shall be forfeited or its Bid Securing Declaration shall be executed.

2. Procuring Entity's Right to Vary Quantities

- (i) At the time of award of contract, the quantity of Goods, Works or services originally specified in the Bidding Document may be increased or decreased by a specified percentage, but such increase or decrease shall not exceed Five percent, of the quantity specified in the Bidding Document. It shall be without any change in the unit prices or other terms and conditions of the Bid and the conditions of contract.
- (ii) If the Procuring Entity does not procure any subject matter of procurement or procures less than the quantity specified in the Bidding Document due to change in circumstances, the Bidder shall not be entitled for any claim or compensation except otherwise provided in the Conditions of Contract.
- (i) In case of procurement of Goods or services, additional quantity may be procured by placing a repeat order on the rates and conditions of the original order. However, the additional quantity shall not be more than 50% of the value of Goods of the original contract and shall be within one month from the date of expiry of last supply. If the supplier fails to do so, the Procuring Entity shall be free to arrange for the balance supply by limited Bidding or otherwise and the extra cost incurred shall be recovered from the supplier.

3. Dividing quantities among more than one Bidder at the time of award (In case of procurement of Goods)

As a general rule all the quantities of the subject matter of procurement shall be procured from the Bidder, whose Bid is accepted. However, when it is considered that the quantity of the subject matter of procurement to be procured is very large and it may not be in the capacity of the Bidder, whose Bid is accepted, to deliver the entire quantity or when it is considered that the subject matter of procurement to be procured is of critical and vital nature, in such cases, the quantity may be divided between the Bidder, whose Bid is accepted and the second lowest Bidder or even more Bidders in that order, in a fair, transparent and equitable manner at the rates of the Bidder, whose Bid is accepted.

राजस्थान राज्य क्रीडा परिषद

सवाई मानसिंह स्टेडियम, जनपथ, जयपुर

<u>कार्यालय दूरभाष नं0 0141—2744283, फैक्स नं0 0141—2740568, ईमेल आईडी—</u>rsscjaipur@gmail.com <u>बोली की शर्त</u>

विशेष टिप्पणी :- बोलीदाताओं को इन शर्तों को सावधानी पूर्वक पढ़ना चाहिए तथा अपनी ई-बोलियां भेजते समय इनकी पूर्ण रूपेण पालना करनी चाहिए।

- 1. तकनीकी प्रस्तावों में सफल बोलीदाताओं के ही वित्तीय प्रस्ताव खोले जावेगें जो निविदादाता तकनीकी बिड में सफल नहीं पाये गये उनकी वित्तीय बोली नहीं खोली जायेगी।
- 2. कोई भी फर्म / संवेदक यदि जी.एस.टी. अधिनियम के अन्तर्गत पंजीकृत नहीं है तो वह बोली नहीं देगा। इनके अभाव में बोलियों पर विचार नहीं किया जायेगा। जी. एस. टी. देयता प्रमाण पत्र मार्च, 2025 का संलग्न करना आवश्यक है।
- 3. दरें जी.एस.टी. तथा केन्द्र व राज्य सरकार द्वारा देय समस्त करों सहित देनी होगी।
- 4. बोली ऑन-लाईन प्रस्तुत की जावेगी एवं निर्दिष्ट कॉलमों में प्रविष्टी की जावेगी।
- 5. दरें गन्तव्य स्थान तक एफ.ओ.आर. सवाई मानसिंह स्टेडियम जयपुर के आधार पर होगीं अर्थात परिवहन संबंधी कोई राशि परिषद द्वारा पृथक से देय नहीं होगी।
- 6. बोलियां उपापन अधिनियम / पारदर्शिता अधिनियम के तत्संबंधी प्रावधानों (धारा—28 आदि) के अध्यधीन रहते हुये उनके खोले जाने की दिनांक से एक वर्ष की अवधि के लिए विधि मान्य होंगी।
- 7. बोलीदाता अपनी संविदा या उसके किसी भाग को किसी अन्य एजेन्सी के लिए नहीं सौंपेगा या उपभाडे पर नहीं देगा।
- 8. बोलीदाता का उसके प्रतिनिधि की ओर से प्रत्यक्ष अथवा अप्रत्यक्ष रूप से अपना पक्ष समर्थन करना एक प्रकार की अनर्हता होगी। हित विरोधी धारा 80 होगी।
- 9. विहित समय एवं तारीख के पश्चात् जो भी बोलियां प्राप्त होंगी उन्हें किसी स्थिति में स्वीकार नहीं किया जावेगा।
- 10. यदि बोलीदाता ऐसी कोई शर्त आरोपित करता है जो उसमें वर्णित शर्तों के अतिरिक्त है या उनके विरोध में है तो उसकी बोली को संक्षिप्त रूप में कार्यवाही कर रद्द कर दिया जावेगा।
- 11. तकनीकी बोली के साथ बोलीदाता को निम्न दस्तावेज संलग्न करने अनिवार्य होगे (जिसके आधार पर तकनीकी बिड का मूल्याकंन किया जायेगा) :-
 - i. बोली में अंकित पते के प्रमाण हेतु पानी/बिजली/टेलीफोन/मोबाईल के बिल, पेन कार्ड, पासपोर्ट, आधार कार्ड अथवा ड्राईविंग लाईसेन्स में से कोई एक की प्रमाणित छाया प्रतियां।
 - i. बोलीदाता / फर्म का विगत 3 वित्तीय वर्षों (2021–22, 2022–23 एवं 2023–24) में औसत वार्षिक टर्न ओवर 25.00 लाख से कम नही होना चाहिये। इस हेतु बोलीदाता को उक्त वर्षों का सीए से प्रमाणित प्रमाण पत्र की प्रति मय यूडीआई नम्बर सहित संलग्न करनी होगी।
 - ii. गत 3 वर्षों (2021–22, 2022–23 एवं 2023–24) में राजकीय विभागों में किये गये ज्योनरी कार्य का एकल कार्य आदेश 20.00 लाख या उससे अधिक, दो कार्य आदेश 12.50 लाख एवं तीन कार्य आदेश 10.00 लाख तक होना आवश्यक है। इसके प्रमाणीकरण हेतु कार्यादेश एवं कार्य के

- सन्तोषजनक होने का प्रमाण पत्र आदि आवश्यक दस्तावेज संलग्न करने होगे।
- iii. बोलीदाता को माल एवं सेवाकर (GST) के रजिस्ट्रेशन की प्रति संलग्न करनी होगी।
- iv. अमानत राशि एवं बोली प्रपत्र शुल्क का डी.डी. संलग्न करना होगा।

12. बयाना राशि :-

- (क) बोली से पूर्व (2% बोली सूचना के अनुसार) नियमानुसार बयाना राशि ऑन—लाईन प्रस्तुत की जायेगी। इसके बिना बोलीओं पर विचार नहीं किया जायेगा। यह राशि सचिव, राजस्थान राज्य क्रीड़ा परिषद, जयपुर के पक्ष में बैंक ड्राफ़ट / बैंकर्स चैक में से किसी रूप में जमा करायी जा सकती है।
- (ख) असफल बोलीदाता की बयाना राशि बोली को अंतिम रूप से स्वीकार करने के बाद यथा संभव शीघ्र लौटा दी जावेगी।
- (ग) अनुमोदन की प्रतीक्षा करने वाली या रद्द की गई या संविदाओं के पूर्ण हो जाने के कारण परिषद कार्यालय के पास जमा बयानाराशि / प्रतिभूति निक्षेप को नवीन निविदा के लिए बायाना राशि / प्रतिभूति राशि के प्रति समायोजित नहीं किया जायेगा।
- 13. **बयाना राशि का समपहरण**:— बयाना राशि को निम्नलिखित मामलों में समपहरत कर लिया जायेगा:—
 - (क) जब बोलीदाता बोली खोलने के बाद किन्तु बोली को स्वीकार करने के पूर्व प्रस्ताव को वापस लेता है या उसमें उपान्तरण करता है।
 - (ख) जब बोलीदाता विर्निष्ट समय के भीतर विहित करार को निष्पादित नहीं करता है।
 - (ग) जब बोलीदाता प्रदायगी के लिए आदेश देने के बाद प्रतिभूति राशि जमा नहीं कराता हो।
 - (घ) जब वह निर्धारित समय के अन्तर्गत आदेशों के अनुसार कार्य करने में असफल रहता है अथवा संतोषजनक सेवाएं देने में असमर्थ रहता है।

14. करार एवं प्रतिभृति निक्षेप :-

- (क) सफल बोलीदाता को आदेश दिनांक से 7 दिन की अवधि के भीतर नियमानुसार मूल्य के नॉन ज्यूडिशियन स्टॉम्प पेपर पर (जिसका व्यय स्वयं बोलीदाता द्वारा वहन किया जावेगा) एक करार—पत्र निष्पादित करना होगा तथा प्रावधित मूल्य जिसके लिए बोली स्वीकार की गई है।
- (ख) बोली के समय जमा कराई गई बयाना राशि को प्रतिभूति की राशि के लिए समायोजित किया जायेगा।
- (ग) बयाना / प्रतिभूति राशि पर परिषद द्वारा कोई ब्याज का भुगतान नहीं किया जायेगा।
- (घ) प्रतिभूति राशि के रूप में नकद रसीद पत्र/शिड्यूल बैंक का ड्राफ्ट/ बैंकर्स चैक मान्य होंगे।
- 15. प्रतिभूति राशि का समपहरण :— प्रतिभूति की राशि को पूर्ण अथवा आंशिक रूप से निम्नलिखित मामलों में समपहरत किया जायेगा:—
 - (क) जब संविदा की किसी शर्त / अथवा शर्तों का उल्लंघन किया गया हो।
 - . (ख) जब बोलीदाता सम्पूर्ण कार्य संतोषजनक ढंग से करने में असफल रहा हो।
 - (ग) प्रतिभूति निक्षेप को समपहरत करने के मामले में युक्तियुक्त नोटिस दिया जावेगा इस सम्बन्ध में परिषद के अधिकारी का निर्णय अन्तिम होगा।

- (घ) कार्य में असफल रहने पर परिषद द्वारा वैकल्पिक व्यवस्था किये जाने पर उसमें जो भी व्यय होगा बोलीदाता से उसकी प्रतिभूति राशि में से अथवा उसको देय बिल की राशि के भुगतान में से की जायेगी। यदि वसूली करना सम्भव न हो तो राजस्थान पी.डी.आर.एक्ट या प्रवृत्त अन्य किसी कानून के अन्तर्गत कार्यवाही की जावेगी।
- 16. करार पत्र को पूर्ण करने एवं उस पर स्टाम्प लगाने का व्यय बोलीदाता द्वारा वहन किया जायेगा तथा परिषद को उस करार पत्र की निष्पादित स्टाम्प शुदा प्रति पड़त निःशुल्क प्रस्तुत की जायेगी।
- 17. परिषद के प्राधिकृत अधिकारी या उसका विधिवत् प्राधिकृत प्रतिनिधि सभी युक्तियुक्त उचित समयों पर ठेकेदार के परिसर में जायेगा तथा वह विनिर्माण की प्रक्रिया के दौरान या उसके बाद जैसे भी हो किसी भी समय सामग्री का निरीक्षण एवं जांच करने की शक्ति रखेगा।
- 18. परीक्षण प्रभार परिषद द्वारा वहन किये जायेंगे। यदि बोलीदाता अत्यावश्यक तत्काल परीक्षण कराना चाहता है या यदि परिणामों से यह ज्ञात होता है कि प्रदाय किया गया सामान विहित स्तरों या विनिर्देशों के अनुसार नहीं है तो परीक्षण प्रभार बोलीदाता द्वारा वहन किये जायेंगे।
- 19. अनुमोदित कार्य के लिए यह समझा जाएगा कि उसने कार्य किये जाने वाले विनिर्देशों की सावधानीपूर्वक जांच कर ली है यदि उसे इन शर्तों, विनिर्देशों, रेखाचित्रों आदि के किसी भाग के आशय के बारे में कोई सन्देह हो तो वह संविदा पर हस्ताक्षर करने से पूर्व परिषद से स्पष्टीकरण प्राप्त करेगा।
- 20. सफल बोलीदाता को कार्य आदेश जारी तिथि के 10 दिवस के अन्दर कार्य प्रारम्भ करना होगा।
- 21. यदि निविदा सूचना में दर्शित मात्रा से अधिक के लिए आदेश दिया जाता है, तो निविदादाता अपेक्षित कार्य करने के लिए बाध्य होगा। पुनः आदेश भी निविदा में दी गयी शर्तों पर दिए जा सकेंगें परन्तु शर्त यह है, कि ऐसे पुनआदेश मूल रूप से खरीदी गयी मात्रा की 50 प्रतिशत तक के अतिरिक्त प्रदाय के लिए ही होगें।
- 22. <u>गारन्टी</u> :--गारन्टी नियमानुसार होगी।

23. परिसमापित नुकसानी :--

- (1) परिसमापित नुकसानी के साथ कार्य अवधि में वृद्धि करने के मामले में, वसूली राजस्थान लोक उपापन पारदर्शिता अधिनियम, 2012 एवं राजस्थान लोक उपापन पारदर्शिता नियम 2013 के प्रावधान अनुसार होगी।
- (2) यदि प्रदायकर्ता किन्ही बाधाओं के कारण संविदान्तर्गत कार्य का प्रदाय पूरा करने के लिए समय में वृद्धि कराना चाहता है, तो वह लिखित में परिषद को आवेदन करेगा। किन्तु वह उसके लिए निवेदन बाधा के घटित होने पर तुरन्त उसी समय करेगा न कि प्रदाय पूर्ण होने की निर्धारित तारीख के बाद करेगा।
- (3) यदि कार्य प्रदाय करने में उत्पन्न हुई बाधा बोलीदाता के नियन्त्रण से परे कारणों से हुई हो तो कार्य की अवधि में वृद्धि परिसमापित नुकसानी सहित या रहित की जा सकेगी।
- 24. वसूली :—परिसमापित नुकसानी, कम प्रदाय, टूट—फूट, रद्द की गई वस्तुओं के लिए वसूली साधारण रूप से बिल में से की जाएगी। संवेदक कम प्रदाय, टूट—फूट, रद्द किए गए कार्यों की सीमा तक राशि को भी रोका जा सकेगा तथा यदि सेवा सन्तोषजनक ढंग से उनको कार्य करता है तो परिसमापित

नुकसानी के साथ वसूली उसे देय राशि एवं विभाग के पास उपलब्ध प्रतिभूति निक्षेप से की जाएगी। यदि वसूली करना सम्भव न हो तो राजस्थान पी डी आर एक्ट या प्रवृत्त अन्य कानून के अन्तर्गत कार्रवाई की जाएगी।

<u> 25. भुगतान</u> :--

- (क) बोलीदाता द्वारा क्रेता अधिकारी को उचित प्रारूप में लोक उपापन नियमों के अनुसार बिल प्रस्तुत करने पर भुगतान किया जायेगा। सभी प्रेषण प्रभार बोलीदाता द्वारा वहन किये जायेंगे। किसी भी सूरत में अग्रिम भुगतान नहीं किया जायेगा।
- (ख) विवादास्पद मदों में राशि का 10 प्रतिशत से 25 प्रतिशत तक को रोका जायेगा तथा उस विवाद का निपटारा हो जाने पर उसका भुगतान कर दिया जायेगा।
- (ग) उन मामलों में, जिनमें परीक्षण करने की जरूरत है, भुगतान तभी किया जायेगा जब उनका परीक्षण कर लिया जाये तथा प्राप्त हुए परीक्षण परिणाम विहित निर्देशों के अनुरूप हों।
- 26. यदि कार्य की तात्कालिक आवश्यकता के कारण पूर्ण या आंशिक रूप में उन कार्यों को बदलना साध्य नहीं समझा जाए तो राजस्थान राज्य क्रीडा परिषद द्वारा बोलीदाता को सुनवाई किये जाने का एक उचित अवसर देकर, ऐसे कारणों से जो अभिलिखित किये जायेंगे, अनुमोदित दरों में से उपयुक्त राशि की कटौती करेगा। इस प्रकार की गई कटौती अन्तिम होगी।
- 27. निविदादाता करार को निष्पादित करते समय निम्नलिखित दस्तावेज प्रस्तुत करेगा :--
 - (i) यदि भागीदारी फर्म हो तो "पार्टनरशिप डीड" की अनुप्रमाणित प्रति।
 - (ii) यदि भागीदारी फर्म रजिस्ट्रार ऑन फर्म्स के पास पंजीकृत हो तो पंजीयन संख्या एवं उसका वर्ष।
 - (iii) एक मात्र स्वामित्तव के मामले में आवास एवं कार्यालय का पता, टेलीफोन नम्बर।
 - (iv) कम्पनी के मामले में कम्पनी के रजिस्ट्रार के द्वारा जारी किया गया प्रमाण–पत्र।
- 28. संविदा के निर्वचन, आशय या संविदा की शर्तों के उल्लंघन के सम्बन्ध में या अन्य किसी भी प्रकार का विवाद होने पर परिषद का निर्णय अन्तिम होगा।
- 29. समस्त विधिक कार्यवाहियां यदि संस्थित किया जाना आवश्यक हो तो जयपुर स्थित न्यायालय में ही की जाएगी। अन्यत्र नहीं की जाएगी।
- 30. बोलीदाता द्वारा अपलोड किये जाने वालो दस्तावेजों पर नम्बरिंग होनी चाही एवं चैक लिस्ट भर कर प्रस्तुत करनी होगी।
- 31. सचिव, राजस्थान राज्य क्रीडा परिषद, जयपुर को बिना कारण बताये किसी भी बोली़ को स्वीकार / अस्वीकार करने का अधिकार होगा।
- 32. जी.एफ. एण्ड ए.आर.,राजस्थान लोक उपापन पारदर्शिता अधिनियम, 2012 एवं राजस्थान लोक उपापन पारदर्शिता नियम 2013 के प्रावधान लागू होगें।

बोलीदाता के हस्ताक्षर (मय नाम पता एवं मोहर)

घोषणा

मैने / हमने सवाई मानसिंह स्टेडियम, जयपुर में ज्योनरी मरम्मत कार्य हेतु (मय सामग्री) की बोली के नियम एवं शर्तो को भली—भॉति पढ व समझ लिया है। मुझे / हमारी फर्म को किसी भी विभाग द्वारा ब्लेक—लिस्ट नहीं किया गया है। इन शर्ती एवं नियमों के अधीन मैं / हम उक्त कार्य करने हेतु सहमत एवं वचनबद्व हूं / है। यदि मेरे / हमारे द्वारा की किसी बोली की शर्तों, नियमों अथवा आदेशों का उल्लंघन किया जावेगा तो सक्षम अधिकारी द्वारा मेरे / हमारे विरुद्ध बोली के नियम / शर्तों के उल्लंघन की कार्यवाही करने के लिए अधिकृत होगा। इस सम्बन्ध में मुझे / हमें सक्षम / अधिकृत अधिकारी द्वारा लिया गया निर्णय मान्य होगा तथा इसमें मुझे / हमको कोई आपत्ति / हस्तक्षेप नहीं है।

हस्ताक्षर बोलीदाता
नाम / पता
,
टेलीफोन नं.
दिनांक

General Instructions for Filling of Bid

The complete bidding document has been published on the website www.rssc.in, http://sppp.raj.nic.in, http://eproc.raj.gov.in, for the purpose of downloading.

- 1. Bidders who wish to participate in this bidding process must register on www.rssc.in & http://sppp.raj.nic.in,
- 2. To participate in online bidding process, Bidders must procure a Digital Signature Certificate (Type III) as per Information Technology Act-2000 using which they can digitally sign their electronic bids. Bidders can procure the same from any CCA approved certifying agency, i.e. TCS, safe crypt, Node etc. Bidders who already have a valid Digital Signature Certificate (DSC) need not procure a new DSC.
- 3. Bidder (authorized signatory) shall submit their offer on-line in Electronic formats both for Technical and financial proposal. However, DD for Tender Fees, EMD payable in favor of SECRETARY RAJASTHAN STATE SPORTS COUNCIL, JAIPUR, payable at Jaipur and Processing Fees payable in favor of Managing Director, RAJCOMP Info Services Limited, payable at JAIPUR. Tender fee, EMD and processing fee DD should be submitted physically at the office of RAJASTHAN STATE SPORTS COUNCIL, JAIPUR, and Scanned copy of same should also be uploaded along with the technical bid.
- 4. RAJASTHAN STATE SPORTS COUNCIL, JAIPUR will not be responsible for delay in online submission due to any reason. For this, bidders are requested to upload the complete bid well advance in time so as to avoid Last hours issues like slow speed; choking of web site due to heavy load or any other unforeseen problems.
- 5. Bidders are also advised to refer "Bidders Manual Kit" available at e-Proc website for further details about the e-tendering process.
- 6. No contractual obligation, whatsoever shall arise from the bidding process unless and until a formal contract is signed and executed between the tendering authority and the successful Bidder.

SECRETARY

UNDERTAKING BY THE BIDDER

This is to certify that I/we before signing this tender have read and fully understood all the terms and conditions contained herein and undertake myself/ourselves to abide by them. I/We have signed all the pages in acceptance of the terms and conditions.

I/We also undertake that I/We will not adopt any malpractices at any stage of bidding/execution.

Signature of the Bidder with Seal Name:
Designation:
Address:

BIDDER'S AUTHORIZATION CERTIFICATE {to be filled by the bidder}

	ering Authority},				
n}	hereby	declare/			
relevar RAJAS He/ Si inform	nt documents or STHAN STATE he is also author nation/clarification purpose of valid	Name/ n behalf of the of SPORTS COUNC. orized to attend to ons as may be requilation, his/ her veri hanking you,	company/ firm IL, JAIPUR. meetings & su ired by you in the company of the company	in dealing v bmit technica he course of p	with Tender with
Author	of the Bidder: - rized Signatory: - f the Organization			Veri	fied Signature:

CHECKLIST OF DOCUMENTS SUBMITTED

S.	Documents to be submitted	Submitted	Not	Page No.
No.			Submitted	
1.	Scanned Copies of tender document fee, EMD			
	and processing fees			
2.	Copy of Registration of firms (F-1 and Above			
	category for Joinery/Furniture works,			
	Registration under Govt. Departments of			
	Rajasthan /India).			
3.	Copy of GST Registration			
<u>4.</u> 5.	Copy of PAN Card Proof of Work order and Satisfactory			
٥.	, and the second se			
	Completion of Joinery work should be as per			
	tender document condition no. 11 (iii) in			
	financial Year 2021-22, 2022-23 & 2023-24.			
6.	Certificate from Chartered Accountant having			
	UDIN for the proof of average annual			
	Turnover that must be equal/more than the cost of work (bid cost) in the last three Financial			
	Years from 2021-22, 2022-23 & 2023-24.			
7.	Annexure A to D duly signed in context to			
	RTPP Rules-2013.			
8.	Authorization certificate If the tender is signed			
	other than owners			
9.	Copy of GST paid certificate filed by March,			
	2025 Financial Year 2024-25 in GSTR-3B			
	Performa			
10.	Tender document and Technical Bid and			
	undertaking all three duly signed			
11.	Any other Document			

Note: -1. The work executed under Govt. /Semi-Govt. / Autonomous Departments shall be considered for experience purposes.

- 2. Similar nature shall mean works related to Joinery/Furniture works.
- 3. Last Three FY for works means 2021-22, 2022-23 & 2023-24.
- 4. Last three FY for average annual turnover means 2021-22, 2022-23 & 2023-24.
- 5. The contractor should ensure that the Registration should be latest or updated.

Signature of Bidder Seal of Establishment Full Name of Bidder with address and date

Schedule "G"

Name of work :- Joinery Work at Sawai Man Singh Stadium, Jaipur..

S. No.	() liantity		Praticular	Rate	e	Amount	
1	1.00	Cum	Providing & fixing door, window, chowkhats and other frames, including antitermite treatment, M.S. flat, hold fasts of size 250 x 40 x 3mm fixed with M.S. bolt 5mm dia 50mm long duly embedded in cement concrete M-15 grade: Ivory coast wood Grade I	135533.00	P.Sqm	135533.00	
2	1.00	Cum	Providing and fixing fully panelled/partly panelled/ double leaf shutter frames for doors as per approved design and drawings with approved ordinary C.P./ oxidised steel fittings as per Annexure - 'A' and width of styles & top rails of 100mm and lock rails width of 150mm and bottom rails of 200mm width including teak wood beading of size 19mm x 12mm on both faces complete : Ivory coast wood grade I	3345.00	P.Sqm	3345.00	
3	1.00	Sqm	30 mm thickIvory coast wood grade I	2957.00	P.Sqm	2957.00	
4	1.00	Sqm	Providing and fixing fully panelled /partly panelled double leaf shutters frame for windows and ventilators as per approved design and drawings with approved steel fittings as per Annexure 'A' and width of styles, bottom and top rails 75mm including intermediate rails 50mm wide, beading of 25mm x 15mm size on both faces: 35 mm thick Ivory coast wood grade I	2976.00	Sqm	2976.00	
5	1.00	Sqm	Providing and fixing fully panelled /partly panelled double leaf shutters frame for windows and ventilators as per approved design and drawings with approved steel fittings as per Annexure 'A' and width of styles, bottom and top rails 75mm including intermediate rails 50mm wide, beading of 25mm x 15mm size on both faces: 30 mm thick Ivory coast wood grade I	2627.00	P.Sqm	2627.00	
6			Providing and fixing wood panelling or panelling and glazing in panelled or panelled and glazed shutters for doors, windows and clerestory windows (Area of opening for panel inserts excluding portion inside grooves or rebates to be measured). Panelling for panelled and glazed shutter 25 mm to 40 mm thick				
i	1.00	Sqm	IS 710- 1976 marked 9 mm thick Teak BWR ply both side	1821.00	Sqm	1821.00	
ii	1.00	Sqm	IS 710- 1976 marked 12 mm thick Teak ply BWR one side	1821.00	Sqm	1821.00	
iii	1.00	Sqm	IS 710- 1976 marked 12 mm thick Teak ply BWR both side	2074.00	Sqm	2074.00	
iv	1.00	Sqm	SS wire gauge 14 mesh x 24 gauge	927.00	Sqm	927.00	
V	1.00	Sqm	5 mm float glass	1020.00	Sqm	1020.00	
vi	1.00	Sqm	8 mm thick glass	1445.00	Sqm	1445.00	
vii	1.00	Sqm	6 mm thick glass	1694.00	Sqm	1694.00	
viii	1.00	Sqm	12 mm thick glass	2755.00	Sqm	2755.00	
ix	1.00	Sqm	5 mm tinted glass	1628.00	Sqm	1628.00	
7	1.00	Sqm	Extra for providing frosted glass panes instead of ordinary float glass panes in doors, windows and clerestory window shutters. (Area of opening for glass panes excluding portion inside rebate shall be measured).	306.00	Sqm	306.00	
8	1.00	Per mm Per Sqm	Extra for providing toughened glass panes instead of ordinary float glass panes in doors, windows and clerestory window shutters. (Area of opening for glass panes excluding portion inside rebate shall be measured).	50.00	Per mm Per Sqm	50.00	

9	1.00	Sqm	Providing and fixing external grade board solid core single leaf flush door shutters ISI 2202-67 marked using Phenol formal dehyderesin in glue both sides with approved steel fittings complete as per annexure 'A' : 30 mm thick , Commercial Veneer both side	1841.00	P.Sqm	1841.00
10	1.00	Sqm	Extra for providing external lipping with 2nd class teak wood battens 6 mm minimum depth on all edges of shutters (over all area of door shutter to be measured) Over item no. 8.13.	141.00	P.Sqm	141.00
11	1.00	Sqm	Extra for providing other type of fittings as mention in annexure A (as approved by EI): Stainless steel fittings	10%	Sqm	0.10
12	1.00	Sqm	Providing and fixing wall panelling using soft wood frame of size 50x25mm @600 mm c/c in both directions duly treated with anti-termite treatment making grooves painting of grooves specification and drawing using : 12 mm thick one side laminated board Practical board (Phenol bonded)	1748.00	Sqm	1748.00
13	1.00	Sqm	Providing and fixing 50 mm thick resin bounded glass wool 32 kg/cum density wrapped in julities cloth bag (box type) and held in position using chicken mesh	560.00	Sqm	560.00
14	1.00	Sqm	Providing and fixing Hassian cloth of approved colour and texture over soft wood frame glass wool & fibre glass tissue paper	312.00	Sqm	312.00
15			Providing and fixing expandable fastners of specified size with necessary plastic sleeves and galvanised M.S. screws including drilling holes in masonry work /CC/R.C.C. and making good etc. complete			
i	1.00	Sqm	25 mm long	13.00	Sqm	13.00
ii	1.00	Sqm	32 mm long	17.00	Sqm	17.00
iii	1.00	Sqm	40 mm long	18.00	Sqm	18.00
iv	1.00	Sqm	50 mm long	19.00	Sqm	19.00
16	1.00	Sqm	Providing and fixing Nigeria / Ghana /Ivory Coast Teak wood grade-I mouldings and beadings in doors and windows size :-50x20 mm	127.00	Sqm	127.00
17	1.00	Mtr.	Providing and fixing curtain rods of 1.25 mm thick chromium plated brass plate, with two chromium plated brass brackets fixed with C.P. brass screws and wooden plugs, etc., wherever necessary complete: 20 mm	266.00	Mtr.	266.00
18	1.00	No.	Providing and fixing IS: 3564 marked aluminium extruded section body tubular type universal hydraulic door closer with double speed adjustment with necessary accessories and screws etc. complete.	1478.00	Each	1478.00
19	1.00	Rm	Providing and fixing wooden moulded corner beading of triangular shape to the junction of panelling etc. with iron screws, plugs and priming coat on unexposed surface etc. complete 2nd class teak wood. 50x50mm (base and height)	182.00	Rm	182.00
20	1.00	Each	Providing and fixing Almirah lock (50 to 70 mm size)of approved make without pair of handles for door with necessary screws etc complete as per direction of Engineer-in-charge.	150.00	Each	150.00

21	1.00	Sqm	Providing & Fixing of ward robe shutters made out of 19mm thick BWP block board ISI of superior quality make with following details: Front side finishing with 1mm thick superior quality mica approved make and 0.8mm thick approved shade mica in the inner side. Covering with teak wood beading 25x12mm all the sides of shutter & 35x12mm on outer frame for making good the wall joint including heavy brass S.S. fittings (Handle 200mm 2 Nos., Tower Bolt 150mm 2 Nos., Brass Lock 1 Nos., Magnetic Catcher 2 Nos., Brass Hinges 75x40x2.5 mm 6 Nos., SS Hanger Rod 20mm dia) complete as per drawing and design approved by Engineer in Charge.	5571.00	Sqm	5571.00
22	1.00	Sqm	Providing & Fixing mica of approved make for inner/outer side of shutters with fevicol & nails complete as per approved by engineer in charge. 0.8mm thick mica	762.00	Sqm	762.00
23	1.00	Sqm	Providing & Fixing decorative veneer of approved make for inner/outer side of shutters with fevicol & nails complete as per approved by engineer in charge. 4.0mm thick veneer	1434.00	Sqm	1434.00
24	1.00	Rmt.	Providing and fixing S.S. Rod 30mm dia (304 grade ,16SWG) including brackets fixed with C.P. brass screws and rawl plugs, etc., wherever necessary complete two side central all fittings.	650.00	Rmt.	650.00
25	1.00	Sqm	Providing & Fixing BWR ISI marked 19 mm board of approved make for making wardrobe/shelves and other furniture with fevicol & nails complete as per approved by engineer in charge.	1350.00	Sqm	1350.00
26			Providing & Fixing Commercial Ply as per IS 710: 1976 BWR of approved make for making wardrobe/shelves and other furniture with fevicol & nails complete as per approved by engineer in charge.			
i	1.00	Sqm	18 mm thick	1350.00	Sqm	1350.00
ii	1.00	Sqm	12 mm thick	1031.00	Sqm	1031.00
iii	1.00	Sqm	6 mm thick	850.00	Sqm	850.00
27			Providing & Fixing telescopic channel of approved make for drawers with screws complete as per approved by engineer in charge.			
i	1.00	Each	300mm long	426.00	Each	426.00
ii	1.00	Each	400mm long	513.00	Each	513.00
iii	1.00	Each	450mm long.	563.00	Each	563.00
iv	1.00	Each	500mm long	628.00	Each	628.00
V	1.00	Each	600mm long	751.00	Each	751.00
28			Providing & Fixing drawer handle of approved make for drawers with screws complete as per approved by engineer in charge.			
i	1.00	Each	100mm long	159.00	Each	159.00
ii	1.00	Each	150mm long	195.00	Each	195.00
29	1.00	Each	Providing & Fixing drawer lock of approved make for drawers with screws complete as per approved by engineer in charge.	448.00	Each	448.00

30	1.00	Sqm	Providing and fixing of double leaf steel shutter for cupboard, the frame is made of pressed steel ISI section 80x25 mmx 1.25 mm thick with 1.00 mm MS sheet to spot welded including holdfasts of 15x3mm, MS oxidized fittings such as butt hinges, sliding doors bolts, handles, tower bolts and twin peg etc complete including applying priming coat of approved steel primer of red oxide zinc chromate and spray painting in approved shade with deco paint of approved quality complete as per direction of Engineer In Charge	3895.00	Sqm	3895.00
31	1.00	Sqm	Providing and fixing 15 mm thick densified tegular edged eco friendly light weight calcium silicate false ceiling tiles of approved texture as per direction of Engineer-in-charge of size 595 X 595 mm in true horizontal level suspended on inter locking metal grid of hot dipped galvanized steel sections (galvanizing @120 grams per sqm) consisting of main 'T' runner suitably spaced at joints to get required length and size of 24X38mm made from 0.33 mm thick (minimum) sheet, 1200mm centre to centre, and cross 'T' of size 24X32mm made out of 0.33mm (Minimum) sheet, 1200mm long spaced between main 'T' at 600mm centre to centre to form a grid of 1200X600mm and secondary cross 'T' of length 600mm and size 24X32mm made out of 0.33 mm thick (Minimum) sheet to be interlocked at middle of the 1200X600mm panel to form grid of size 600X600mm resting on periphery walls/partitions on a perimeter wall angle pre-coated steel of size (24X24X3000mm made of 0.40mm thick (minimum) sheet with the help of rawl plugs at 450mm centre to centre with 25mm long dry wall screws @ 230mm interval and laying 15mm thick densified edged calcium silicate ceiling tiles of approved texture in the grid including cutting /making opening for services like diffusers, grills, light fitting, fixtures, smoke detectors etc., wherever required, Main 'T' runners to be suspended from ceiling using 50 mm long M 6 dash fasteners, 6mm G.I. fully threaded rods with galvnised steel L cleat level adjusters of size 80x25x2mm, spaced at 1200mm centre to centre long main 'T' bottom exposed with 24mm of all T-sections shall be pre-painted with polyster baked paint, for all heights, as per specifications, drawing and as directed by engineer-in-charge. Note: Only calcium silicate false ceiling area will be measured from wall to wall. No deduction shall be made for exposed frames/opening (cut outs)having area less than 0.30 Sqm. The calcium silicate ceiling tiles shall have NRC. Value 0.50 (Minimum), light reflection> 85% non-combustible as per B.S. 476 part IV, 100% humi	1650.00	Sqm	1650.00

Providing and fixing of Un perforated Antibacterial Metal Tile Ceiling System comprising of Tile of 600mm wide and 600mm long manufactured out of 0.7mm thick aluminium alloy 3105 with beveled edge of 4.15mm width height of 32mm. The Tile will be manufactured on advanced equipment that includes several leveling stages in the manufacturing process by approved manufacturers. Tile ends will be raised with pips and slops to ensure positive engagement into the spring to enable for de-mounting of individual panels. The Tile sides will be sufficiently high to ensure a minimum deflection across the length of Tile. All Tiles will be bevel edged. The Tile shall be epoxy polyester powder coating with ANTIBAC in white colour which is in compliant to ROHS directive. The Tile shall be clipped into clip in rail of 0.5mm thick GI. in form of a grid system using a cross connector. The clip in rail shall be supported from slab by means of rigid Suspension of 4mm G. I rod, Hold on Clamp with Clip. POWDER COATING SPECIFICATION: Aluminium PANELS, cleaned through eco friendly cleaning ,process and powder applied thru electrostatic charged Automatic Carona technology spray guns and cured in combination of Infrared & hot air oven in a certified plant as Akzo International approved applicator. Providing and Fixing Cushion Vinyl/Fully flexible Vinyl Flooring confirming to 1.53462 Flooring of approved make with fibre base using rubber base adhesives including rolling with light wooden roller complete: 2.0 mm thick. Renewing glass panes, with putty and nails wherever necessary: Float glass panes of thickness 4 mm Renewing glass panes with wooden fillets wherever necessary: 4mm thick plain glass panes. Renewing glass panes and refixing existing wooden fillets: Amm thick plain glass panes. Renewing glass panes and refixing existing wooden fillets: Amm thick plain glass panes.	32	1.00	Sqm	Providing and fixing of perforated Metal Tile Ceiling System comprising of Tile of 600mm wide and 600mm long manufactured out of 0.7mm thick aluminium alloy 3105 with beveled edge of 4.15mm width height of 32mm. The tiles shall be perforated to 1.5mm dia with open area of 23%. The Tile will be manufactured on advanced includes several leveling stages in the manufacturing process by approved manufacturers. Tile ends will be raised with pips and slops to ensure positive engagement into the spring to enable for demounting of individual panels. The Tile sides will be sufficiently high to ensure a minimum deflection across the length of Tile. All Tiles will be bevel edged. The Tile shall be epoxy polyester powder coating in white colour. The Tile shall be clipped into clip in rail of 0.5mm thick GI. in form of a grid system using a cross connector. The clip in rail shall be supported from slab by means of rigid Suspension of 4mm G .I rod, Hold on Clamp with Clip. POWDER COATING SPECIFICATION: Aluminium PANELS, cleaned through eco friendly cleaning ,process and powder applied through electrostatic charged Automatic Carona technology spray guns and cured in combination of Infrared & hot air oven in a certified plant as Akzo International approved applicator .	3775.00	Sqm	3775.00
341.00SqmFlooring confirming to I.S3462 Flooring of approved make with fibre base using rubber base adhesives including rolling with light wooden roller complete : 2.0 mm thick.990.00Sqm990.00351.00SqmRenewing glass panes, with putty and nails wherever necessary: Float glass panes of thickness 4 mm617.00P.Sqm617.00361.00SqmRenewing glass panes with wooden fillets wherever necessary: 4mm thick plain glass panes.765.00Sqm765.00371.00SqmRenewing glass panes and refixing existing wooden fillets: 4mm thick plain glass panes.636.00P.Sqm636.00381.00Rmt.Renewal of old putty of glass panes (length)18.00P.Rmt.18.00	33	1.00	Sqm	Tile Ceiling System comprising of Tile of 600mm wide and 600mm long manufactured out of 0.7mm thick aluminium alloy 3105 with beveled edge of 4.15mm width height of 32mm. The Tile will be manufactured on advanced equipment that includes several leveling stages in the manufacturing process by approved manufacturers. Tile ends will be raised with pips and slops to ensure positive engagement into the spring to enable for de-mounting of individual panels. The Tile sides will be sufficiently high to ensure a minimum deflection across the length of Tile. All Tiles will be bevel edged. The Tile shall be epoxy polyester powder coating with ANTIBAC in white colour which is in compliant to ROHS directive. The Tile shall be clipped into clip in rail of 0.5mm thick GI. in form of a grid system using a cross connector. The clip in rail shall be supported from slab by means of rigid Suspension of 4mm G. I rod, Hold on Clamp with Clip. POWDER COATING SPECIFICATION: Aluminium PANELS, cleaned through eco friendly cleaning ,process and powder applied thru electrostatic charged Automatic Carona technology spray guns and cured in combination of Infrared & hot air oven in a certified plant	4117.00	Sqm	4117.00
36 1.00 Sqm Renewing glass panes with wooden fillets wherever necessary 1.00 Sqm Renewing glass panes with wooden fillets wherever necessary 1.00 Sqm Renewing glass panes and refixing existing wooden fillets 636.00 P.Sqm 636.00 Renewing glass panes 1.00 Rmt. Renewal of old putty of glass panes (length) 18.00 P.Rmt. 18.00 Rmt. 18.00 R	34	1.00	Sqm	Flooring confirming to I.S3462 Flooring of approved make with fibre base using rubber base adhesives including rolling	990.00	Sqm	990.00
361.00SqmRenewing glass panes with wooden fillets wherever necessary : 4mm thick plain glass panes.765.00Sqm765.00371.00SqmRenewing glass panes and refixing existing wooden fillets : 4mm thick plain glass panes.636.00P.Sqm636.00381.00Rmt.Renewal of old putty of glass panes (length)18.00P.Rmt.18.00	35	1.00	Sqm		617.00	P.Sqm	617.00
37 1.00 Sqiii 4mm thick plain glass panes. 38 1.00 Rmt. Renewal of old putty of glass panes (length) 18.00 P.Rmt. 18.00	36	1.00	Sqm	Renewing glass panes with wooden fillets wherever necessary	765.00	Sqm	765.00
	37	1.00	Sqm		636.00	P.Sqm	636.00
39 1.00 Sqm Refixing old glass panes with putty and nails 213.00 P.Sqm 213.00				1 0 1 0 1		 	

42 43 (a) (i) (ii) (b) (ii) (iii) (c) (ii) (d) (ii) (ii) (e) (f) (ii) (iii) (g) (h)	1.00 1.00 1.00 1.00 1.00 1.00 1.00	Sqm Sqm Rmt. Rmt. Sqm. Sqm. Sqm. Each	Repair of existing steel glazed doors, windows and ventilator, MS sheet door, garge doors, compound wall gates etc. by welding drilling complete include. Cost of welding rods and hire charge of welding meachine and TP etc complete Labour charges for repair to door / window without using any material such as applying randha (finishing) tightening of bolts & screw etc. Repair of door, window shutters including cost of material and labour for change of damaged: Style / rail of teak wood 30mm thick/ Aluminium Section 4"wide 6" wide Panel by Shuttering Ply - 9mm thick (Commercial) Wire Gauge 14 mesh x 24 gauge Plain Glass Panes 4mm thick Aldrop of mild Steel 12" long x12mm dia 8" long x 10mm dia	220.00 220.00 266.00 367.00 598.00 534.00 431.00 147.00 106.00	P.Sqm P.Sqm Rmt. Rmt. Sqm. Sqm. Sqm.	332.00 220.00 266.00 367.00 598.00 534.00 431.00
(a) (i) (ii) (b) (ii) (iii) (c) (ii) (d) (ii) (ii) (e) (f) (ii) (iii) (g) (h)	1.00 1.00 1.00 1.00 1.00	Rmt. Rmt. Sqm. Sqm. Sqm.	material such as applying randha (finishing) tightening of bolts & screw etc. Repair of door, window shutters including cost of material and labour for change of damaged: Style / rail of teak wood 30mm thick/ Aluminium Section 4"wide 6" wide Panel by Shuttering Ply - 9mm thick (Commercial) Wire Gauge 14 mesh x 24 gauge Plain Glass Panes 4mm thick Aldrop of mild Steel 12" long x12mm dia 8" long x 10mm dia	266.00 367.00 598.00 534.00 431.00	Rmt. Rmt. Sqm. Sqm. Sqm.	266.00 367.00 598.00 534.00 431.00
(a) (i) (ii) (b) (ii) (iii) (c) (ii) (ii) (d) (i) (ii) (e) (f) (ii) (iii) (g) (h)	1.00 1.00 1.00 1.00	Rmt. Sqm. Sqm. Sqm. Each	material and labour for change of damaged: Style / rail of teak wood 30mm thick/ Aluminium Section 4"wide 6" wide Panel by Shuttering Ply - 9mm thick (Commercial) Wire Gauge 14 mesh x 24 gauge Plain Glass Panes 4mm thick Aldrop of mild Steel 12" long x12mm dia 8" long x 10mm dia	367.00 598.00 534.00 431.00	Rmt. Sqm. Sqm. Sqm.	367.00 598.00 534.00 431.00
(a) (i) (ii) (b) (ii) (iii) (c) (ii) (ii) (d) (i) (ii) (e) (f) (ii) (iii) (g) (h)	1.00 1.00 1.00 1.00	Rmt. Sqm. Sqm. Sqm. Each	Style / rail of teak wood 30mm thick/ Aluminium Section 4"wide 6" wide Panel by Shuttering Ply - 9mm thick (Commercial) Wire Gauge 14 mesh x 24 gauge Plain Glass Panes 4mm thick Aldrop of mild Steel 12" long x12mm dia 8" long x 10mm dia	367.00 598.00 534.00 431.00	Rmt. Sqm. Sqm. Sqm.	367.00 598.00 534.00 431.00
(i) (ii) (b) (i) (ii) (iii) (c) (i) (ii) (d) (i) (ii) (e) (f) (ii) (iii) (g) (h)	1.00 1.00 1.00 1.00	Rmt. Sqm. Sqm. Sqm. Each	4"wide 6" wide Panel by Shuttering Ply - 9mm thick (Commercial) Wire Gauge 14 mesh x 24 gauge Plain Glass Panes 4mm thick Aldrop of mild Steel 12" long x12mm dia 8" long x 10mm dia	367.00 598.00 534.00 431.00	Rmt. Sqm. Sqm. Sqm.	367.00 598.00 534.00 431.00
(ii) (b) (i) (iii) (c) (iii) (d) (iii) (e) (f) (iii) (g) (h)	1.00 1.00 1.00 1.00	Rmt. Sqm. Sqm. Sqm. Each	6" wide Panel by Shuttering Ply - 9mm thick (Commercial) Wire Gauge 14 mesh x 24 gauge Plain Glass Panes 4mm thick Aldrop of mild Steel 12" long x12mm dia 8" long x 10mm dia	367.00 598.00 534.00 431.00	Rmt. Sqm. Sqm. Sqm.	367.00 598.00 534.00 431.00
(b) (i) (ii) (iii) (c) (i) (ii) (d) (i) (ii) (e) (f) (ii) (iii) (g) (h)	1.00 1.00 1.00	Sqm. Sqm. Sqm.	Panel by Shuttering Ply - 9mm thick (Commercial) Wire Gauge 14 mesh x 24 gauge Plain Glass Panes 4mm thick Aldrop of mild Steel 12" long x12mm dia 8" long x 10mm dia	598.00 534.00 431.00	Sqm. Sqm. Sqm.	598.00 534.00 431.00
(i) (ii) (iii) (c) (i) (ii) (d) (i) (ii) (e) (f) (i) (ii) (ii) (g) (h)	1.00 1.00 1.00	Sqm. Sqm.	Shuttering Ply - 9mm thick (Commercial) Wire Gauge 14 mesh x 24 gauge Plain Glass Panes 4mm thick Aldrop of mild Steel 12" long x12mm dia 8" long x 10mm dia	534.00 431.00 147.00	Sqm.	534.00 431.00
(ii) (iii) (c) (i) (ii) (d) (i) (ii) (e) (f) (ii) (iii) (g) (h)	1.00 1.00 1.00	Sqm. Sqm.	Wire Gauge 14 mesh x 24 gauge Plain Glass Panes 4mm thick Aldrop of mild Steel 12" long x12mm dia 8" long x 10mm dia	534.00 431.00 147.00	Sqm.	534.00 431.00
(iii) (c) (i) (ii) (d) (i) (ii) (e) (f) (ii) (iii) (iii) (g) (h)	1.00	Sqm.	Plain Glass Panes 4mm thick Aldrop of mild Steel 12" long x12mm dia 8" long x 10mm dia	431.00 147.00	Sqm.	431.00
(c) (i) (ii) (d) (i) (ii) (e) (f) (ii) (iii) (g) (h)	1.00	Each	Aldrop of mild Steel 12" long x12mm dia 8" long x 10mm dia	147.00	-	
(i) (ii) (d) (ii) (e) (f) (ii) (iii) (g) (h)			12" long x12mm dia 8" long x 10mm dia		Each	147 00
(ii) (d) (i) (ii) (e) (f) (ii) (iii) (iii) (g) (h)			8" long x 10mm dia		Lacii	
(d) (i) (ii) (e) (f) (ii) (iii) (iii) (g) (h)	1.00	Lucii	Č	106 00	Each	106.00
(i) (ii) (e) (f) (i) (ii) (iii) (g) (h)			Stopper of Aluminium with	100.00	Eden	100.00
(ii) (e) (f) (i) (ii) (iii) (g) (h)	1.00	Each	Single Rubber Gutka	33.00	Each	33.00
(e) (f) (i) (ii) (iii) (g) (h)	1.00	Each	Double Rubber Gutka	47.00	Each	47.00
(f) (i) (ii) (iii) (g) (h)	1.00	Each	Door Springs of mild Steel	160.00	Each	160.00
(i) (ii) (iii) (g) (h)			Steel Hinges			
(ii) (iii) (g) (h)	1.00	Each		24.00	Each	24.00
(g) (h)	1.00	Each	For Wooden Chowkhat 4" size	34.00	Each	34.00
(h)	1.00	Each	For Stone Chowkhat ,4"size	29.00	Each	29.00
	1.00	Each	Mild Steel Tower Bolt 6" long	39.00	Each	39.00
(i)	1.00	Each	Steel Locking Bolt	53.00	Each	53.00
(/	1.00	Each	Steel Handle 6" size	24.00	Each	24.00
44			Providing and fixing aluminum work for doors ,windows, ventilators and partition with extruded built up standard tubular / appropriate Z sections and other sections of approved make conforming to IS:733 and IS:1285, fixed with rawl plugs and screws or with fixing clips ,or with expansion hold fasteners including necessary filling up of gap. at junctions , at top ,bottom and sides with required PVC/neoprene felt etc. Aluminium section shall be smooth ,rust free, straight ,mitered and jointed mechanically wherever required including cleat angle Aluminium snap beading for glazing /paneling , C.P. brass/ stainless steel screws Al. Tower bolt & Al. handle & Al. Aldrop etc.,all complete as per architectural drawings and the directions of Engineer- in – charge . (Glazing and paneling to be paid for separately). For fixed portion .			

		I		I	1 1	
a	1.00	Kg	Powder coating aluminum (minimum thickness of powder coating 50 micron)	351.00	Kg	351.00
ii			For shutters builtup standard tubular sections of openable doors ,windows & ventilators including providing & fixing hinges / rollers etc. and making provision for fixing of fittings wherever required (lockes shall be paid for separately).			
a	1.00	Kg	Powder coating aluminum (minimum thickness of powder coating 50 micron)	381.00	Kg	381.00
45	1.00	Kg	For fixed portion, Anodised aluminum (anodised transparent 81 dyed to required shade according to IS: 1868. (Minimum anodic coating of grade AC 15, Anodizing to be got done from approved Anodizer)	326.00	P.Kg	326.00
46	1.00	Kg	For shutters builtup standard tubular sections of openable doors ,windows & ventilators including providing & fixing hinges / rollers etc. and making provision for fixing of fittings wherever required (lockes shall be paid for separately). Anodised aluminum (anodised transparent 81 dyed to required shade according to IS: 1868. (Minimum anodic coating of grade AC 15, Anodizing to be got done from approved Anodizer)	355.00	P.Kg	355.00
47	1.00	Sqm	Extra for shutters of sliding aluminum windows	10%	Sqm	0.10
48	1.00	Sqm	Providing and fixing 12 mm thick prelaminated three layer medium density (exterior grade) particle board Grade I, Type II conforming to IS: 12823 bonded formaldehyde synthetic resin, of approved brand and manufacture in paneling fixed in aluminium doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and direction of engineer-in-charge. Prelaminated particle board with decorative lamination on both sides.	1092.00	Sqm	1092.00
49	1.00	Sqm	Providing and fixing glazing in aluminium door, window ventilator shutters and partitions etc. with PVS / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item.) With float glass panes of 5.0 mm thickness (weight not less than 13.50 kg/sqm)	902.00	P.Sqm	902.00
50	1.00	No.	Providing and fixing double action hydraulic floor spring of approved brand and manufacture IS: 6315 marked, for doors including cost of cutting floors as required, embedding in floors and cover plates with brass pivot and single piece M.S. With stainless steel cover plate	1426.00	Each	1426.00
51	1.00	Each	Providing and fixing double action hydraulic floor spring of approved brand and manufacture IS: 6315 marked, for doors including cost of cutting floors as required, embedding in floors and cover plates with brass pivot and single piece M.S. With brass cover plate	1976.00	Each	1976.00
52	1.00	Rmt.	Filling the gap upto 5 mm depth and 5 mm width in between aluminium frame & adjacent RCC/ Brick/ Stone work by providing weather silicon sealant over backer rod of approved quality as per architectural drawings and direction of Engineer-in-charge complete.	78.00	P.Rmt.	78.00
53	1.00	No.	Providing and fixing 100mm brass locks (best make of approved quality) for aluminium doors including necessary cutting and making good etc. complete.	328.00	Each	328.00
54	1.00	No.	Providing and fixing aluminium round shape handle of outer dia 100mm with SS screws etc. Complete as per direction of Engineer-in-charge. Anodized (AC 15) aluminium	67.00	Each	67.00

55	1.00	Sqm	Providing and fixing expanded grill made of aluminum as per design and drawing having members section of size 7.5mm x 6.0mm and opening of size 102mm x 99mm to aluminum window/vent with required screws, Y and H aluminium sec (as per drawing) at the ends and middle joints respectively complete in all respect as per direction of engineer in charge. Powder coating aluminum (minimum thickness of powder coating 50 micron)	1843.00	Sqm	1843.00
56	1.00	Sqm	S&f fixed wire gauge of stainless steel of 14 mesh x 24 gauge to the aluminium window by Aluminium beading 20x3mm with suitable screws not exceeding 150mm distance at all heights with all lead and lift with scafolding.	925.00	Sqm	925.00
57	1.00	Sqm	Providing and fixing vertical Blinds, headrail shall be oriented aluminum alloy 50 mm wide x 18 mm high the thickness shall be 1.2 mm. Control unit shall be made of high grade polymer and shall be housed in side the headrail, which shall transfer motion from chain tilter to tilt rod. Chain tilter shall be made of plastic bead of diameter 4.5 mm through which 2 mm thick polyester code passes. Tilt rod shall be extruded aluminum having 3 key ways. Runner shall be moulded plastic and shall have to plastic wheels mounted on plastic exles to enable runner to slide unhindered in headrail. Luver shall be made of fabric 100 mm colour fast and shall have protective scotchgard coating to resist stains and dust. Bottom mechanism consist bottom weight made of powder coated galvanized steel for maximum corrosion resistance. The bottom weight shall be attached with bottom.	1623.00	Sqm	1623.00
58	1.00	Rm	Providing and fixing Drapery rod shall be made of 20 gauge cold rolled steel strip. Which is electrical resistance welded, The section will be available 25.4 mm diameter the section shall be coated with acid resistance polymer finial shall made from ABS material in nearest matching colour of rod. The ring shall be made from ABS material in nearest matching colour to rod. Brackets of made of galvanized steel.	474.00	Rm	474.00
59	1.00	Sqm	Providing and fixing sun control film, thickness of film 1 Mil Visible Light Transmittance 4-24% & Solar Energy Transmittance 42-51% & Total solar Energy rejection 37-43% of approved colour and shade, complete in all respect, at all level, as directed by engineer- in -charge.	639.00	Sqm	639.00
60	1.00	Rm	Providing and fixing factory made P.V.C. door frame of size 50x47mm with a wall thickness of 5mm, made out of extruded 5mm rigid PVC foam sheet mitred at corners and joined with 2 Nos. of 150mm long brackets of 15x15mm M.S. square tube, the vertical door profiles to be reinforced with 19x19mm M.S. square tube of 19 gauge, EPDM rubber gasket weather seal to be provided through out the frame. The door frame to be fixed to the wall using M.S. screws of 65/100mm size complete as per manufacturers specification and direction of Engineer-in-Charge.	277.00	Rm	277.00

61	1.00	Sqm	Providing and fixing to existing door frames. 30mm thick factory made solid panel PVC door shutter consisting of frame made out of M.S. tubes of 19 gauge thickness and size of 19mm x 19mm for stiles and 15 mm x15mm, top & bottom rails. M.S. frame shall have a coat of steel primers of approved make and manufacture M.S. frame covered with 5mm thick heat moulded PVC 'C channel of size 30mm thickness, 70mm width out of which 50mm shall be flat and 20mm shall be tapered in 45 degree angle on either side forming stiles; and 5mm thick, 95mm wide PVC sheet out of which 75 mm shall be flat and 20mm shall be tapered in 45 degree on the inner side to form top and bottom rail and 115mm wide PVC sheet out of which 75 mm shall be flat and 20mm shall be tapered on both sides to form lock rail. Top bottom and lock rails shall be provided either side of the panel. 10mm (5mm x 2) thick, 20mm wide cross PVC sheet shall be provided as gap insert for top rail & bottom rail. Panelling of 5mm thick PVC sheet to be fitted in the M.S. frame welded/ sealed to the stiles & rails with 7mm (5mm +2mm) thick x 15mm wide PVC sheet bending on inner side, and joined together with solvent cement adhesive. An additional 5mm thick PVC strip of 20mm width is to be stuck on the interior side of the 'C Channel using PVC solvent adhesive etc. complete as per direction of Engineer-in-charge, manufacture's specification & drawing.(For W.C.and bathroom door shutter).	3211.00	Sqm	3211.00
62	1.00	Sqm	Providing and fixing Structural glazing work with toughened glass of 6mm thick and reflective colour as approved in dark shade like Blue/Dark Blue etc. with frame work of curtain section 65x60mm (Weight 1.64 kg/m min.) made of aluminium with chrome plating. Internal frame work will also be of curtain section 65x60mm of chrome plated aluminium section with20x20mm aluminium tube section and structural spacer made of rubber. The aluminium frame work size as per instruction of Engineer-in-charge and including openable panels with all necesary sections and fitting. The work include silicon structural adhesive for complete gripping of glass with framing members and silicon weather seal sealant to prevent moisture/water through joints. Glass will be fixed in plumb and with uniform spacing of 10-12mm wide duly filled with silicon weather seal sealant. The work includes all labour, scaffolding, structural aluminium work, toughened glasses, silicon weather seal sealant, silicon structural adhesive structural spacer, all accessories like handles, peg stays, M-15 grade cement concrete for fixing holdfast .(Face area of glass shall be measured)	5381.00	Sqm	5381.00

63	1.00	Sqm	Providing and fixing of UPVC casement openable windows (outward / inward): Outer Frame made from the Extruded UPVC Windows profile section of size 60w X 60h mm having outer wall thickness of 2.5mm (+/- 0.2mm) and three chamber constuction in Laminated (colour) finish, duly reinforced with 1.5mm thick GI section. All the four corners shall be mitered cut & thermal welded so as to form window frame. Frame shall be milled with drain and air equalizer hole in order to be water tight and for drainage of accumulated water, if any, to outer side. Fix Mullion made of 60w X 80h mm UPVC profile section with steel reinforcement shall be provided in windows having 2 or more openable shutters, as per the requirement. Frame shall have co-extruded with EPDM/TPE-E gasket fitted in in-built groove of frame profile for proper air & sound Shutter: The shutter of outward openable window shall be made of size 60w X 74h mm and shutter of inward openable window shall be made of size 60w x 77h mm Extruded 3 box multi-chamber UPVC Window profile section of laminated(colour) having outer wall thickness of 2.25mm (+/- 0.2mm) provided with reinforcement of 1.5mm thick GI section duly mitered cut & thermal welded at all corners and fitted with UPVC glazing bead of size 36 X 20mm with inner and outer co-extruded EPDM/TPE-E weather seal gasket alongwith 6mm thick ISI make plain float glass. All welding joints of frame and shutter shall be cleaned and milled with the CNC mechainism to provide uniform grooved finish on all visible joints. Hardware: Window shutter are fixed with frame on 2.5mm thick SS301 Grade friction hinge system to keep the window opened at desired angle. Friction Hinge also enables easy cleaning of glass on both side from the inside of building insulation of the shutter.	13474.00	Sqm	13474.00
64	1.00	Sqm	Providing and fixing of openable uPVC Doors with or without fix top: Frame Made of Extruded uPVC Window Profile Section of size 60w x 70h mm having outer wall thickness of 2.75mm (+/- 0.2mm) and 3 box multi-chamber construction, Laminated (colour) finish, duly reinforced with 1.2mm thick GI section. All the corners shall be mitered cut & thermal welded so as to form door frame. Fix Mullion made of 60w x 80h mm uPVC Profile Section with steel reinforcement shall be provided for the top fix portion of the doors or in case of the doors having more than two openable shutters, as per the requirement / drawing. Frame of openable door shall have coextruded EPDM/TPE-E gasket fitted in in-built groove of frame profile for proper air & sound insulation of the shutter. Shutter: The shutters of openable door shall be made of 60w x 95h mm Extruded 3 box multi-chamber uPVC Window Profile Section of laminated(colour) having outer wall thickness of 2.75mm (+/- 0.2mm) provided with reinforcement of 2.0 mm thick GI section duly mitered cut & thermal welded at all corners, provided with center mullion (if specified in drawing) of size 60w x 80h mm uPVC Profile Section and fitted with uPVC glazingbead of size 36 x 20mm with inner and outer co-extruded EPDM/TPE-E weather seal gaskets alongwith 6mm thick ISI make plain float glass. All welding joints of frame and shutter shall be cleaned and milled with the CNC mechanism to provide uniform grooved finish on all visible joints. Hardware: Each openable door shutters is to be fixed with three load beading butt hinges and locking of doors is to be provided with multi-point transmission gear (ESPAG) with white finish powder- coated	13558.00	Sqm	13558.00

65	1.00	Sqm	lockable handle. Installation at site: Complete door is to be installed on site with 10 X 100mm fastners with white cap in existing pre-finished wall cut-out cemented to glass level plane at all height & width and silicon glue is applied to fill up the crevices between wall and door frame. Complete in all respect as per the drawing and specification and direction of engineer-in-charge. Providing and Fixing Aluminium composite panel of approved make 3mm thick with 0.5mm thick skin & PVDF coated approved shade for wall panelling. Main framing work to be done using 50mmx25mmx1.6mm tubular section of approved make. Stainless steel screw to be used to fix the ACP panel to be fixed to the main frame with industrial adhesive tape and panel groove to be sealed with weather proof silicon sealant suitable for glass/aluminium etc. complete in all respect as approved by Engineer-in-charge.	2594.00	Sqm	2594.00
66			Providing and fixing stainless steel railing made of Hollow tubes, channels, plates etc., including welding, grinding, buffing, polishing and making curvature (wherever required) and fitting the same with necessary stainless steel nuts and bolts complete, i/c fixing the railing with necessary accessories & stainless steel dash fasteners, stainless steel bolts etc., of required size, on the top of the floor or the side of waist slab with suitable arrangement as per approval of Engineer-in-charge, (for payment purpose only weight of stainless steel members shall be considered excluding fixing accessories such as nuts, bolts, fasteners etc.).			
a	1.00	Kg	Grade 304	503.00	Kg	503.00
b	1.00	Kg	Grade 204	432.00	Kg	432.00
67	1.00	Kg	AccessoriesSupply and Installation of (Labour rate included in main item). Adhesives.	198.00	Kg	198.00
68	1.00	Sqm	Supply and fixing of Cement Bonded Particle Board (as per 14276) double skin partition using with 10 MM thick Cement Board made out of G.I. track section of size 50mmx 35mm x 0.55 mm for fixing to the roof and floor and stud section of size 48mm x 35mm x 0.55mm placed in track section vertically at 610mm intervals and at 1200mm intervals horizontally fixed to the wall by means of self expansion screws and caps to the wall and roof. Cement Board panel is to be fixed both sides of frame work by using self taping screws fixed at every 300mm intervals to the frame work leaving 3 mm gap between two panels. The cost inclusive with one coat of Alltek primer and two coats of Alltek smooth finish and cost and conveyance of all materials to site, labor charges etc., complete as per the direction of Engineer in charge.	2429.00	Sqm	2429.00

69	1.00	Sqm	Supply and fixing of Factory Laminated Cement Bonded Particle Board double skin partition using with 10MM Factory Laminated Cement Bonded Board made out of G.I track section of size 50 mm x 35mm x 0.55mm for fixing to the roof and floor and stud section of size 48mm x 35mm x 0.55mm placed in track section vertically at 610mm intervals and at 1200mm internals horizontally. The frame is fixed by means of self expansion screws and caps to the wall / roof. Laminated Cement Bonded Particle Board is to be fixed both sides of the frame work by using 2mm thick electro plated CR flat section leaving 3mm gap between two panels. The cost inclusive of cost and conveyance of all materials to sites, other materials incidentals and labor charges as per the direction of Engineer in charges.	3401.00	Sqm	3401.00	
----	------	-----	---	---------	-----	---------	--

Secretary Rajasthan State Sports Council Jaipur