राजस्थान राज्य क्रीडा परिषद

सवाई मानसिंह स्टेडियम, जनपथ, जयपुर

कार्यालय दरभाष नं0 0141-2744283, फैक्स नं0 0141-2740568, ईमेल आईडी-rsscjaipur@gmail.com

No.F.8/KIUG-2025/Sanitary Work /Raj-Kaj Ref.

निविदा सचना संख्या 40/2025-26

Date: (E-Signed)

राजस्थान में आयोजित होने वाले खेलों इंडिया यूनिवर्सिटी गेम्स-2025 हेत् आयोजन रथलों / स्थानों (संभाग मुख्यालयों) पर आवश्यक रखरखाव / मरम्मत सैनेट्ररी कार्य हेत् राज्य / केन्द्र सरकार के संगठनों / विभागों में पंजीकृत संवेदकों से ई-प्रोक्यूरमेंट प्रक्रिया हेत् ऑनलाइन निविदा आमंत्रित की जाती है।

निविदा से संबंधित अन्य आवश्यक विवरण वेबसाईट http://sppp.rajasthan.gov.in, http://eproc.rajasthan.gov.in व www.rssc.in पर देखी जा सकती है।

सचिव



Digitally signed by Rais ndra Singh Designation, Secretary Date: 2025.08.29 13.16:04 IST

Reason: Appro



RAJASTHAN STATE SPORTS COUNCIL

TENDER DOCUMENT

FOR

Development and Maintenance Works (Sanitary) for KIUG-2025.

NIT NO. NIT No. /2025-26

ESTIMATED COST Rs. 45.00 Lacs

EARNEST MONEY Rs. 90,000/-

DATE OF SALE / DOWNLOADING: From Saturday August 30, 2025 to Monday

September 08, 2025, 13:00 Hours

DATE OF RECEIPT (D.D. & From Saturday August 30, 2025 to Monday

September 08, 2025, 15:00 Hours **DOCUMENTS**)

DATE OF OPENING OF TENDER Tuesday September 09, 2025 AT 16:00 Hours

COMPLETION PERIOD 45 Days

COST OF TENDER Rs. 1500/- in favour of Secretary, RSSC, Jaipur

PROCESSING FEES Rs 500/- in favour of MD, RISL, Jaipur

Signature yalid

Digitally signed by Raichdra Singh Designation, Secretary Date: 2025.08.29 13.16:04 IST

Reason: Appro

Rajasthan State Sports Council. Jaipur

Important Dates of Bids

1. Completion Period	45 Days
2. Date of Issue of Notice Inviting Tender	Saturday September 30, 2025
3. Period and Places of Sale/ Download of	From Saturday August 30, 2025 to Monday September 08,
Bidding Documents -	2025, 13:00 Hours
	http://sppp.rajasthan.gov.in, www.rssc.in &
	http://eproc.rajasthan.gov.in
4. Deadline for uploading	From Saturday August 30, 2025 to Monday September 08,
	2025, 13:00 Hours
5. Time and Date for Opening of Bids	Tuesday September 09, 2025 AT 16:00 Hours
6. Place of Opening of Bids	Rajasthan State Sports Council, SMS Stadium, Jaipur-
	302005
7. Officer Inviting Bids	Secretary, Rajasthan State Sports Council. Jaipur.
	Address: SMS Stadium, Jaipur-302005
8. Earnest money to be deposited	As per NIT

Signature valid

Digitally signed by Rajondra Singh
Designation, Secretary
Date: 2025.08.29 19:16:04 IST
Reason: Approver

Instructions and information to bidder regarding Fee, EMD etc.

Place	Name of Work Package No.	Estimated Cost (Rs.)	Earnest Money	Time Allowed for completion		date of	Place of Sale of documents	Class of contractor.
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)
All Division Rajasthan State	Development and Maintenance Works (Sanitary) for KIUG-2025.	45.00 Lacs	Rs. 90,000/-	45 Days	Monday September 08, 2025, 13:00 Hours	Tuesday September 09, 2025 AT 16:00 Hours	http://sppp.rajasthan.gov.in, http://eproc.rajasthan.gov.in & www.rssc.in	S-I and Above category for Sanitary works

- The Tender Fee and earnest money as mentioned above should be deposited in the appropriate form as per the tender documents in favour of Secretary, Rajasthan State Sports Council. Jaipur payable at Jaipur and Processing Fees in favour of MD, RISL, Jaipur payable at Jaipur and must be uploaded scan copy of Registration of Firm, Demand Draft of Tender Cost, Processing Fee & Earnest Money and GST Number on the site
- 2. The tender can be viewed and downloaded from web site http://sppp.rajasthan.gov.in, http://eproc.rajasthan.gov.in & www.rssc.in
- 3. The authorized tender documents are available for inspection in the office of **Rajasthan State**Sports Council, SMS Stadium, Jaipur from all working days.

Signature yalid

Digitally signed by Fajendra Singh Designation Secretary

Designation Secretary Date: 2025.08.29 19:16:04 IST

Reason: Approve

Annexure A: Compliance with the Code of Integrity and No Conflict of Interest

Any person participating in a procurement process shall-

- (a) Not offer any bribe, reward or gift or any material benefit either directly or indirectly in exchange for an unfair advantage in procurement process or to otherwise influence the procurement process;
- (b) Not misrepresent or omit that misleads or attempts to mislead so as to obtain a financial or other benefit or avoid an obligation;
- (c) Not indulge in any collusion, Bid rigging or anticompetitive behavior to impair the transparency, fairness and progress of the procurement process;
- (d) Not misuse any information shared between the procuring entity and the bidders with an intent to gain unfair advantage in the procurement process;
- (e) Not indulge in any coercion including impairing or harming or threatening to do the same, directly or indirectly, to any party or to its property to influence the procurement process;
- (f) Not obstruct any investigation or audit of a procurement process;
- (g) Disclose conflict of interest, if any; and
- (h) Disclose any previous transgressions with any entity in India or any other country during the last three years or any debarment by any other procuring entity.

Conflict of interest.-

The Bidder participating in a bidding process must not have a Conflict of Interest.

A Conflict of interest is considered to be a situation in which a party has interests that could improperly influence that party's performance of official duties or responsibilities, contractual obligations, or compliance with applicable laws and regulations.

- (i) A bidder may be considered to be in conflict of interest with one or more parties in the bidding process if, including but not limited to:
- (a) Have controlling partners/shareholders in common; or
- (b) Receive or have received any direct or indirect subsidy from any of them; or
- (c) Have the same legal representative for purposes of the bid; or
- (d) have a relationship with each other, directly or through common third parties, that puts them in a position to have access to information about or influence on the bid of another bidder, or influence the decisions of the procuring Entity regarding the bidding process; or
- (e) The bidder participates in more than one bid in a bidding process. Participation by a bidder in more than one bid will result in the disqualification of all bids in which the bidder is involved. However, this does not limit the inclusion of the same subcontractor, not otherwise participating as a bidder, in more than one bid; or
- (f) the bidder or any of its affiliates participated as a consultant in the preparation of the design or technical specifications of the goods, Works or services that are the subject of the Bid; or
- (g) Bidder or any of its affiliates has been hired (opproposed to be hired) by the procuring entity as engineer-in-charge/consultant for instance.

Digitally signed by Raigndra Singh Designation Secretary

Date: 2025.08.29/17.16:04 IST

Reason: Approve

Annexure B: Declaration by the Bidder regarding Qualifications **Declaration by the Bidder**

In re	lation to my/our	Bid su	bmitted to				for	procure	mei	nt
of	•••••	in	response	to	their	Notice	inv	iting	Bio	ds
No	Dated	I/	we	•••••	hereby	declare	under	Section	7 (эf
Rajas	than Transparen	cy in Pul	blic Procure	ement Act.	2012 tha	at:				

- 1. I/we possess the necessary professional, technical, financial and managerial resources and competence required by the Bidding Document issued by the Procuring Entry;
- 2. I/we have fulfilled my/our obligation to pay such of the taxes payable to the union and the state government or any local authority as specified in the Bidding Document.
- I/we are not insolvent, in receivership, bankrupt or being wound up, not have 3. my/our affairs administered by a court or a judicial officer, not have my/our business activities suspended and not the subject of legal proceedings for any of the foregoing reasons;
- I/we do not have, and our directors and officers not have, been convicted of any 4. criminal offence related to my/our professional conduct or the making of false statements or misrepresentations as to my/our qualifications to enter into a procurement contract within a period of three years preceding the commencement of this procurement process, or not have been otherwise disqualified pursuant to debarment proceedings;
- I/we do not have a conflict of interest as specified in the Act, Rules and the Bidding 5. Document, which materially affects fair competition;

Date:	Signature of bidder
Place:	Name:
	Designation:
	Address:

Signature yalid

Digitally signed by Raindra Singh Digitally Signed Designation Secretary

Designation Secretary

10025 08 20 17.16:04 IST

Reason: Appro

Annexure C: Grievance Redressed during Procurement Process

The designation and address of the First Appellate Authority is **Deputy Secretary**, Youth Affairs & Sports Department Govt. of Rajasthan. The designation and address of the Second Appellate Authority is **Principal Secretary**, Youth Affairs & Sports Department Govt. of Rajasthan, Jaipur.

(1) Filing an appeal:-

if any bidder or prospective bidder is aggrieved that any decision, action or omission of the procuring entity is in contravention to the provisions of the Act or the rules or the guidelines issued there under, he may file an appeal to First Appellate authority, as specified in the Bidding document within a period of ten days from the date of such decision or action, omission, as the case may be, clearly giving the specific ground or grounds on which he feels aggrieved:

Provided that after the declaration of a bidder as successful the appeal may be filed only by a bidder who has participated in procurement proceedings:

Provided further that in case a procuring entity evaluates the technical bids before the opening of the financial bids, an appeal related to the matter of financial bids may be filed only by a bidder whose technical bid is found to be acceptable.

- The officer to whom an appeal is filed under Para (1) shall deal with the appeal as expeditiously as possible and shall endeavor to dispose it of within thirty days from the date of the appeal.
- If the officer designated under Para (1) fails to dispose of the appeal filed within the period specified in Para (2), or if the bidder or prospective bidder or the procuring entity is aggrieved by the order passed by the first appellate authority, the bidder or prospective bidder or the procuring entity, as the case may be, may file a second appeal to second appellate authority specified in the bidding document in this behalf within fifteen days from the expiry of the period specified in Para (2) or of the date of receipt of the order passed by the first appellate authority, as the case may be.

Appeals not to lie in certain cases:-

No appeal shall lie against any decision of the procuring entity relating to the following matters, namely:-

- (a) Determination of need of procurement
- (b) Provisions limiting participation of bidders in the bid process
- (c) The decision of whether or not to enter into negotiations
- (d) Cancellation of a procurement process
- (e) Applicability of the provisions of confidentiality

Form of Appeals:-

- An appeal under Para (1) or (3) above shall be in the annexed form along with as many copies as there are respondents in the appeal.
- (b) Every appeal shall be accompanied by an order appealed against, if any, Affidavit verifying the facts stated in the appeal and proof of payment of fee,
- Every appeal may be presented to first appellate authority or second Appellate authority, as the case may be, in person or though registered post Or authorized representative.

(6) Fee for filing Appeal:-

- Fee for first appeal shall be rupees two thousand five hundred and for second (a) appeal shall be rupees ten thousand, which shall be non-refundable.
- The fee shall be paid in the form of bank demand draft or banker's cheque of (b) a scheduled bank in India payable in the interpretary and int concerned.

Digitally signed by Raindra Singh Designation Secreta

.16:04 IST Date: 2025.08

Reason: Appro

(7) Procedure for disposal of Appeal:-

- (a) The first appellate authority or second appellate authority as the case may be, upon filing of appeal, shall issue notice accompanied by copy of appeal, affidavit and documents, if any, to the respondents and fix date of hearing
- (b) On the date fixed for hearing, the first appellate authority of second appellate authority, as the case may be shall-
 - (i) Hear all the parties to appeal present before him; and
 - (ii) Peruse or inspect documents, relevant records or copies thereof relating to the matter.
- (c) After hearing the parties, perusal or inspection of documents and relevant records or copies thereof relating to the matter, the appellate authority concerned shall pass an order in writing and provide the copy of order to the parties to appeal free of cost.
- (d) The order passed under sub-clause (c) above shall also be placed on the state public procurement portal.

Signature yalid

Digitally signed by Rai ndra Singh

Designation Secretary Date: 2025.08.29 12:16:04 IST

Reason: Approve

Annexure D: Additional Conditions of Contract

1. Correction of arithmetical errors

Provided that a Financial Bid is substantially responsive, the Procuring Entity will correct arithmetical errors during evaluation of Financial Bids on the following basis:

- i. If there is a discrepancy between the unit price and the total price that is obtained by multiplying the unit price and quantity, the unit price shall prevail and the total price shall be corrected, unless in the opinion of the Procuring Entity there is an obvious misplacement of the decimal point in the unit price, in which case the total price as quoted shall govern and the unit price shall be corrected;
- ii. It there is an error in a total corresponding to the addition or subtraction of subtotals, the subtotals shall prevail and the total shall be corrected; and
- iii. If there is a discrepancy between words and figures, the amount in words shall prevail, unless the amount expressed in words is related to an arithmetic error, in which case the amount in figures shall prevail subject to (i) and (ii) above.

If the Bidder that submitted the lowest evaluated Bid does not accept the correction of errors, its Bid shall be disqualified and its Bid Security shall be forfeited or its Bid Securing Declaration shall be executed.

2. Procuring Entity's Right to Vary Quantities

- (i) At the time of award of contract, the quantity of Goods, Works or services originally specified in the Bidding Document may be increased or decreased by a specified percentage, but such increase or decrease shall not exceed Five percent, of the quantity specified in the Bidding Document. It shall be without any change in the unit prices or other terms and conditions of the Bid and the conditions of contract.
- (ii) If the Procuring Entity does not procure any subject matter of procurement or procures less than the quantity specified in the Bidding Document due to change in circumstances, the Bidder shall not be entitled for any claim or compensation except otherwise provided in the Conditions of Contract.
- (iii) In case of procurement of Goods or services, additional quantity may be procured by placing a repeat order on the rates and conditions of the original order. However, the additional quantity shall not be more than 50% of the value of Goods of the original contract and shall be within one month from the date of expiry of last supply. If the supplier fails to do so, the Procuring Entity shall be free to arrange for the balance supply by limited Bidding or otherwise and the extra cost incurred shall be recovered from the supplier.

3. Dividing quantities among more than one Bidder at the time of award (In case of procurement of Goods)

As a general rule all the quantities of the subject matter of procurement shall be procured from the Bidder, whose Bid is accepted. However, when it is considered that the quantity of the subject matter of procurement to be procured is very large and it may not be in the capacity of the Bidder, whose Bid is accepted, to deliver the entire quantity or when it is considered that the subject matter of procurement to be procured is of critical and vital nature, in such cases, the quantity may be divided between the Bidder, whose Bid is accepted and the second lowest Bidder or even more Bidders in that order, in a fair, transparent and equitable manner at the rates of the Bidder, whose Bid is accepted.

Signature yalid

Digitally signed by Raindra Singh

Reason: Appro

राजस्थान राज्य क्रीडा परिषद

सवाई मानसिंह स्टेडियम, जनपथ, जयपुर

कार्यालय दरभाष नं0 0141-2744283, फैक्स नं0 0141-2740568, ईमेल आईडी-rsscjaipur@gmail.com बोली की शर्ते

विशेष टिप्पणी :- बोलीदाताओं को इन शर्तों को सावधानी पूर्वक पढ़ना चाहिए तथा अपनी ई-बोलियां भेजते समय इनकी पूर्ण रूपेण पालना करनी चाहिए।

- 1. तकनीकी प्रस्तावों में सफल बोलीदाताओं के ही वित्तीय प्रस्ताव खोले जावेगें जो निविदादाता तकनीकी बिड में सफल नहीं पाये गये उनकी वित्तीय बोली नहीं खोली जायेगी।
- 2. कोई भी फर्म / संवेदक यदि जी एस.टी. अधिनियम के अन्तर्गत पंजीकृत नहीं है तो वह बोली नहीं देगा। इनके अभाव में बोलियों पर विचार नहीं किया जायेगा। जी. एस. टी. देयता प्रमाण पत्र जून, 2025 का संलग्न करना आवश्यक है।
- 3. दरें जी.एस.टी. तथा केन्द्र व राज्य सरकार द्वारा देय समस्त करों सहित देनी होगी।
- 4. बोली ऑन-लाईन प्रस्तुत की जावेगी एवं निर्दिष्ट कॉलमों में प्रविष्टी की जावेगी।
- 5. दरें गन्तव्य स्थान तक एफ.ओ.आर. सवाई मानसिंह स्टेडियम जयपूर के आधार पर होगीं अर्थात परिवहन संबंधी कोई राशि परिषद द्वारा पृथक से देय नहीं होगी।
- 6. बोलियां उपापन अधिनियम / पारदर्शिता अधिनियम के तत्संबंधी प्रावधानों (धारा-28 आदि) के अध्यधीन रहते हुये उनके खोले जाने की दिनाक से एक वर्ष की अवधि के लिए विधि मान्य होंगी।
- 7. बोलीदाता अपनी संविदा या उसके किसी भाग को किसी अन्य एजेन्सी के लिए नहीं सौंपेगा या उपभाड़े पर नहीं देगा।
- 8. बोलीदाता का उसके प्रतिनिधि की ओर से प्रत्यक्ष अथवा अप्रत्यक्ष रूप से अपना पक्ष समर्थन करना एक प्रकार की अनर्हता होगी। हित विरोधी धारा 80 होगी।
- 9. विहित समय एवं तारीख के पश्चात् जो भी बोलियां प्राप्त होंगी उन्हें किसी स्थिति में स्वीकार नहीं किया जावेगा।
- 10. यदि बोलीदाता ऐसी कोई शर्त आरोपित करता है जो उसमें वर्णित शर्तों के अतिरिक्त है या उनके विरोध में है तो उसकी बोली को संक्षिप्त रूप में कार्यवाही कर रदद कर दिया जावेगा।
- 11 तकनीकी बोली के साथ बोलीदाता को निम्न दस्तावेज सलग्न करने अनिवार्य होगे (जिसके आधार पर तकनीकी बिड का मूल्याकन किया जायेगा) :--
 - बोली में अंकित पते के प्रमाण हेत् पानी/बिजली/टेलीफोन/मोबाईल के बिल, पेन कार्ड, पासपोर्ट, आधार कार्ड अथवा डाईविंग लाईसेन्स में से कोई एक की प्रमाणित छाया प्रतियां।
 - बोलीदाता / फर्म का विगत ३ वित्तीय वर्षों (२०२१–२२, २०२२–२३ एवं 2023—24) में औसत वार्षिक टर्न ओवर 45.00 लाख से कम नहीं होना चाहिये। इस हेत् बोलीदाता को उक्त वर्षों का सीए से प्रमाणित प्रमाण पत्र की प्रति मय यूडीआई नम्बर सहित संलग्न करनी होगी।
 - गत 3 वर्षों (2021–22, 2022–23 एवं 2023–24) में राजकीय विभागों में किये गये सैनेट्ररी कार्य का एकल कार्य **अन्याप्त प्रवास्त** अधिक, दो कार्य आदेश 22.50 लाख एव तीन कार्य आदेश 18.00 के तक Digitally signed by Rais ndra Singh Designation Secretary Date: 2025.08.29 17.16:04 IST

Reason: Appro

- सन्तोषजनक होने का प्रमाण पत्र आदि आवश्यक दस्तावेज संलग्न करने
- बोलीदाता को माल एवं सेवाकर (GST) के रजिस्ट्रेशन की प्रति संलग्न करनी iii.
- अमानत राशि एवं बोली प्रपत्र शुल्क का डी.डी. संलग्न करना होगा।

12. **बयाना राशि** :--

- (क) बोली से पूर्व (2% बोली सूचना के अनुसार) नियमानुसार बयाना राशि ऑन-लाईन प्रस्तुत की जायेगी। इसके बिना बोलीओं पर विचार नहीं किया जायेगा। यह राशि सचिव, राजस्थान राज्य क्रीडा परिषद, जयपुर के पक्ष में बैंक ड्राफट / बैंकर्स चैक में से किसी रूप में जमा करायी जा सकती है।
- (ख) असफल बोलीदाता की बयाना राशि बोली को अंतिम रूप से स्वीकार करने के बाद यथा संभव शीघ्र लौटा दी जावेगी।
- (ग) अनुमोदन की प्रतीक्षा करने वाली या रद्द की गई या संविदाओं के पूर्ण हो जाने के कारण परिषद कार्यालय के पास जमा बयानाराशि / प्रतिभूति निक्षेप को नवीन निविदा के लिए बायाना राशि / प्रतिभृति राशि के प्रति समायोजित नहीं किया जायेगा।
- 13. **बयाना राशि का समपहरण**:— बयाना राशि को निम्नलिखित मामलों में समपहरत कर लिया जायेगा:–
 - (क) जब बोलीदाता बोली खोलने के बाद किन्तू बोली को स्वीकार करने के पूर्व प्रस्ताव को वापस लेता है या उसमें उपान्तरण करता है।
 - जब बोलीदाता विर्निष्ट समय के भीतर विहित करार को निष्पादित नहीं (ख)
 - जब बोलीदाता प्रदायगी के लिए आदेश देने के बाद प्रतिभृति राशि जमा (ग) नहीं कराता हो।
 - जब वह निर्धारित समय के अन्तर्गत आदेशों के अनुसार कार्य करने में (ਬ) असफल रहता है अथवा संतोषजनक सेवाएं देने में असमर्थ रहता है।

14. करार एवं प्रतिभृति निक्षेप :—

- सफल बोलीदाता को आदेश दिनांक से 7 दिन की अवधि के भीतर (क) नियमानुसार मृल्य के नॉन ज्युडिशियन स्टॉम्प पेपर पर (जिसका व्यय स्वयं बोलीदाता द्वारा वहन किया जावेगा) एक करार-पत्र निष्पादित करना होगा तथा प्रावधित मुल्य जिसके लिए बोली स्वीकार की गई है।
- बोली के समय जमा कराई गई बयाना राशि को प्रतिभूति की राशि के लिए (ख) समायोजित किया जायेगा।
- बयाना / प्रतिभूति राशि पर परिषद द्वारा कोई ब्याज का भूगतान नहीं किया (₁)
- प्रतिभूति राशि के रूप में नकद रसीद पत्र/शिड्यूल बैंक का ड्राफ्ट/ (ਬ) बैंकर्स चैक मान्य होंगे।
- 15. प्रतिभृति राशि का समपहरण :- प्रतिभृति की राशि को पूर्ण अथवा आंशिक रूप से निम्नलिखित मामलों में समपहरत किया जायेगा:-
 - जब संविदा की किसी शर्त / अथवा शर्तों डिंग्लुम्ब चिम्स्या स्विद्धा जब बोलीदाता सम्पूर्ण कार्य संतोषजनक ढंग से करने में असफल हो।
 - (ख)
 - प्रतिभूति निक्षेप को समपहरत करने के मिंग्रीविश signeday Fair de a mid in secretary on a resignation secretary on a resignation secretary on a resignation secretary of the secr Reason: Appro

- (घ) कार्य में असफल रहने पर परिषद द्वारा वैकल्पिक व्यवस्था किये जाने पर उसमें जो भी व्यय होगा बोलीदाता से उसकी प्रतिभूति राशि में से अथवा उसको देय बिल की राशि के भुगतान में से की जायेगी। यदि वसूली करना सम्भव न हो तो राजस्थान पी.डी.आर.एक्ट या प्रवृत्त अन्य किसी कानून के अन्तर्गत कार्यवाही की जावेगी।
- 16. करार पत्र को पूर्ण करने एवं उस पर स्टाम्प लगाने का व्यय बोलीदाता द्वारा वहन किया जायेगा तथा परिषद को उस करार पत्र की निष्पादित स्टाम्प शुदा प्रति पडत निःशुल्क प्रस्तुत की जायेगी।
- 17. परिषद के प्राधिकृत अधिकारी या उसका विधिवत् प्राधिकृत प्रतिनिधि सभी युक्तियुक्त उचित समयों पर ठेकेदार के परिसर में जायेगा तथा वह विनिर्माण की प्रक्रिया के दौरान या उसके बाद जैसे भी हो किसी भी समय सामग्री का निरीक्षण एवं जांच करने की शक्ति रखेगा।
- 18. परीक्षण प्रभार परिषद द्वारा वहन किये जायेंगे। यदि बोलीदाता अत्यावश्यक तत्काल परीक्षण कराना चाहता है या यदि परिणामों से यह ज्ञात होता है कि प्रदाय किया गया सामान विहित स्तरों या विनिर्देशों के अनुसार नहीं है तो परीक्षण प्रभार बोलीदाता द्वारा वहन किये जायेंगे।
- 19. अनुमोदित कार्य के लिए यह समझा जाएगा कि उसने कार्य किये जाने वाले विनिर्देशों की सावधानीपूर्वक जांच कर ली है यदि उसे इन शतों, विनिर्देशों, रेखाचित्रों आदि के किसी भाग के आशय के बारे में कोई सन्देह हो तो वह संविदा पर हस्ताक्षर करने से पूर्व परिषद से स्पष्टीकरण प्राप्त करेगा।
- 20. सफल बोलीदाता को कार्य आदेश जारी तिथि के 10 दिवस के अन्दर कार्य प्रारम्भ करना होगा।
- 21. यदि निविदा सूचना में दर्शित मात्रा से अधिक के लिए आदेश दिया जाता है, तो निविदादाता अपेक्षित कार्य करने के लिए बाध्य होगा। पुनः आदेश भी निविदा में दी गयी शर्तों पर दिए जा सकेंगें परन्तु शर्त यह है, कि ऐसे पुनआदेश मूल रूप से खरीदी गयी मात्रा की 50 प्रतिशत तक के अतिरिक्त प्रदाय के लिए ही होगें।
- 22. <u>गारन्टी</u> :—गारन्टी नियमानुसार होगी।

23. <u>परिसमापित नुकसानी</u> :--

- (1) पिरसमापित नुकसानी के साथ कार्य अविध में वृद्धि करने के मामले में, वसूली राजस्थान लोक उपापन पारदर्शिता अिधनियम, 2012 एवं राजस्थान लोक उपापन पारदर्शिता नियम 2013 के प्रावधान अनुसार होगी।
- (2) यदि प्रदायकर्ता किन्ही बाधाओं के कारण संविदान्तर्गत कार्य का प्रदाय पूरा करने के लिए समय में वृद्धि कराना चाहता है, तो वह लिखित में परिषद को आवेदन करेगा। किन्तु वह उसके लिए निवेदन बाधा के घटित होने पर तुरन्त उसी समय करेगा न कि प्रदाय पूर्ण होने की निर्धारित तारीख के बाद करेगा।
- (3) यदि कार्य प्रदाय करने में उत्पन्न हुई बाधा बोलीदाता के नियन्त्रण से परे कारणों से हुई हो तो कार्य की अवधि में वृद्धि परिसमापित नुकसानी सहित या रहित की जा सकेगी।
- 24. <u>वस्ली</u> :—परिसमापित नुकसानी, कम प्रदाय, टूट्**Sig ratore valle** लए वसूली साधारण रूप से बिल में से की जीएगी। संवेदक र प्रदाय Digitally signed by Rais ndra Singh टूट—फूट, रद्द किए गए कार्यों की सीमा तक Designation Secured, सकेंगी तथा यदि सेवा सन्तोषजनक ढंग से उनको क्रिक्क 2025 08 29 14 कि. 14 कि.

नुकसानी के साथ वसूली उसे देय राशि एवं विभाग के पास उपलब्ध प्रतिभूति निक्षेप से की जाएगी। यदि वसूली करना सम्भव न हो तो राजस्थान पी डी आर एक्ट या प्रवृत्त अन्य कानून के अन्तर्गत कार्रवाई की जाएगी।

25. भगतान :-

- (क) बोलीदाता द्वारा क्रेता अधिकारी को उचित प्रारूप में लोक उपापन नियमों के अनुसार बिल प्रस्तुत करने पर भुगतान किया जायेगा। सभी प्रेषण प्रभार बोलीदाता द्वारा वहन किये जायेंगे। किसी भी सूरत में अग्रिम भुगतान नहीं किया जायेगा।
- (ख) विवादास्पद मदों में राशि का 10 प्रतिशत से 25 प्रतिशत तक को रोका जायेगा तथा उस विवाद का निपटारा हो जाने पर उसका भुगतान कर दिया जायेगा।
- (ग) उन मामलों में, जिनमें परीक्षण करने की जरूरत है, भुगतान तभी किया जायेगा जब उनका परीक्षण कर लिया जाये तथा प्राप्त हुए परीक्षण परिणाम विहित निर्देशों के अनुरूप हों।
- 26. यदि कार्य की तात्कालिक आवश्यकता के कारण पूर्ण या आंशिक रूप में उन कार्यों को बदलना साध्य नहीं समझा जाए तो राजस्थान राज्य क्रीडा परिषद द्वारा बोलीदाता को सुनवाई किये जाने का एक उचित अवसर देकर, ऐसे कारणों से जो अभिलिखित किये जायेंगे, अनुमोदित दरों में से उपयुक्त राशि की कटौती करेगा। इस प्रकार की गई कटौती अन्तिम होगी।
- 27. निविदादाता करार को निष्पादित करते समय निम्नलिखित दस्तावेज प्रस्तुत करेगा:-
 - (i) यदि भागीदारी फर्म हो तो "पार्टनरिशप डीड" की अनुप्रमाणित प्रति।
 - (ii) यदि भागीदारी फर्म रजिस्ट्रार ऑन फर्म्स के पास पंजीकृत हो तो पंजीयन संख्या एवं उसका वर्ष।
 - (iii) एक मात्र स्वामित्तव के मामले में आवास एवं कार्यालय का पता, टेलीफोन नम्बर।
 - (iv) कम्पनी के मामले में कम्पनी के रिजस्ट्रार के द्वारा जारी किया गया प्रमाण–पत्र।
- 28. संविदा के निर्वचन, आशय या संविदा की शतों के उल्लंघन के सम्बन्ध में या अन्य किसी भी प्रकार का विवाद होने पर परिषद का निर्णय अन्तिम होगा।
- 29. समस्त विधिक कार्यवाहियां यदि संस्थित किया जाना आवश्यक हो तो जयपुर स्थित न्यायालय में ही की जाएगी। अन्यत्र नहीं की जाएगी।
- 30. बोलीदाता द्वारा अपलोड किये जाने वालो दस्तावेजों पर नम्बरिंग होनी चाही एवं चैक लिस्ट भर कर प्रस्तुत करनी होगी।
- 31. सचिव, राजस्थान राज्य क्रीडा परिषद, जयपुर को बिना कारण बताये किसी भी बोली को स्वीकार / अस्वीकार करने का अधिकार होगा।
- 32. जी.एफ. एण्ड ए.आर.,राजस्थान लोक उपापन पारदर्शिता अधिनियम, 2012 एवं राजस्थान लोक उपापन पारदर्शिता नियम 2013 के प्रावधान लागू होगें।

Signature valid

aidicini के हस्त

Digitally signed by Raidical Singh

Designation, Secretary

Date: 2025, 08.29 18.16:04 IST

Reason: Approve

घोषणा

मैने / हमने राजस्थान में आयोजित होने वाले खेलों इंडिया यूनिवर्सिटी गेम्स-2025 हेत् आयोजन स्थलों / स्थानों (संभाग मुख्यालयों) पर आवश्यक रखरखाव / मरम्मत सैनेट्ररी कार्य के लिए (मय सामग्री) की बोली के नियम एवं शर्ती को भली-भॉति पढ व समझ लिया है। मुझे / हमारी फर्म को किसी भी विभाग द्वारा ब्लेक-लिस्ट नहीं किया गया है। इन शर्तों एवं नियमों के अधीन मैं / हम उक्त कार्य करने हेतू सहमत एवं वचनबद्ध हॅं / है। यदि मेरे / हमारे द्वारा की किसी बोली की शर्तों, नियमों अथवा आदेशों का उल्लंघन किया जावेगा तो सक्षम अधिकारी द्वारा मेरे / हमारे विरुद्ध बोली के नियम / शर्तों के उल्लंधन की कार्यवाही करने के लिए अधिकृत होगा। इस सम्बन्ध में मुझे / हमें सक्षम / अधिकृत अधिकारी द्वारा लिया गया निर्णय मान्य होगा तथा इसमें मुझे / हमको कोई आपत्ति / हस्तक्षेप नहीं है।

हस्ताक्षर बोलीदाता
नाम / पता
टेलीफोन नं
दिनांक

Signature valid

Digitally signed by Rajondra Singh Designation Secretary Date: 2025.08.29 17:16:04 IST

Reason: Appro

General Instructions for Filling of Bid

The complete bidding document has been published on the website www.rssc.in, http://sppp.raj.nic.in, http://eproc.raj.gov.in, for the purpose of downloading.

- 1. Bidders who wish to participate in this bidding process must register on www.rssc.in & http://sppp.raj.nic.in,
- 2. To participate in online bidding process, Bidders must procure a Digital Signature Certificate (Type III) as per Information Technology Act-2000 using which they can digitally sign their electronic bids. Bidders can procure the same from any CCA approved certifying agency, i.e. TCS, safe crypt, Node etc. Bidders who already have a valid Digital Signature Certificate (DSC) need not procure a new DSC.
- 3. Bidder (authorized signatory) shall submit their offer on-line in Electronic formats both for Technical and financial proposal. However, DD for Tender Fees, EMD payable in favor of SECRETARY RAJASTHAN STATE SPORTS COUNCIL, JAIPUR, payable at Jaipur and Processing Fees payable in favor of Managing Director, RAJCOMP Info Services Limited, payable at JAIPUR. Tender fee, EMD and processing fee DD should be submitted physically at the office of RAJASTHAN STATE SPORTS COUNCIL, JAIPUR, and Scanned copy of same should also be uploaded along with the technical bid.
- 4. RAJASTHAN STATE SPORTS COUNCIL, JAIPUR will not be responsible for delay in online submission due to any reason. For this, bidders are requested to upload the complete bid well advance in time so as to avoid Last hours issues like slow speed; choking of web site due to heavy load or any other unforeseen problems.
- 5. Bidders are also advised to refer "Bidders Manual Kit" available at e-Proc website for further details about the e-tendering process.
- 6. No contractual obligation, whatsoever shall arise from the bidding process unless and until a formal contract is signed and executed between the tendering authority and the successful Bidder.

SECRETARY

Signature yalid

Digitally signed by Raindra Singh

Reason: Appro

UNDERTAKING BY THE BIDDER

This is to certify that I/we before signing this tender have read and fully understood all the terms and conditions contained herein and undertake myself/ourselves to abide by them. I/We have signed all the pages in acceptance of the terms and conditions.

I/We also undertake that I/We will not adopt any malpractices at any stage of bidding/execution.

> Signature of the Bidder with Seal Name: Designation: Address:

> > Signature yalid

Digitally signed by Rajondra Singh Designation, Secretary Date: 2025.08.29 13:16:04 IST

Reason: Appro

BIDDER'S AUTHORIZATION CERTIFICATE {to be filled by the bidder}

	ering Authority},				
I/					
n}	hereby	declare/	certify	{ that	Name/Designatio
relevar RAJAS He/ Si inform	nt documents or STHAN STATE ! he is also author ation/ clarification purpose of valid	{Name/ behalf of the of SPORTS COUNC orized to attend ns as may be requ ation, his/ her veri hanking you,	Designation} company/ firm IL, JAIPUR. meetings & suired by you in t	in dealing values in technicate the course of p	with Tender with al & commercial
Author	of the Bidder: - rized Signatory: - f the Organizatior	ı: -		Veri	fied Signature:

Signature yalid

Digitally signed by Rajondra Singh Designation, Secretary Date: 2025.08.29 13.16:04 IST Reason: Approved

CHECKLIST OF DOCUMENTS SUBMITTED

S.	Documents to be submitted	Submitted	Not	Page No.
No.			Submitted	
1.	Scanned Copies of tender document fee, EMD			
	and processing fees			
2.	Copy of Registration of firms (S-I & Above			
	category for Sanitary works, Registration under			
	Govt. Departments of Rajasthan/India).			
3.	Copy of GST Registration			
4.	Copy of PAN Card			
5.	Proof of Work order and Satisfactory			
	Completion of Sanitary work should be as per			
	tender document condition no. 11 (iii) in			
	financial Year 2021-22, 2022-23 & 2023-24.			
6.	Certificate from Chartered Accountant having			
	UDIN for the proof of average annual			
	Turnover that must be equal/more than the cost			
	of work (bid cost) in the last three Financial			
	Years from 2021-22, 2022-23 & 2023-24.			
7.	Annexure A to D duly signed in context to			
	RTPP Rules-2013.			
8.	Authorization certificate If the tender is signed other than owners			
	2			
9.	Copy of GST paid certificate filed by June,			
	2025 Financial Year 2024-25 in GSTR-3B Performa			
10	Tender document and Technical Bid and			
10.	undertaking all three duly signed			
1.1	• • •			
11.	Any other Document			

Note: -1. The work executed under Govt. /Semi-Govt. / Autonomous Departments shall be considered for experience purposes.

- 2. Similar nature shall mean works related to Sanitary works.
- 3. Last Three FY for works means 2021-22, 2022-23 & 2023-24.
- 4. Last three FY for average annual turnover means 2021-22, 2022-23 & 2023-24.
- 5. The contractor should ensure that the Registration should be latest or updated.

Signature of Bidder Seal of Establishment Full Name of Bidder with address and date

Signature yalid

Digitally signed by Rair ndra Singh Designation, Secretary Date: 2025.08.29 13.16:04 IST

Reason: Appro

Estimate

Name of Work :- Development and Maintenance Works (Sanitary) for KIUG-2025

S.									
No .	Item No.	Praticular	Qty		Qty		Rate	Unit	Amount
1	S-1.2.2	P & F Indian type white glazed vitreous china 1st quality W.C. orissa pan (IS:2556 Mark) with 100 mm vitreous china P or S trap including cutting and making good the wall and floor: Size 580x440mm.	1.00	Nos	3080.00	Each	3080.00		
2	S-1.3	P & F European type white glazed vitreous china 1st quality W.C pan (IS: 2556 Mark) with P or S trap including cutting and making good the wall and floor	1.00	Nos	2420.00	Each	2420.00		
3	S-1.7.2	P & F water closet Seat Covers with brass hinges complete: Solid PVC (IS 2548 marked) grade-I White for EWC.	1.00	Nos	485.00	Each	485.00		
4	S-1.9	Labour charges for removing W.C. pan (any type) of all sizes with care including all necessary fittings P or S trap.	1.00	Nos	286.00	Each	286.00		
5	S-1.11	P & F vitreous china P trap of approved quality	1.00	Nos	215.00	Each	215.00		
6	S-1.14.2	P & F lst quality WVC Urinal (IS:2556 mark) with 25mm dia G.I. waste pipe, dome waste couplings, concealed iron brackets or screws etc complete. Flat Back (large) or half stall size 610x400x80mm.	1.00	Nos	4637.00	Each	4637.00		
7	S-1.16.1	P&F Marble <i>Urinal Partition slab</i> both sides polished of approved design cut from marble size 900x600mm. Makrana II quality marble having light spots	1.00	Nos	923.00	Each	923.00		
8	S-1.19	Labour charges for removing and refixing of urinals (all type & sizes) including all necessary fittings.	1.00	Nos	339.00	Each	339.00		
9	S-2.14	P & F Flush Cock / Flush Valve (IS: 9758 Mark) for WC of approved quality make:							
a	S-2.14.5	(-do-) concealed 25mm nominal bore.	1.00	Each	975.00	Each	975.00		
b	S-2.14.9	Brass / Gun metal Half-turn wt. 1 Kg. of approved quality / make, 25mm nominal bore.	1.00	Each	551.00	Each	551.00		
10	S-1.33	Removing and re-fixing of wash hand basin including all necessary fittings.	1.00	Nos	239.00	Each	239.00		
11	S-1.36	P & F WVC wash basin (1st quality, I.S.: 2556 Mark) of approved make with C.I. brackets duly painted, 1 No. 15 mm C.P. Pillar cock (IS: 8934 Mark) & 32 mm C.P. brass waste coupling of approved make,25 mm G.I. waste pipe complete including cutting & making good the wall.:							
a	S-1.36.4	Size 580 mm x 450 mm		Each	2745.00	Each	2745.00		
b	S-1.36.8	Size 550 mm x 400 mm dia for counter top	1.60		atur	CEN	1 4 .00		
12	S-1.41	P & F Bottle Trap of approved make:	Di	gitally	signed b	y Rajy nd	ra Singh		
a 12	S-1.41.1	C.P Brass 40 mm P& F waste Pipe with all fitting P.V.C with	1.00	signa	tion (**) ed 254) 8.2 9	retary	584.00 4 IS4F.00		
13	S-1.43.1	P& F waste Pipe with all fitting P.V.C with			Approve		# 14 0 40.00		

теазоп. дррго

		C.P nut 32 mm					
14	S-1.44	P & F Bevelled edge Mirror/mirror with teak wood lipping around of special glass of approved make as per direction of Engineerin-charge complete with 6mm thick commercial ply base fixed to wooden screws & washers.					
a	S-1.44.1	Size 600 x 450mm x 4 mm thick	1.00	Nos	575.00	Each	575.00
b	S-1.44.2	Other sizes	1.00	Sqm	1538.00	Sqm	1538.00
15	S-1.47	P & F Towel Rail or Ring of approved quality/make:					
a	S-1.47.2	C.P. brass Towel Rail elbow type with concealed screws size 600 mm (Heavy duty).	1.00	Nos	516.00	Each	516.00
b	S-1.47.8	C.P. Brass Towel Ring revolving type	1.00	Nos	254.00	Each	254.00
16	S-1.48.2	P & F Grating of approved quality/make:Stainless Steel Sheet size 125mm dia. Heavy Quality of approved make	1.00	Nos	97.00	Each	97.00
17	S-1.51.2	P & F <i>Toilet Paper Holder</i> with rod of approved quality/make: C.P. brass heavy & Superior quality.	1.00	Nos	602.00	Each	602.00
18	S-1.52.2	P & F Soap Dish or Tray of approved quality/make C.P. brass heavy and superior quality.	1.00	Nos	156.00	Each	156.00
19	S-1.53.2	P & F Twin- peg of approved quality / make C.P. brass (heavy)Superior quality	1.00	Nos	149.00	Each	149.00
20	S-1.54.4	P & F Shower arm 15mm dia of approved quality/make. C.P.brass heavy & superior quality 370mm Projection.	1.00	Nos	376.00	Each	376.00
21	S-1.55.3	P & F Bath Shower of approved quality/make. C.P. brass of Heavy & superior quality, revolving with adjustable key 150mm.	1.00	Nos	573.00	Each	573.00
22	S-1.56.2	P & F Extension Pipe for bib cocks of approved quality/make. C.P. brass of Heavy & Superior quality 5100x15mm	1.00	Nos	119.00	Each	119.00
23	S-1.60	Providing & fixing C.P.flange for 15mm dia taps.	1.00	Nos	18.00	Each	18.00
24	S-1.61	Providing and fixing 1st quality standard white, grey, ivory, fume red brown, light green, light blue and other light shades glazed tiles confirming to IS: 13753 & IS:15622 of size 200mm x 300mm in walls, floors, steps, pillars etc. laid on a bed of neat cement slurry finished with flush pointing in the white cement mixed with pigment to match the shade of the tile complete (excluding the cost of cement plaster on walls and pillar).	1.00	sqm	674.00	P.Sqm	674.00
25	S-1.64	Extra for using size above 200x300mm in glazed tiles and for using 400mm x 400mm MAT finished tiles in place of 300mm x 300mm size.	1.00	Sqm	6.74	P.Sqm	6.74
26	S-1.62	Providing and fixing 1st quality MAT finished ceremic tile size 300x300mm confirming to IS: 13755 and IS: 15622 colour such as white, grey, ivory, fume red brown, light green, light blue and other light shades in floors, steps, pillars etc. laid on a bed of neat cement slurry finished with flush pointing in the white cement mixed with pigment to match the shade of the tile complete (including the cost of cement mortar bed 1:4).	Di	gitally	signed by	y Rajond	ra Singh
		,	Re	eason:	Approve	1	

				ı			
27	B-11.27	Filling of sunk portion of roof with earthen pots of required height including filling voids with 1:3:6 light concrete, using brick bats complete levelling and dressing the surface by 50mm thick cement concrete 1:2:4 as per specification.	1.00	Cum	1775.00	P.Cum	1775.00
28	S-1.67	Removing & Re fixing of P.V.C. Cistern fittings (Syphon, Ball cock & Handle Set) complete as per direction of Enginner-in-Charge	1.00	Nos	468.00	Each	468.00
29	S-2.1	P & F <i>G.I. pipes (Internal Work)</i> with G.I. Fittings excluding union (IS:1239 Mark) & MS clamps including cutting and making good the walls and floors:					
a	S-2.1.1	Concealed pipe in wall including painting with anticorrosive bitumen paint 15 mm dia nominal bore 'B' Class	1.00	Mtr	230.00	P.Mtr	230.00
b	S-2.1.3	Exposed on wall 25 mm dia nominal bore B class	1.00	Mtr	360.00	P.Mtr	360.00
30	S-2.3	Making connection of G.I. distribution branch with G.I. main including all fitting.					
a	S-2.3.1	Upto 25mm dia	1.00	Nos	265.00	Each	265.00
ь	S-2.3.2	Beyond 25mm & upto 100mm dia	1.00	Nos	389.00	Each	389.00
31	S-2.6	P & F Pilllar Cocks (IS :8934 Mark) of superior quality and approved make:					
a	S-2.6.1	C.P. Pillar cock, 15 mm dia nominal bore	1.00	Nos	779.00	Each	779.00
b	S-2.6.6	Synthetic Material (PTMT) Pillar cock of approved quality / make 15mm nominal bore.	1.00	Nos	388.00	Each	388.00
32	S-2.7	P & F Bib Cock (IS: 8931 Mark), Superior quality of approved make:					
a	S-2.7.3	C.P. Brass bib cock,15mm nominal bore.	1.00	Each	590.00	Each	590.00
b	S-2.7.4	(-do-) Long body, 15mm nominal bore weight not less than 690 gm	1.00	Each	783.00	Each	783.00
c	S-2.7.9	Synthetic Material(PTMT) bib cock of approved quality/ make, Long Body, 175 mm long	1.00	Each	295.00	Each	295.00
33	S-2.10	P & F <i>Push Cock</i> superior quality, of approved make					
a	S-2.10.1	C.P. Brass 15 mm.	1.00	Each	370.00	Each	370.00
b	S-2.10.2	Synthetic Material (PTMT) push cock of approved quality/make 15mm.	1.00	Each	205.00	Each	205.00
34	S-2.11	P & F Ball Cock (IS :1703 Mark) with Rod & P.V.C. Ball complete :					
a	S-2.11.1	Brass wt. Not less than 300 gm,15mm.	1.00	Each	314.00	Each	314.00
b	S-2.11.3	(-do-) wt.Not less than 600 gm, 25mm.	1.00	Each	440.00	Each	440.00
с	S-2.11.4	(-do-) wt.Not less than 800 gm, 32mm.	1.00	Each	480.00	Each	480.00
35	S-2.12	P & F Inlet Connection (Angle Valves) Superior quality, of approved make, for Wash basin, Gyser etc.					
a	S-2.12.2	do with 37 cm long thread and nut	1.00	Each	590.00	Each	590.00
b	S-2.12.4	Synthetic Material (PTMT) Inlet connection of approved quality/make 15 mm nominal size.	1.	igr	atur	e ya	li c 0.00
36	S-2.13.3	P & F 15 mm. Dia Connection Pipe of approved quality/make: PVC pipe with C.P. Brass nuts upto length, 450mm	l De	signa	signed by	retary	ra Singh 1 IST
					Approve	. 10.02	101

Reason: Approver

		D 0 F F # 1/ 1 (IS 770 M 1) 1 1					
37	S-2.15	P & F <i>Full-way Valve</i> (IS:778 Mark) or wheel valve of approved make :					
a	S-2.15.1	Gun-metal 15mm nominal bore.	1.00	Each	227.00	Each	227.00
ь	S-2.15.3	(-do-) 25mm nominal bore.	1.00	Each	529.00	Each	529.00
c	S-2.15.6	(-do-) 50mm nominal bore.	1.00	Each	1464.00	Each	1464.00
38	S-2.26	P & F <i>PVC Storage Tank</i> ISI Marked (IS: 12701) indicating the BIS license No), of approved make with cover, 25mm dia 1M long G.I. over-flow pipe & 25 Cm. long wash out pipe with plug & socket, including making connection etc., complete of approved design:					
a	S-2.26.2	300 litres capacity	1.00	Nos	2352.00	Each	2352.00
ь	S-2.26.3	500 (-do-)	1.00	Nos	3920.00	Each	3920.00
c	S-2.26.5	1000 (-do-)	1.00	Nos	7841.00	Each	7841.00
39	S-2.27.2	Hoisting Charges for each floor : For water tanks	1.00	Nos	157.00	Each	157.00
40	S-2.32	Supply & fixing G.I. Union ISI marked in G.I. pipe line as required complete in all respect of size:					
a	S-2.32.1	15mm dia nominal bore	1.00	Nos	101.00	Each	101.00
b	S-2.32.3	25mm dia nominal bore	1.00	Nos	164.00	Each	164.00
С	S-2.32.6	50mm dia nominal bore P & F Square-mouth gully trap `A` grade (IS)	1.00	Nos	463.00	Each	463.00
41	S-3.5.2	651-1992 :marked) of approved make complete with C.I. grating, frame & Cover masonary chamber in C.M. 1:6, 100mm thick C.C. 1:5:10 base concrete, 40mm thick C.C.M-15 grade coping, 12mm thick cement plaster in CM 1:3 complete as per approved design & type. Trap size 225 X 150 mm, ferrow cement cover with frame Internal Chamber size 450 X 450mm.	1.00	Nos	1529.00	Each	1529.00
42	S-3.18.2	Raising manhole cover and frames slab to required level including dismantling existing slab and making good the damage as required (raising depth of manhole masonry to be paid separately). Rectangular manhole 150x120 cm	1.00	Nos	1487.00	Each	1487.00
43	S-3.19	Construction of manhole in all type of soil inner size 90 X 60 Cm. 300 mm thick masonry in CM 1:6, 10 Cm. thick cement concrete 1:5:10 in foundation, 20 mm thick inside plaster in CM 1:6, finished with floating neat cement, 50mm thick M-15 grade C.C. flooring, making channels, 80mm thick stone slab covering with 40mm thick M-15 grade C.C. flooring, Cement cover with frame of 450mm dia, earthwork etc. complete as per design including disposal of surplus earth within 50 mtr. lead.					
(a)	S-3.19.1	Depth up to 0.5 M	1.00	Nos	5489.00	Each	5489.00
(b)	S-3.19.2	Add extra over item 3.19.1 for every additional 0.10m depth above 0.5 m depth.	1.00	Nos	206.00	Each	206.00
44	S-3.40.2	Providing & fixing Spun —Centrifugally cast Iron Pipes (IS: 3989 Mark) of Approved make in wall or in floor with M.S. Holder bat clamps in 10 X 10 X10 Cm. M-15 Grade concrete blocks, joints filled with CM 1:4 with spun yarn including cutting holes and making good the wall:- 100 mm dia	1.00 Dig De Da	Mtr gitally signa te: 20	1299.00 signed by tion Sec 25.08.29 Approve	P Rair nd retally 15:16:0	1299.00 ra Singh

	G 2 41	Providing & fixing Spun –Centrifugally cast					
45	S-3.41	Iron Pipes fitting (IS: 3989 Mark) in CM 1:4 with spun Yarn.					
a	S- 3.41.2(i)	100mm w/o door Offset	1.00	Nos	809.00	Each	809.00
b	S- 3.42.2(ii)	100mm w/o door Socket	1.00	Nos	519.00	Each	519.00
с	S- 3.41.2(iv)	100mm w/o door Bend	1.00	Nos	655.00	Each	655.00
d	S- 3.41.2(vi)	100mm w/o door Cowel	1.00	Nos	529.00	Each	529.00
f	S- 3.41.5(iii)	100mm with door Tee	1.00	Nos	989.00	Each	989.00
46	S-3.42.1	Providing and Fixing Spun –Cast Iron floor trap (Nahani) of (IS :3989 Mark) approved quality / make with socket down or hinged grating including cutting and making good the floor :- Size 100 x 100 mm	1.00	Nos	1000.00	Each	1000.00
47	S-3.10.2	Add extra for <i>Lead caulked joints</i> (IS:782-1978) in sand cast iron pipes/spun- 100mm dia, 0.98 Kg. Pig lead	1.00	Nos	344.00	Each	344.00
48	S-3.46.1	Providing & fixing Spun –Centrifugally cast Iron Pipes fitting (IS: 3989 Mark) in CM 1:4 with spun Yarn 100mm w/o door as per direction of Engineer-in-Charge. P Trap of standard size	1.00	Nos	936.00	Each	936.00
49	S-3.39.2	Construction of Cement Concrete Chamber 125mm dia on depressed floor upto 45cm height from floor with : C.P. doom grating	1.00	Nos	263.00	Each	263.00
50	B-14.3	Demolishing R.C.C. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge.	1.00	Cum	930.00	P.Cum	930.00
51	B-14.23.1	Dismantling tile work in floors and roofs laid in cement mortar including stacking of serviceable material and disposal of unserviceable material within 50 meter lead: For thickness of tiles 10mm to 25mm.	1.00	Sqm	20.00	P.Sqm	20.00
52	B-14.43.1	Dismantling GI pipes (external work) including excavation and refilling trenches after taking out the pipes and including stacking of pipes within 50 meter lead: 15mm to 40mm nominal bore.	1.00	Mtr	41.00	P.Mtr	41.00
53	B-14.44.1	Dismantling CI pipes including excavation and refilling trenches after taking out the pipes, breaking lead caulked joints, melting of lead and making into block, including stacking of pipes lead at site within 50 meter, of dia: Up to 150mm dia.	1.00	Mtr	109.00	P.Mtr	109.00
54	B-14.50	Dismantling of gully chamber of various sizes including CI grating with frame including stacking of useful materials near the site and disposal of unserviceable material within 50 meter lead including refilling the gap.	1.00	Nos	255.00	Each	255.00
55	B-14.55	Dismantling old plaster or skirting, raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 meter lead.	1.00 je	samy	signed by	y Kajond	
56	B-14.58.2	Making of hole (width up to 150 mm) in	l ₁Æaa	te: 20	25.58.29 Approve	12. 16:04	4 IST.00

		R.C.C. slab/wall/beams by power driven	1				
		drilling machine complete as per direction of EI above 150 mm thick					
57	B-12.2.1	Plaster on new surface on walls in cement sand mortar 1:4 including racking of joints etc. complete fine finish: 25mm thick	1.00	Sqm	227.00	P.Sqm	227.00
58	B-12.7	Finishing with neat cement (punning).	1.00	Sqm	36.00	P.Sqm	36.00
59	B-5.8.2	Half brick masonry in Superstructure, above plinth level upto floor V level using bricks of designation 75 Cement mortar 1:4 (1 cement: 4 coarse sand)	1.00	Sqm	553.00	P.Sqm	553.00
60	B-7.5.3	Providing and fixing Granite stone slab mirror polished and machine edge cut in walls, pillars, steps, Shelves, Sills Counters, Floors etc. laid on 12mm (Av.) thick base of cement mortar 1:3 (1 cement : 3 coarse sand) jointing with white cement mortar 1:2 (1white cement : 2 marble dust) with pigment to match the shade of the marble slab including grinding, rubbing and polishing complete. South zed Black Above 3601 Cm2 Slabs	1.00	Sqm	4076.00	P.Sqm	4076.00
61	B-7.2.3	Providing and fixing Marble stone flooring table rubbed, 15-18 mm thick over 20mm (Av.) thick base of CM 1:4 (1 cement : 4 coarse sand) jointing with white cement mortar 1:2 (1 white cement : 2 marble dust) with pigment to match the shade of the marble slab including grinding, rubbing and polishing complete. Rajnagar 1st quality/Ageria with light spots.Above 3601 Cm2 Slabs	1.00	Sqm	1305.00	P.Sqm	1305.00
62	B-7.6.1	Extra for providing edge moulding to 15-18mm thick marble/ Granite stone counters, Vanities etc. including machine polishing to edge to give high gloss finish etc. complete as per design approved by Engineer-in-Charge. Granite/ Kota stone Work. Full edge moulding.	1.00	Mtr	146.00	P.Mtr	146.00
63	B-7.7	Extra for providing opening of required size & shape for wash basins/ kitchen sink in kitchen platform, vanity counters and similar location in marble/Granite/stone work including necessary holes for pillar taps etc. including rubbing and polishing of cut edges etc. complete	1.00	Nos	256.00	Each Opening	256.00
64	B-3.1.3	Providing and laying in position cement concrete including curing, compaction etc. complete in specified grade excluding the cost of centering and shuttering - All work up to plinth level. M15 grade Nominal Mix 1: 2: 4 (1 cement : 2 coarse sand : 4 graded stone aggregate 40mm nominal size).	1.00	Cum	4544.00	P.Cum	4544.00
65	B-14.3	Demolishing R.C.C. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge.	1.00	Cum	930.00	P.Cum	930.00
66	S-3.17	P&F rigid PVC pipe fittings (IS: 4985 mark) of approved quality /make including joining the pipe with solvent cement rubber ring and lubricant:	Di	gitally	signed by tion Section 25.08.29	y Rajond	ra Singh
a	S-3.17.3	Plain Tee	Da	ite: 20	25.0 8.2 9 Approve	16:04	4 IS I
			1/6	-aouii.	~hhi o		

i	S-	75mm dia	1.00	Each	114.00	Each	114.00
ii	3.17.3(i) S-	110mm dia	1.00	Each	187.00	Each	187.00
	3.17.3(ii)	Di ' (I	1.00	Buch	107.00	Buen	107.00
b	S-3.17.18	Plain floor trap					
i	S-3.17.18	110mm dia	1.00	Each	230.00	Each	230.00
c	S-3.17.12	Vent Cowel					
i	S- 3.17.12(ii)	110mm dia	1.00	Each	56.00	Each	56.00
d	S-3.17.9	Bend 87 .5					
i	S- 3.18.9(ii)	110mm dia	1.00	Each	161.00	Each	161.00
67	S-3.45	Providing and Fixing Unplasticized Poly Vinyl Chloride (UPVC) SWR Pipes fittings type B for sciland waste discharge system (IS:13592 : 1992 Marked) of approved quality/make					
a	S-3.45.20	Offset 110mm dia	1.00	Each	282.00	Each	282.00
68	S-2.8	P & F Stop Cock (IS:8931 Mark), superior quality & of approved make:					
a	S-2.8.4	C.P. Brass 15mm nominal bore.	1.00	Each	477.00	Each	477.00
b	S-2.8.5	C.P. Brass Concealed Stop Cock 15mm	1.00	Each	1009.00	Each	1009.00
69	S-3.16	P&F rigid <i>PVC Pipe</i> (IS:4985 mark) class II/ (4 Kg. /Cm ² .) approved quality /make including joining the pipe with solvent cement rubber ring and lubricant.					
a	S-3.16.2	75 mm dia	1.00	Mtr	177.00	P.Mtr	177.00
ь	S-3.17.3	110 mm dia	1.00	Mtr	282.00	P.Mtr	282.00
70	S-1.20	P & F Low level Flushing Cistern of 10 litres capacity (IS: 2556mark). Of approved make with complete fittings C.I. brackets duly painted, brass ball cock with ball, (IS: 1703 mark) complete including cutting and making good the wall:					
a	S-1.20.5	PVC with CP brass long band.	1.00	Each	1491.00	Each	1491.00
71	S-1.59	P & F <i>Jet spray</i> for water closet with C.P. Copper Tube flange of approved make.	1.00	Each	381.00	Each	381.00
72	S-2.1.6	P & F G.I. pipes (Internal Work) with G.I. Fittings excluding union (IS:1239 Mark) & MS clamps including cutting and making good the walls and floors:50mm dia nominal bore 'B' Class	1.00	Mtr.	673.00	Mtr.	673.00
73	S- 2.16.1(i)	P & F Gun-metal Non-return Valve or Check Valve (IS :Make) of approved make, superior quality: (a) 15mm nominal bore- Horizontal	1.00	Each	272.00	Each	272.00
74	S-2.21-1	P & F <i>Mixing Range</i> (15mm) C.P. One hole/close hole basin mixer with casted spout.	1.00	Each	1740.00	Each	1740.00
75	S-1.29.1	P & F C.P. brass <i>Urinal Spreader</i> for stall urinal of approved make.	1.00	Each	363.00	Each	363.00
76	S-1.42.2	P& F waste Coulping with fittings of approved quality /make: C.P Brass 40 mm dia	1.00	Each	218.00	Each	218.00
77	S-3.27.2	Construction of septic Tank in all types of soil with 40 Cm .thick masonry in CM 1:6, 15 Cm thick C.C bed of 1:5:10, M-15 grade C.C flooring & over stone slab covering ,80 mm thick slab ,jointing of slab in CM 1:3. Ralthal, Kharanja, 50 mm thick stone partition walls,	1.Mig De Da	gitally signa ite: 20	signed by tion Sec 25.08.29 Approve	y Rajond retaly 15:16:04	rasSiongoh

		20 mm thick plaster in CM 1:6 finished with neat floating cement, 4 Nos C.I foot rests of approved design ,two No. 450 mm dia each Ferro cement cover with frame, earth work etc. complete as per approved drawing including disposal of surplus earth within a lead of 50 mtr:- Size 230 x110 x150 cm.(for 20 users) with 115 mm thick RCC (M-20) slab with Tor steel reinforcement 10mm \$\phi\$ @15 cm c/c bothways including shuttering complete in all respect.					
78	S-3.28	Emptying of Septic tank ,Soakage well etc. by disposing or sludge upto 5 Km. lead & taking out sewage including cleaning of site.	1.00	Cum	286.00	P.Cum	286.00
79	S-3.33.4	Supplying & Fixing R.C.C. Manholes covers with frame of approved make (Light duty). Size 600 X 600mm (Double seal)	1.00	Each	502.00	Each	502.00
80	S-3.22.1	Construction of soakage well in all type of soil with 300 mm thick dry masonry, top and bottom 300 mm course in CM 1:6, 80mm thick stone slab, jointing of slab in CM 1:3, Ralthal, Kharanja, 40 mm thick M-15 grade C.C flooring, earthwork complete as per approved drawing including disposal of earth within a lead of 50 mtr.: Size 300 Cm. dia outside & 300 Cm. depth.	1.00	Each	24135.00	Each	24135.00
81	S-3.24.1	Construction of Soakage well in all types of soil of approved drawing, top 90 Cm. Portion in 450mm thick masonry with CM 1:6, 80 mm thick stone slab covering, jointing of slab in CM 1:3, Ralthal, kharanja 40mm thick M-15 grade C.C flooring, earth work etc. complete including disposal of surplus earth within a lead of 50 mtr. Inner dia 90 Cm & 10 to 12 Mtr deep.	1.00	Each	5478.00	Each	5478.00
82	S-3.1.2	Providing Laying & jointing glazed S.W. pipes grade 'A' (IS;651 marked) of approved make with spun yarn & stiff mixture of cement mortar 1:1, excavation & refilling of earth in all types of soil upto 1.2m depth, S.W. fittings, including testing of joints etc, complete. 150mm dia	1.00	Mtr.	406.00	P.Mtr	406.00
83	S-3.3.2	Providing & Laying C.C. 1:5:10 (Stone aggregate 40mm nominal size) upto haunches of S.W. pipes including 150 mm thick bed concrete (Width W= Dia of pipe in Cm+30Cm.) concrete width to be reduced from width W at center of pipe to '0' at top of pipe. (Excluding cost of pipe) 150mm dia S.W. pipe	1.00	Mtr.	353.00	P.Mtr	353.00
84	S-3.21.2	Construction of <i>chamber</i> in all type of soil with 300 mm thick masonry in CM 1:6 m,10 cm thick C.C. 1:5:10 in foundation, 20mm thick insider plaster in Cm 1:6, finished with floating neat cement, 50mm thick M-15 grade C.C. flooring, earthwork etc. complete as per design including disposal of surplus earth within a lead of 50 mtr. Inside size 450 x 450mm depth upto 0.5 M Cement cover with frame		•	2332.00 latur		2332.00 lid ra Singh
85	S-1.67	Removing & Re fixing of P.V.C. Cistern fittings (Syphon, Ball cock & Handle Set) complete as per direction of Enginner-in-	1.%	signa te ^{ac} 20	tion Sec 25:08.29 Approve	retally 12:46:0	4 1 \$1 8.00

		Charge					
86	S-2.23.1	P & F foot valve of superior quality and approved make with fittings: Brass 25 mm.	1.00	Each	172.00	Each	172.00
87	B-13.32	Mechanised cleaning of storage tanks comprises of following 6 stage as mentioned below : 1. Mechanical dewatering 2. Desalting removal of leftover dirty water and sludge with sludge pump 3. Cleaning of wall, ceiling and floor by high pressure water jet with help of equipments which creates a pressure of 100-150 bar 4. Removal of remaing sludge from floor with the help of industrial vacuum cleaner. 5. Spraying of non toxic, bio degradable ecofriendly and bacterial agent certified by a govt approved laborary to disinfect the tank from all harmfull pathogens. The dose should be safe as per the UECD guidelines & 23 adopted on 17 th december 2001. 6. Treatment of inside tank by exposing UV radiation to kill further suspended or floating bacteria if any					
a	13.32.1	Upto 500 ltr.	1.00	Ltr.	0.40	P.litres	0.40
b	13.32.2	Above 500 ltr. to 1000 Ltr.	1.00	Ltr.	0.35	P.litres	0.35
С	13.32.3	Above 1000 ltr.	1.00	Ltr.	0.30	P.litres	0.30
88	S-1.38.9.3	P & F Kitchen & Lab. Sink of approved make with C.I. brackets duly painted, 40 mm C.P. waste coupling, C.P. Brass chain with rubber plug, 40 mm G.I. waste pipe up-to floor level complete including cutting and making good the wall & floor: 1.0 mm thick Salem stainless steel AISI -304 & IS 13983-1994 kitchen sink of approved make as per Engineer-in-charge with large waste coupling. 24 x 18 x 8 20x16x8	1.00	Each	5062.00	Each	5062.00
89	S-1.65	P & F C.P. Health Faucet with 1Mtr. Long Tube & Hook of approved make and heavy as per direction of Enginner-in-Charge	1.00	Each	605.00	Each	605.00
90	S-2.6.4	C.P. Pillar cock, Swan-neck with casted spout, 15mm nominal bore.	1.00	Each	1246.00	Each	1246.00
91	S- 2.33.6	Providing and fixing Superior quality CP Brass fittings of approved make as per direction of Engineer-in-charge Angular stop cock with long thread 15 mm nominal size	1.00	Each	762.00	Each	762.00
92	S- 2.33.5	Providing and fixing Superior quality CP Brass fittings of approved make as per direction of Engineer-in-charge Two way Bib Cock 15 mm nominal size	1.00	Each	1174.00	Each	1174.00
93	S- 2.21.7	P & F Mixing Range (15mm) C.P. wall mixer telephonic type crutch & telephonic shower.	1.00	Each	2541.00	Each	2541.00
94	S- 2.21.3	P & F Mixing Range (15mm) C.P. sink mixer with swinging spout J-pipe.	1.00	Each	1876.00	Each	1876.00
95	S-3.16.4	P&F rigid PVC Pipe (IS:4985 mark) class II/ (4 Kg. /Cm2.) approved quality /make including joining the pipe with solvent cement rubber ring and lubricant. 160 mm dia	Di	gitally	atur	y Rajond	
96	S-2.33.18	Providing and fixing Superior quality CP Brass fittings of approved make as per	De 1. 0 0a	signa tēª∕20	tion Sec 25:08.29 Approve	reta y 18:448:04	

		direction of Engineer-in-charge 190 mm rain shower					
97	S-2.33.19	Providing and fixing Superior quality CP Brass fittings of approved make as per direction of Engineer-in-charge Shower arm	1.00	Each	1210.00	Each	1210.00
98	S-1.18	P & F W.V.C. (IS: 2556 Mark) Squatting Urinal of standard make complete. Including cutting & making good the floor: Size 450x350mm	1.00	Each	853.00	Each	853.00
99	S-3.21.1	Construction of chamber in all type of soil with 300 mm thick masonry in CM 1:6 m,10 cm thick C.C. 1:5:10 in foundation, 20mm thick insider plaster in Cm 1:6, finished with floating neat cement, 50mm thick M-15 grade C.C. flooring, earthwork etc. complete as per design including disposal of surplus earth within a lead of 50 mtr. Inside size 300 X 300 mm depth upto 0.5 M Cement cover with frame.	1.00	Each	1049.00	Each	1049.00
100	S-4.25.2	Supply & fixing Pre-cast RCC Rinngs at the mouth of recharge shaft of M20 mix with 40 mm thickness Diameter 750 mm	1.00	Rm	666.00	Rm	666.00
101	B-11.3.2	Cement concrete flooring 1:2:4 (1 cement: 2 coarse sand: 4 graded stone aggregate) finished with a floating coat of neat cement including cement slurry, making of lines or groove etc complete but excluding the cost of nosing of steps etc. complete. 75mm thick with 20mm thick nominal size aggregate.	1.00	Sqm	458.00	Sqm	458.00
102	B-5.2.1	Brick work with F.P.S. bricks of class designation 75 in superstructure above plinth level upto floor V level in all shapes and sizes in: Cement mortar 1:4 (1 cement: 4 coarse sand)	1.00	Cum	5196.00	Cum	5196.00
103	B - 6.1.6	Random Rubble stone masonry for with hard stone in foundation and plinth in Cement Sand mortar above 30 CM thick wall in: Cement Mortar 1:6 (1-Cement: 6-Sand).	1.00	Cum	2838.00	Cum	2838.00
104	B-10.16	Stone slab roofing on ground floor with fine grained stone slab from approved quarry including filling of joints of parapet and slab on both sides in cement sand mortar 1:4, with ceiling pointing in cement sand mortar 1:3 complete as per specification and instruction of Engineer In Charge	1.00	Sqm	1648.00	Sqm	1648.00
105	B-10.16.1	Add extra for subsequent story (Rs. 1648 of 20% Rate)	1.00	Sqm	329.60	Sqm	329.60
106	В-1.8	Earth work in excavation by mechanical means (Hydraulic Excavator)/ manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sum on plan) including dressing of sides and ramming of bottoms, lift upto 1.5 m, including taking out the excavated soil and depositing and refilling of jhiri with watering & ramming and disposal of surplus excavated soil as directed with in a lead of 50 meter. All kinds of soils	1.00	_{Cum}	178.00	Cum	178.00
107	B-3.1.2	Providing and laying in position cement concrete including curing, compaction etc. complete in specified grade excluding the cost of centering and shuttering - All work up to	1.00e	signa te: 20	signed by tign Sec 25.08.29 Approve	retz (M 19:16:0	4624.00

	plinth level. M15 grade Nominal Mix					
	1: 2: 4 (1 cement : 2 coarse sand : 4 graded					
B-7.18.2	tiles on floor, skirting and steps etc.in different sizes (thickness to be specified by manufactuer) with water absortion less than 0.08% and conforming to IS 15622 of approved make in all colour and shade, laid with 20 mm thick CM 1: 4 including grounting the joints with white cement and matching pigment etc complete. size 600 mm	1.00	Sqm	911.00	Sqm	911.00
B - 7.19	Vitrified floor tiles with cement based high polymer modified quick-set tile adhesive (Water based) conforming to IS: 15477, using 5kg. adhesive per sum of tile area, in average	1.00	Sqm	128.00	Sqm	128.00
	Providing and laying water proofing treatment					
B-15.3	in sunken portion of WCs, bathroom etc., by applying cement slurry mixed with water proofing cement compound consisting of applying: a) first layer of slurry of cement @ 0.488 kg/sqm mixed with water proffing cement compound @0.253 kg//sqm .This layer will be allowed to air cure for 4 hours.b) Second layer of slurry of cement @ 0.242 kg/sqm mixed with water proffing cement compound @ 0.126 kg/sqm This layer will be allowed to air cure for 4 hours followed by water curing for 48 hours.The rates includes preparation of surface treatment & sealing of all joints ,corners, junction with polymer mixed slurry.	1.00	Sqm	275.00	Sqm	275.00
G-4.1	Carriage of Building Rubbish Stone metal (Grit and ballast etc.) including loading unloading etc. complete with all lead. 1 Km.	1.00	Cum	80.00	Sqm	80.00
S-1.68.4	Providing & Fixing Premium Quality white glazed vitreous china Sanitary Wares (IS:2556 Mark) of approved make as per direction of Engineer-in-charge including cutting and making good the wall and floor. Double Syphonic European W.C. with mounted W.V.C. flushing cistern of 10 litre capacity complete with all necessary internal fittings with Hydraulic seat cover.	1.00	Each	17839.00	Each	17839.00
S-3.27.3	Construction of septic Tank in all types of soil with 40 Cm. thick masonry in CM 1:6, 15 Cm thick C.C bed of 1:5:10, M-15 grade C.C floor & RCC slab covering with M15 grade c.c. floor, 50 mm thick stone slab partition walls, 20 mm thick plaster in CM 1:6 finished with neat floating cement, 4 Nos stone foot rests of approved design ,two No. 450 mm dia each Ferro cement cover with frame, earth work etc. complete as per approved drawing including disposal of surplus earth within a lead of 50 mtr:- Size 400 x140x150 cm.(for 50 users) with 115 mm thick RCC (M-20) slab with Tor steel reinforcement 10mm \$\phi\$ @15 cm c/c bothways	Dig De Da	gitally signa ite: 20	sianed by	Rajond retaly 19:16:04	ra Singh
	B-7.19 B-15.3 G-4.1 S-1.68.4	I: 2: 4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20mm nominal size). P & F 1st quality Vitrified Porcelain Polished tiles on floor, skirting and steps etc.in different sizes (thickness to be specified by manufactuer) with water absortion less than 0.08% and conforming to IS 15622 of approved make in all colour and shade, laid with 20 mm thick CM 1 : 4 including grounting the joints with white cement and matching pigment etc complete. size 600 mm X 600 mm Add extra for Fixing glazed/ Ceramic/ Vitrified floor tiles with cement based high polymer modified quick-set tile adhesive (Water based) conforming to IS: 15477, using Skg. adhesive per sum of tile area, in average 3mm thickness instead of cement mortar. Providing and laying water proofing treatment in sunken portion of WCs, bathroom etc., by applying cement slurry mixed with water proofing cement compound consisting of applying: a) first layer of slurry of cement @ 0.488 kg/sqm mixed with water proffing cement compound @0.253 kg//sqm. This layer will be allowed to air cure for 4 hours.b) Second layer of slurry of cement @ 0.242 kg/sqm mixed with water proffing cement compound @ 0.126 kg/sqm This layer will be allowed to air cure for 4 hours followed by water curing for 48 hours.The rates includes preparation of surface treatment & sealing of all joints ,corners, junction with polymer mixed slurry. Carriage of Building Rubbish Stone metal (Grit and ballast etc.) including loading unloading etc. complete with all lead. I Km. Providing & Fixing Premium Quality white glazed vitreous china Sanitary Wares (IS:2556 Mark) of approved make as per direction of Engineer-in-charge including cutting and making good the wall and floor. Double Syphonic European W.C. with mounted W.V.C. flushing cistern of 10 litre capacity complete with all necessary internal fittings with Hydraulic seat cover. S-3.27.3 Construction of septic Tank in all types of soil with 40 Cm. thick masonry in CM 1:6, fished with neat floating cement, 4 Nos stone foot rests of approved	B-7.18.2 B-7.18.2 B-7.18.2 B-7.18.2 B-7.18.2 B-7.18.2 B-7.18.2 B-7.18.2 B-7.18.3 B-7.18.2 B-7.18.2 B-7.18.2 B-7.18.3 B-7.18.4 B-7.18.5 B-7.18.5 B-7.19 Add extra for Fixing glazed/ Ceramic/Vitrified floor tiles with with ecment based high polymer modified quick-set tile adhesive (Water based) conforming to IS: 15477, using Skg, adhesive per sum of tile area, in average 3mm thickness instead of cement mortar. Providing and laying water proofing treatment in sunken portion of WCs, bathroom etc., by applying cement compound consisting of applying: a) first layer of slurry of cement @ 0.242 kg/sqm mixed with water proffing cement compound @0.253 kg/sqm This layer will be allowed to air cure for 4 hours blowed by water curing for 48 hours. The rates includes preparation of surface treatment & sealing of all joints, corners, junction with polymer mixed slurry. Carriage of Building Rubbish Stone metal (Grit and ballast etc.) including loading unloading etc. complete with all lead. I Km. Providing & Fixing Premium Quality white glazed vitreous china Sanitary Wares (IS:2556 Mark) of approved make as per direction of Engineer-in-charge including cutting and making good the wall and floor. Double Syphonic European W.C. with mounted W.V.C. flushing cistern of 10 litre capaci	1: 2: 4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20mm nominal size). P & F 1st quality Virified Porcelain Polished tiles on floor, skirrling and steps etc.in different sizes (thickness to be specified by manufactuer) with water absortion less than 0.08% and conforming to 1S 15622 of approved make in all colour and shade, laid with 20 mm thick CM 1 : 4 including grounting the joints with white cement and matching pigment etc complete. size 600 mm X 600 mm Add extra for Fixing glazed/ Ceramic/ Vitrified floor tiles with cement based high polymer modified quick-set tile adhesive (Water based) conforming to 1S: 15477 using 5kg. adhesive per sum of tile area, in average 3mm thickness instead of cement mortar. Providing and laying water proofing treatment in sunken portion of WCs, bathroom etc., by applying cement slurry mixed with water proofing cement compound @0.253 kg/sqn This layer of applying : a) first layer of slurry of cement @0.488 kg/sqn mixed with water proffing cement compound @0.253 kg/sqn This layer will be allowed to air cure for 4 hours b) Second layer of slurry of cement @0.242 kg/sqn mixed with water proffing cement compound @0.126 kg/sqn This layer will be allowed to air cure for 4 hours followed by water curing for 48 hours.The rates includes preparation of surface treatment & sealing of all joints, corners, junction with polymer mixed slurry. G-4.1 (Grit and ballast etc.) including loading unloading etc. complete with all lead. 1 Km. Providing & Fixing Premium Quality white glazed vitreous china Sanitary Wares (IS:2556 Mark) of approved make as per direction of Engineer-in-charge including cutting and making good the wall and floor. Double Syphonic European W.C. with mounted W.V.C. flushing cistern of 10 litre capacity complete with all necessary internal fittings with Hydraulic seat cover. S-3.27.3 Construction of septic Tank in all types of soil with 40 Cm .thick masonry in CM 1.6, 15 Cm thick C.C bed of 1:5:10, M-15 grade C.C floor & RCC slab covering with Mil Mil 5 grade c	i: 2: 4 (1 cement: 2 coarse sand: 4 graded stone aggregate 20mm nominal size). P & F 1st quality Vitrified Porcelain Polished tiles on floor, skirting and steps etc.in different sizes (thickness to be specified by manufactuer) with water absortion less than 0.08% and conforming to 18 15622 of approved make in all colour and shade, laid with 20 mm thick CM 1: 4 including grounting the joints with white cement and matching pigment etc complete, size 600 mm X 600 mm Add extra for Fixing glazed/ Ceramic/ Vitrified floor tiles with cement based high polymer modified quick-set tile adhesive (Water based) conforming to 18: 15477, using 5kg, adhesive per sum of tile area, in average 3mm thickness instead of cement mortar. Providing and laying water proofing treatment in sunken portion of WCs, bathroom etc., by applying cement surry mixed with water proofing cement compound @0.235 kg/sqm. This layer will be allowed to air cure for 4 hours.bl) Second layer of slurry of cement @0.242 kg/sqm mixed with water proffing cement compound @0.126 kg/sqm This layer will be allowed to air cure for 4 hours followed by water curing for 48 hours. The rates includes preparation of surface treatment & sealing of all joints .comers, junction with polymer mixed slurry. Carriage of Building Rubbish Stone metal (Grit and ballast etc.) including loading to unloading etc. complete with all lead. 1 Km. Providing & Fixing Premium Quality white glazed vitreous china Sanitary Wares (18:2556 Mark) of approved make as per direction of Engineer-in-charge including cutting and making good the wall and floor. Double Syphonic European W.C. with mounted W.V.C. flushing eistem of 10 lifte capacity complete with all lead. 1 Km. Providing & Fixing Premium Quality white glazed vitreous china Sanitary Wares (18:2556 Mark) of approved make as per direction of Engineer-in-charge including cittem of 10 lifte capacity complete with all necessary internal fittings with Hydraulic seat cover. S-3.27.3. Construction of septic Tank in all types of soil with 40	1: 2: 4 (1 cement: 2 coarse sand: 4 graded stone aggregate 20mm nominal size). P. & F 1st quality Vitrified Porcelain Polished tiles on floor, skirting and steps etc. In different sizes (thickness to be specified by manufactuer) with water absortion less than 0.08% and conforming to IS 15622 of approved make in all colour and shade, laid with 20 mm thick CM 1: 4 including grounting the joints with white cement and matching pigment etc complete, size 600 mm Add extra for Fixing glazed/ Ceramic/Vitrified floor tiles with cement based high polymer modified quick-set tile adhesive (Water based) conforming to IS: 15477, using 5kg, adhesive per sum of tile area, in averagamt bickness instead of cement mortar. Providing and laying water proofing treatment in sunken portion of WCs, bathroom etc., by applying: a) first layer of slurry of cement @ 0.488 kg/sqm mixed with water profling cement compound @ 0.158/sq/sqm. This layer will be allowed to air cure for 4 hours. b) Second layer of slurry of cement @ 0.424 kg/sqm mixed with water profling cement compound @ 0.126 kg/sqm This layer will be allowed to air cure for 4 hours. b) water curing for 48 hours. The rates includes preparation of surface treatment & sealing of all joints , corners, junction with polymer mixed slury. G-4.1 Carriage of Building Rubbish Stone metal (Grit and ballast etc.) including loading unloading etc. complete with all necessary internal fittings with Hydraulic seat cover. S-3,27.3 Construction of septic Tank in all types of soil unloading etc. Construction of septic Tank in all types of soil with near floating counting and making good the wall and floor. Double Syphonic European W.C. with mounted W.V.C. flushing cistern of 10 litre eapacity complete with all necessary internal fittings with Hydraulic seat cover. S-3,27.3 Construction of septic Tank in all types of soil with near floating cement, 4 Nos stone foot rests of approved design , two No. 450 mm dia each Ferro cement cover with frame, earth work etc. complete as p

		including shuttering complete in all respect.					
114	S-2.1.8	P & F G.I. pipes (Internal Work) with G.I. Fittings excluding union (IS:1239 Mark) & MS clamps including cutting and making good the walls and floors:80mm dia nominal bore 'B' Class	1.00	Mtr.	963.00	Mtr.	963.00
115	S-2.37	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes (IS 15778 : 2007 code) having thermal stability for hot & cold water supply including all CPVC plain & brass threaded fittings i/c fixing the pipe with clamps at 1 metre spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge. (Internal work Exposed on wall)					
a	2.37.1	15 mm nominal size	1.00	Rm	191.00	Rm	191.00
b	2.37.2	20mm nominal size	1.00	Rm	222.00	Rm	222.00
c	2.37.3	25 mm nominal size	1.00	Rm	282.00	Rm	282.00
d	2.37.4	32mm nominal size	1.00	Rm	369.00	Rm	369.00
e	2.37.5	40 mm nominal size	1.00	Rm	519.00	Rm	519.00
f	2.37.6	50 mm nominal size	1.00	Rm	802.00	Rm	802.00

Signature valid Digitally signed by Raigndra Singh Designation, Secretary Date: 2025.08.29 13:16:04 IST Reason: Approved