



राजस्थान राज्य क्रीडा परिषद

सवाई मानसिंह स्टेडियम, जनपथ, जयपुर

कार्यालय दूरभाष नं० 0141-2744283. फ़ैक्स नं० 0141-2740568. ईमेल आईडी-rsscjaipur@gmail.com

No. : F.8/T.C./Khelo India/2026/Alwar/Raj-Kaj

Date : (E-Signed)

निविदा सूचना संख्या 23 / 2026-27

राजस्थान राज्य क्रीडा परिषद, जयपुर की ओर से भारत सरकार की खेलों इंडिया योजनान्तर्गत पीएम श्री नवीन सीनियर सैकेण्डरी स्कूल, अलवर में सिन्थेटिक हॉकी टर्फ मैदान निर्माण कार्य हेतु राज्य/केन्द्र सरकार के संगठनों/विभागों में पंजीकृत संवेदकों से ई-प्रोक्यूरमेंट प्रक्रिया हेतु ऑनलाइन निविदा आमंत्रित की जाती है।

निविदा से संबंधित अन्य आवश्यक विवरण वेबसाइट <http://sppp.rajasthan.gov.in>, <http://eproc.rajasthan.gov.in> व www.rssc.in पर देखी जा सकती है।

सचिव

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897



M e-Sign



RAJASTHAN STATE SPORTS COUNCIL

TENDER DOCUMENT

FOR

Construction of Synthetic Hockey Turf Ground at PM Shree Naveen Senior Secondary School, Alwar, Rajasthan.

NIT NO.	:	NIT No. 23/2026-27
ESTIMATED COST	:	Rs. 765.00 Lacs
EARNEST MONEY	:	Rs. 15,30,000/-
DATE OF SALE / DOWNLOADING	:	From Thursday June 25, 2026 to Wednesday July 15, 2026 11:00 Hours
DATE OF RECEIPT (D.D. & DOCUMENTS)	:	From Thursday June 25, 2026 to Wednesday July 15, 2026 13:00 Hours
PRE-BID MEETING	:	Wednesday July 01, 2026 11:00 Hours
DATE OF OPENING OF TENDER	:	Thursday July 16, 2026 12:00 Hours
		(Before participating in the pre-bid, the contractor must deposit the tender fee. Only after depositing the tender cost (Not refunded) will the contractor be allowed to participate in the pre-bid)
COMPLETION PERIOD	:	8 Months
COST OF TENDER	:	Rs. 5000/- in favour of Secretary, RSSC, Jaipur
PROCESSING FEES	:	Rs 2500/- in favour of MD, RISL, Jaipur
DLP Period	:	5 Years

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

Rajasthan State Sports Council. Jaipur

Important Dates of Bids

1. Completion Period	8 Months
2. Date of Issue of Notice Inviting Tender	Thursday June 25, 2026
3. Period and Places of Sale/ Download of Bidding Documents -	From Thursday June 25, 2026 to Wednesday July 15, 2026 11:00 Hours http://sppp.rajasthan.gov.in, www.rssc.in & http://eproc.rajasthan.gov.in
4. Deadline for uploading	From Thursday June 25, 2026 to Wednesday July 15, 2026 11:00 Hours
5. Time and Date for Opening of Bids	Thursday July 16, 2026 12:00 Hours
6. Place of Opening of Bids	Rajasthan State Sports Council, SMS Stadium, Jaipur-302005
7. Officer Inviting Bids	Secretary, Rajasthan State Sports Council. Jaipur. Address: SMS Stadium, Jaipur-302005
8. Earnest money to be deposited	As per NIT

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

Instructions and information to bidder regarding Fee, EMD etc.

District	Name of Work Package No.	Estimated Cost (Rs.)	Earnest Money	Time Allowed for completion	End date and time for downloading Tender	Time and date of opening of tender	Place of Sale of documents	Class of contractor.
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)
Jaipur	Construction of Synthetic Hockey Turf Ground at PM Shree Naveen Senior Secondary School, Alwar, Rajasthan.	765.00 Lacs	Rs. 15,30,000/-	8 Months	Wednesday July 15, 2026 11:00 Hours	Thursday July 16, 2026 12:00 Hours	http://spppp.rajasthan.gov.in , http://eproc.rajasthan.gov.in & www.rssc.in	State/Central के अधिकृत संगठनों के विभागों में पंजीकृत संवेदक or Eligible Sports Infrastructure Companies

1. The Tender Fee and earnest money as mentioned above should be deposited in the appropriate form as per the tender documents in favour of **Secretary, Rajasthan State Sports Council, Jaipur** payable at **Jaipur** and **Processing Fees** payable at **MD, RISL, Jaipur** payable at Jaipur and must be uploaded scan copy of Registration of Firm, Demand Draft of Tender Cost, Processing Fee & Earnest Money on the site.
2. The tender can be viewed and downloaded from web site <http://spppp.rajasthan.gov.in>, <http://eproc.rajasthan.gov.in> & www.rssc.in.
3. The authorized tender documents are available for inspection in the office of **Rajasthan State Sports Council, SMS Stadium, Jaipur** from all working days.

Signature valid

Digitally signed by Rajesh Meena
Designation: Secretary
Date: 2026.06.25/12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

Annexure A: Compliance with the Code of Integrity and No Conflict of Interest

Any person participating in a procurement process shall-

- (a) Not offer any bribe, reward or gift or any material benefit either directly or indirectly in exchange for an unfair advantage in procurement process or to otherwise influence the procurement process;
- (b) Not misrepresent or omit that misleads or attempts to mislead so as to obtain a financial or other benefit or avoid an obligation;
- (c) Not indulge in any collusion, Bid rigging or anticompetitive behavior to impair the transparency, fairness and progress of the procurement process;
- (d) Not misuse any information shared between the procuring entity and the bidders with an intent to gain unfair advantage in the procurement process;
- (e) Not indulge in any coercion including impairing or harming or threatening to do the same, directly or indirectly, to any party or to its property to influence the procurement process;
- (f) Not obstruct any investigation or audit of a procurement process;
- (g) Disclose conflict of interest, if any; and
- (h) Disclose any previous transgressions with any entity in India or any other country during the last three years or any debarment by any other procuring entity.

Conflict of interest

The Bidder participating in a bidding process must not have a Conflict of Interest.

A Conflict of interest is considered to be a situation in which a party has interests that could improperly influence that party's performance of official duties or responsibilities, contractual obligations, or compliance with applicable laws and regulations.

(i) A bidder may be considered to be in conflict of interest with one or more parties in the bidding process if, including but not limited to:

- (a) Have controlling partners/shareholders in common; or
- (b) Receive or have received any direct or indirect subsidy from any of them; or
- (c) Have the same legal representative for purposes of the bid; or
- (d) have a relationship with each other, directly or through common third parties, that puts them in a position to have access to information about or influence on the bid of another bidder, or influence the decisions of the procuring Entity regarding the bidding process; or
- (e) The bidder participates in more than one bid in a bidding process. Participation by a bidder in more than one bid will result in the disqualification of all bids in which the bidder is involved. However, this does not limit the inclusion of the same subcontractor, not otherwise participating as a bidder, in more than one bid; or
- (f) the bidder or any of its affiliates participated as a consultant in the preparation of the design or technical specifications of the goods, Works or services that are the subject of the Bid; or
- (g) Bidder or any of its affiliates has been hired (or proposed to be hired) by the procuring entity as engineer-in-charge/consultant for the contract.

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

Annexure B: Declaration by the Bidder regarding Qualifications

Declaration by the Bidder

In relation to my/our Bid submitted tofor procurement ofin response to their Notice inviting Bids No.....Dated.....I/wehereby declare under Section 7 of Rajasthan Transparency in Public Procurement Act, 2012 that :

1. I/we possess the necessary professional, technical, financial and managerial resources and competence required by the Bidding Document issued by the Procuring Entry;
2. I/we have fulfilled my/our obligation to pay such of the taxes payable to the union and the state government or any local authority as specified in the Bidding Document.
3. I/we are not insolvent, in receivership, bankrupt or being wound up, not have my/our affairs administered by a court or a judicial officer, not have my/our business activities suspended and not the subject of legal proceedings for any of the foregoing reasons;
4. I/we do not have, and our directors and officers not have, been convicted of any criminal offence related to my/our professional conduct or the making of false statements or misrepresentations as to my/our qualifications to enter into a procurement contract within a period of three years preceding the commencement of this procurement process, or not have been otherwise disqualified pursuant to debarment proceedings;
5. I/we do not have a conflict of interest as specified in the Act, Rules and the Bidding Document, which materially affects fair competition;

Date:
Place:

Signature of bidder
Name:
Designation:
Address:

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.06.25/12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

Annexure C: Grievance Redressed during Procurement Process

The designation and address of the First Appellate Authority is **Joint Secretary**, Youth Affairs & Sports Department Govt. of Rajasthan. The designation and address of the Second Appellate Authority is **Secretary**, Youth Affairs & Sports Department Govt. of Rajasthan, Jaipur.

(1) Filing an appeal:-

if any bidder or prospective bidder is aggrieved that any decision, action or omission of the procuring entity is in contravention to the provisions of the Act or the rules or the guidelines issued there under, he may file an appeal to First Appellate authority, as specified in the Bidding document within a period of ten days from the date of such decision or action, omission, as the case may be, clearly giving the specific ground or grounds on which he feels aggrieved:

Provided that after the declaration of a bidder as successful the appeal may be filed only by a bidder who has participated in procurement proceedings:

Provided further that in case a procuring entity evaluates the technical bids before the opening of the financial bids, an appeal related to the matter of financial bids may be filed only by a bidder whose technical bid is found to be acceptable.

(2) The officer to whom an appeal is filed under Para (1) shall deal with the appeal as expeditiously as possible and shall endeavor to dispose it of within thirty days from the date of the appeal.

(3) If the officer designated under Para (1) fails to dispose of the appeal filed within the period specified in Para (2), or if the bidder or prospective bidder or the procuring entity is aggrieved by the order passed by the first appellate authority, the bidder or prospective bidder or the procuring entity, as the case may be, may file a second appeal to second appellate authority specified in the bidding document in this behalf within fifteen days from the expiry of the period specified in Para (2) or of the date of receipt of the order passed by the first appellate authority, as the case may be.

(4) Appeals not to lie in certain cases:-

No appeal shall lie against any decision of the procuring entity relating to the following matters, namely:-

- (a) Determination of need of procurement
- (b) Provisions limiting participation of bidders in the bid process
- (c) The decision of whether or not to enter into negotiations
- (d) Cancellation of a procurement process
- (e) Applicability of the provisions of confidentiality

(5) Form of Appeals:-

- (a) An appeal under Para (1) or (3) above shall be in the annexed form along with as many copies as there are respondents in the appeal.
- (b) Every appeal shall be accompanied by an order appealed against, if any, Affidavit verifying the facts stated in the appeal and proof of payment of fee,
- (c) Every appeal may be presented to first appellate authority or second Appellate authority, as the case may be, in person or through registered post Or authorized representative.

(6) Fee for filing Appeal:-

- (a) Fee for first appeal shall be rupees two thousand five hundred and for second appeal shall be rupees ten thousand, which shall be non-refundable.
- (b) The fee shall be paid in the form of bank demand draft or banker's cheque of a scheduled bank in India payable in the name of appellate authority concerned.

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

(7) Procedure for disposal of Appeal:-

- (a) The first appellate authority or second appellate authority as the case may be, upon filing of appeal, shall issue notice accompanied by copy of appeal, affidavit and documents, if any, to the respondents and fix date of hearing
- (b) On the date fixed for hearing, the first appellate authority or second appellate authority, as the case may be shall-
 - (i) Hear all the parties to appeal present before him; and
 - (ii) Peruse or inspect documents, relevant records or copies thereof relating to the matter.
- (c) After hearing the parties, perusal or inspection of documents and relevant records or copies thereof relating to the matter, the appellate authority concerned shall pass an order in writing and provide the copy of order to the parties to appeal free of cost.
- (d) The order passed under sub-clause (c) above shall also be placed on the state public procurement portal.

Signature valid

Digitally signed by Rajesh Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

Annexure D: Additional Conditions of Contract

1. Correction of arithmetical errors

Provided that a Financial Bid is substantially responsive, the Procuring Entity will correct arithmetical errors during evaluation of Financial Bids on the following basis:

- i. If there is a discrepancy between the unit price and the total price that is obtained by multiplying the unit price and quantity, the unit price shall prevail and the total price shall be corrected, unless in the opinion of the Procuring Entity there is an obvious misplacement of the decimal point in the unit price, in which case the total price as quoted shall govern and the unit price shall be corrected;
- ii. If there is an error in a total corresponding to the addition or subtraction of subtotals, the subtotals shall prevail and the total shall be corrected; and
- iii. If there is a discrepancy between words and figures, the amount in words shall prevail, unless the amount expressed in words is related to an arithmetic error, in which case the amount in figures shall prevail subject to (i) and (ii) above.

If the Bidder that submitted the lowest evaluated Bid does not accept the correction of errors, its Bid shall be disqualified and its Bid Security shall be forfeited or its Bid Securing Declaration shall be executed.

2. Procuring Entity's Right to Vary Quantities

- (i) At the time of award of contract, the quantity of Goods, Works or services originally specified in the Bidding Document may be increased or decreased by a specified percentage, but such increase or decrease shall not exceed Five percent, of the quantity specified in the Bidding Document. It shall be without any change in the unit prices or other terms and conditions of the Bid and the conditions of contract.
- (ii) If the Procuring Entity does not procure any subject matter of procurement or procures less than the quantity specified in the Bidding Document due to change in circumstances, the Bidder shall not be entitled for any claim or compensation except otherwise provided in the Conditions of Contract.
- (iii) In case of procurement of Goods or services, additional quantity may be procured by placing a repeat order on the rates and conditions of the original order. However, the additional quantity shall not be more than 50% of the value of Goods of the original contract and shall be within one month from the date of expiry of last supply. If the supplier fails to do so, the Procuring Entity shall be free to arrange for the balance supply by limited Bidding or otherwise and the extra cost incurred shall be recovered from the supplier.

3. Dividing quantities among more than one Bidder at the time of award (In case of procurement of Goods)

As a general rule all the quantities of the subject matter of procurement shall be procured from the Bidder, whose Bid is accepted. However, when it is considered that the quantity of the subject matter of procurement to be procured is very large and it may not be in the capacity of the Bidder, whose Bid is accepted, to deliver the entire quantity or when it is considered that the subject matter of procurement to be procured is of critical and vital nature, in such cases, the quantity may be divided between the Bidder, whose Bid is accepted and the second lowest Bidder or even more Bidders in that order, in a fair, transparent and equitable manner at the rates of the Bidder, whose Bid is accepted.

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

राजस्थान राज्य क्रीडा परिषद

सवाई मानसिंह स्टेडियम, जनपथ, जयपुर

कार्यालय दूरभाष नं० 0141-2744283, फ़ैक्स नं० 0141-2740568, ईमेल आईडी—rsscjaipur@gmail.com

बोली की शर्तें

विशेष टिप्पणी :- बोलीदाताओं को इन शर्तों को सावधानी पूर्वक पढ़ना चाहिए तथा अपनी ई-बोलियां भेजते समय इनकी पूर्ण रूपेण पालना करनी चाहिए।

1. तकनीकी प्रस्तावों में सफल बोलीदाताओं के ही वित्तीय प्रस्ताव खोले जावेंगे जो निविदादाता तकनीकी बिड में सफल नहीं पाये गये उनकी वित्तीय बोली नहीं खोली जायेगी।
2. कोई भी फर्म/संवेदक यदि जी.एस.टी. अधिनियम के अन्तर्गत पंजीकृत नहीं है तो वह बोली नहीं देगा। इनके अभाव में बोलियों पर विचार नहीं किया जायेगा। जी. एस. टी. देयता प्रमाण पत्र मार्च, 2026 का संलग्न करना आवश्यक है।
3. दरें जी.एस.टी. तथा केन्द्र व राज्य सरकार द्वारा देय समस्त करों सहित देनी होगी।
4. बोली ऑन-लाईन प्रस्तुत की जावेगी एवं निर्दिष्ट कॉलमों में प्रविष्टी की जावेगी।
5. दरें गन्तव्य स्थान तक एफ.ओ.आर. सवाई मानसिंह स्टेडियम जयपुर के आधार पर होगीं अर्थात् परिवहन संबंधी कोई राशि परिषद द्वारा पृथक से देय नहीं होगी।
6. बोलियां उपापन अधिनियम/पारदर्शिता अधिनियम के तत्संबंधी प्रावधानों (धारा-28 आदि) के अध्यक्षीन रहते हुये उनके खोले जाने की दिनांक से एक वर्ष की अवधि के लिए विधि मान्य होंगी।
7. बोलीदाता अपनी संविदा या उसके किसी भाग को किसी अन्य एजेन्सी के लिए नहीं सौंपेगा या उपभाडे पर नहीं देगा।
8. बोलीदाता का उसके प्रतिनिधि की ओर से प्रत्यक्ष अथवा अप्रत्यक्ष रूप से अपना पक्ष समर्थन करना एक प्रकार की अनर्हता होगी। हित विरोधी धारा 80 होगी।
9. विहित समय एवं तारीख के पश्चात् जो भी बोलियां प्राप्त होंगी उन्हें किसी स्थिति में स्वीकार नहीं किया जावेगा।
10. यदि बोलीदाता ऐसी कोई शर्त आरोपित करता है जो उसमें वर्णित शर्तों के अतिरिक्त है या उनके विरोध में है तो उसकी बोली को संक्षिप्त रूप में कार्यवाही कर रद्द कर दिया जावेगा।
11. तकनीकी बोली के साथ बोलीदाता को निम्न दस्तावेज संलग्न करने अनिवार्य होंगे (जिसके आधार पर तकनीकी बिड का मूल्यांकन किया जायेगा) :-
 - i. बोली में अंकित पते के प्रमाण हेतु पानी/बिजली/टेलीफोन/मोबाईल के बिल, पेन कार्ड, पासपोर्ट, आधार कार्ड अथवा ड्राईविंग लाईसेन्स में से कोई एक की प्रमाणित छाया प्रतियां।
 - i. बोलीदाता/फर्म का विगत 5 वित्तीय वर्षों (2021-22, 2022-23, 2023-24, 2024-25 एवं 2025-26) में औसत वार्षिक टर्न ओवर 765.00 लाख से कम नहीं होना चाहिये। इस हेतु बोलीदाता को उक्त वर्षों का सीए से प्रमाणित प्रमाण पत्र की प्रति मय यूडीआई नम्बर सहित संलग्न करनी होगी।

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

- ii. गत 5 वर्षों (2021-22, 2022-23, 2023-24, 2024-25 एवं 2025-26) में कम से कम दो नवीन FIH Certified Global Category Synthetic Hockey Ground के निर्माण कार्य का अनुभव होना आवश्यक है, इसके प्रमाणीकरण हेतु कार्यादेश एवं कार्य के सन्तोषजनक होने का प्रमाण पत्र आदि आवश्यक दस्तावेज संलग्न करने होंगे।
- iii. बोलीदाता को माल एवं सेवाकर (GST) के रजिस्ट्रेशन की प्रति संलग्न करनी होगी।
- iv. अमानत राशि एवं बोली प्रपत्र शुल्क का डी.डी. संलग्न करना होगा।

12. **बयाना राशि :-**

- (क) बोली से पूर्व (2%) नियमानुसार बयाना राशि ऑफ-लाईन प्रस्तुत की जायेगी। इसके बिना बोलीओं पर विचार नहीं किया जायेगा। यह राशि सचिव, राजस्थान राज्य क्रीड़ा परिषद, जयपुर के पक्ष में बैंक ड्राफ्ट/बैंकर्स चैक में से किसी रूप में जमा करायी जा सकती है।
- (ख) असफल बोलीदाता की बयाना राशि बोली को अंतिम रूप से स्वीकार करने के बाद यथा संभव शीघ्र लौटा दी जावेगी।
- (ग) अनुमोदन की प्रतीक्षा करने वाली या रद्द की गई या संविदाओं के पूर्ण हो जाने के कारण परिषद कार्यालय के पास जमा बयानाराशि/प्रतिभूति निक्षेप को नवीन निविदा के लिए बायाना राशि/प्रतिभूति राशि के प्रति समायोजित नहीं किया जायेगा।

13. **बयाना राशि का समपहरण:-** बयाना राशि को निम्नलिखित मामलों में समपहरत कर लिया जायेगा:-

- (क) जब बोलीदाता बोली खोलने के बाद किन्तु बोली को स्वीकार करने के पूर्व प्रस्ताव को वापस लेता है या उसमें उपान्तरण करता है।
- (ख) जब बोलीदाता विनिश्चित समय के भीतर विहित करार को निष्पादित नहीं करता है।
- (ग) जब बोलीदाता प्रदायगी के लिए आदेश देने के बाद प्रतिभूति राशि जमा नहीं कराता हो।
- (घ) जब वह निर्धारित समय के अन्तर्गत आदेशों के अनुसार कार्य करने में असफल रहता है अथवा संतोषजनक सेवाएं देने में असमर्थ रहता है।

14. **करार एवं प्रतिभूति निक्षेप :-**

- (क) सफल बोलीदाता को आदेश दिनांक से 7 दिन की अवधि के भीतर नियमानुसार मूल्य के नॉन ज्यूडिशियन स्टॉम्प पेपर पर (जिसका व्यय स्वयं बोलीदाता द्वारा वहन किया जावेगा) एक करार-पत्र निष्पादित करना होगा तथा प्रावधित मूल्य जिसके लिए बोली स्वीकार की गई है।
- (ख) बोली के समय जमा कराई गई बयाना राशि को प्रतिभूति की राशि के लिए समायोजित किया जायेगा।
- (ग) बयाना/प्रतिभूति राशि पर परिषद द्वारा कोई ब्याज का भुगतान नहीं किया जायेगा।
- (घ) प्रतिभूति राशि के रूप में नकद रसीद पत्र/शिड्यूल बैंक का ड्राफ्ट/बैंकर्स चैक मान्य होंगे।

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

15. **प्रतिभूति राशि का समपहरण** :- प्रतिभूति की राशि को पूर्ण अथवा आंशिक रूप से निम्नलिखित मामलों में समपहरत किया जायेगा:-
- (क) जब संविदा की किसी शर्त/अथवा शर्तों का उल्लंघन किया गया हो।
- (ख) जब बोलीदाता सम्पूर्ण कार्य संतोषजनक ढंग से करने में असफल रहा हो।
- (ग) प्रतिभूति निक्षेप को समपहरत करने के मामले में युक्तियुक्त नोटिस दिया जावेगा इस सम्बन्ध में परिषद के अधिकारी का निर्णय अन्तिम होगा।
- (घ) कार्य में असफल रहने पर परिषद द्वारा वैकल्पिक व्यवस्था किये जाने पर उसमें जो भी व्यय होगा बोलीदाता से उसकी प्रतिभूति राशि में से अथवा उसको देय बिल की राशि के भुगतान में से की जायेगी। यदि वसूली करना सम्भव न हो तो राजस्थान पी.डी.आर.एक्ट या प्रवृत्त अन्य किसी कानून के अन्तर्गत कार्यवाही की जावेगी।
16. करार पत्र को पूर्ण करने एवं उस पर स्टाम्प लगाने का व्यय बोलीदाता द्वारा वहन किया जायेगा तथा परिषद को उस करार पत्र की निष्पादित स्टाम्प शुदा प्रति पडत निःशुल्क प्रस्तुत की जायेगी।
17. परिषद के प्राधिकृत अधिकारी या उसका विधिवत् प्राधिकृत प्रतिनिधि सभी युक्तियुक्त उचित समयों पर ठेकेदार के परिसर में जायेगा तथा वह विनिर्माण की प्रक्रिया के दौरान या उसके बाद जैसे भी हो किसी भी समय सामग्री का निरीक्षण एवं जांच करने की शक्ति रखेगा।
18. परीक्षण प्रभार परिषद द्वारा वहन किये जायेंगे। यदि बोलीदाता अत्यावश्यक तत्काल परीक्षण कराना चाहता है या यदि परिणामों से यह ज्ञात होता है कि प्रदाय किया गया सामान विहित स्तरों या विनिर्देशों के अनुसार नहीं है तो परीक्षण प्रभार बोलीदाता द्वारा वहन किये जायेंगे।
19. अनुमोदित कार्य के लिए यह समझा जाएगा कि उसने कार्य किये जाने वाले विनिर्देशों की सावधानीपूर्वक जांच कर ली है यदि उसे इन शर्तों, विनिर्देशों, रेखाचित्रों आदि के किसी भाग के आशय के बारे में कोई सन्देह हो तो वह संविदा पर हस्ताक्षर करने से पूर्व परिषद से स्पष्टीकरण प्राप्त करेगा।
20. सफल बोलीदाता को कार्य आदेश जारी तिथि के 10 दिवस के अन्दर कार्य प्रारम्भ करना होगा।
21. यदि निविदा सूचना में दर्शित मात्रा से अधिक के लिए आदेश दिया जाता है, तो निविदादाता अपेक्षित कार्य करने के लिए बाध्य होगा। पुनः आदेश भी निविदा में दी गयी शर्तों पर दिए जा सकेंगे परन्तु शर्त यह है, कि ऐसे पुनःआदेश मूल रूप से खरीदी गयी मात्रा की 50 प्रतिशत तक के अतिरिक्त प्रदाय के लिए ही होंगे।
22. **गारन्टी** :-गारन्टी नियमानुसार होगी।
23. **परिसमापित नुकसानी** :-
- (1) परिसमापित नुकसानी के साथ कार्य अवधि में वृद्धि करने के मामले में, वसूली राजस्थान लोक उपापन पारदर्शिता अधिनियम, 2012 एवं राजस्थान लोक उपापन पारदर्शिता नियम 2013 के प्रावधान अनुसार होगी।
- (2) यदि प्रदायकर्ता किन्ही बाधाओं के कारण संविदान्तर्गत कार्य का प्रदाय पूरा करने के लिए समय में वृद्धि कराना चाहता है, तो वह लिखित में परिषद को आवेदन करेगा। किन्तु वह उसके लिए निवेदन बाधा के घटित होने पर तुरन्त उसी समय करेगा न कि प्रदाय पूर्ण होने की निर्धारित तारीख के बाद करेगा।

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

- (3) यदि कार्य प्रदाय करने में उत्पन्न हुई बाधा बोलीदाता के नियन्त्रण से परे कारणों से हुई हो तो कार्य की अवधि में वृद्धि परिसमापित नुकसानी सहित या रहित की जा सकेगी।
24. **वसूली** :-परिसमापित नुकसानी, कम प्रदाय, टूट-फूट, रद्द की गई वस्तुओं के लिए वसूली साधारण रूप से बिल में से की जाएगी। संवेदक कम प्रदाय, टूट-फूट, रद्द किए गए कार्यों की सीमा तक राशि को भी रोका जा सकेगा तथा यदि सेवा सन्तोषजनक ढंग से उनको कार्य करता है तो परिसमापित नुकसानी के साथ वसूली उसे देय राशि एवं विभाग के पास उपलब्ध प्रतिभूति निक्षेप से की जाएगी। यदि वसूली करना सम्भव न हो तो राजस्थान पी डी आर एक्ट या प्रवृत्त अन्य कानून के अन्तर्गत कार्रवाई की जाएगी।
- 25. भुगतान :-**
- (क) बोलीदाता द्वारा क्रेता अधिकारी को उचित प्रारूप में लोक उपापन नियमों के अनुसार बिल प्रस्तुत करने पर भुगतान किया जायेगा। सभी प्रेषण प्रभार बोलीदाता द्वारा वहन किये जायेंगे। किसी भी सूरत में अग्रिम भुगतान नहीं किया जायेगा।
- (ख) विवादास्पद मदों में राशि का 10 प्रतिशत से 25 प्रतिशत तक को रोका जायेगा तथा उस विवाद का निपटारा हो जाने पर उसका भुगतान कर दिया जायेगा।
- (ग) उन मामलों में, जिनमें परीक्षण करने की जरूरत है, भुगतान तभी किया जायेगा जब उनका परीक्षण कर लिया जाये तथा प्राप्त हुए परीक्षण परिणाम विहित निर्देशों के अनुरूप हों।
26. यदि कार्य की तात्कालिक आवश्यकता के कारण पूर्ण या आंशिक रूप में उन कार्यों को बदलना साध्य नहीं समझा जाए तो राजस्थान राज्य क्रीडा परिषद द्वारा बोलीदाता को सुनवाई किये जाने का एक उचित अवसर देकर, ऐसे कारणों से जो अभिलिखित किये जायेंगे, अनुमोदित दरों में से उपयुक्त राशि की कटौती करेगा। इस प्रकार की गई कटौती अन्तिम होगी।
27. निविदादाता करार को निष्पादित करते समय निम्नलिखित दस्तावेज प्रस्तुत करेगा :-
- (i) यदि भागीदारी फर्म हो तो "पार्टनरशिप डीड" की अनुप्रमाणित प्रति।
- (ii) यदि भागीदारी फर्म रजिस्ट्रार ऑन फर्म्स के पास पंजीकृत हो तो पंजीयन संख्या एवं उसका वर्ष।
- (iii) एक मात्र स्वामित्व के मामले में आवास एवं कार्यालय का पता, टेलीफोन नम्बर।
- (iv) कम्पनी के मामले में कम्पनी के रजिस्ट्रार के द्वारा जारी किया गया प्रमाण-पत्र।
28. संविदा के निर्वचन, आशय या संविदा की शर्तों के उल्लंघन के सम्बन्ध में या अन्य किसी भी प्रकार का विवाद होने पर परिषद का निर्णय अन्तिम होगा।
29. समस्त विधिक कार्यवाहियां यदि संस्थित किया जाना आवश्यक हो तो जयपुर स्थित न्यायालय में ही की जाएगी। अन्यत्र नहीं की जाएगी।
30. बोलीदाता द्वारा अपलोड किये जाने वाले दस्तावेजों पर नम्बरिंग होनी चाही एवं चैक लिस्ट भर कर प्रस्तुत करनी होगी।

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

31. सचिव, राजस्थान राज्य क्रीडा परिषद, जयपुर को बिना कारण बताये किसी भी बोली को स्वीकार/अस्वीकार करने का अधिकार होगा।
32. जी.एफ. एण्ड ए.आर., राजस्थान लोक उपापन पारदर्शिता अधिनियम, 2012 एवं राजस्थान लोक उपापन पारदर्शिता नियम 2013 के प्रावधान लागू होंगे।
33. **Special Conditions of Contract:**
 1. The bidder should be an FIH Certified field bidder and the field bidder Certificate to be attached along with the bid.
 2. Manufacturer has to be FIH preferred supplier and evidence of same to be submitted along with the bid.
 3. The offered product should be of European, Australian, American Origin only. Manufacturer's declaration should be submitted with technical bid.
 4. Joint ventures and consortium are not accepted.
 5. Custom Duty Exemption Certificate to be issued by the department as per notification of Govt. of India.
 6. The Manufacturer should be an OEM for the bidder for the product being proposed. Manufacturer to give an undertaking of exclusivity for the said project to the bidder.
 7. The Product/ Brand should be FIH approved.
 8. The Engineer-in-Charge / Rajasthan State Sports Council shall have the full and exclusive right to require testing of any material, at any stage and prior to final acceptance, in laboratories of their choice, including FIH-approved laboratories. The bidder/contractor shall, at his own cost, make all necessary arrangements for such testing (except those specified elsewhere in the tender documents) and shall bear all expenses towards sampling, testing, packing, transportation, loading, unloading and all incidental charges whatsoever. Any material found not conforming to the prescribed specifications, standards or quality requirements shall be rejected and shall not be accepted for use in the work.
 9. In case any material/work is found substandard the same shall be rejected by the Engineer-in Charge and the same shall be removed from the site of work within 48 hours, failing which the same shall be got removed by the Engineer-in-Charge at the risk & cost of the Contractor without giving any further notice and time.
 10. The Bidder shall ensure quality control measures on different aspects of construction including materials, workmanship and correct construction methodologies to be adopted.
 11. The Malba/Garbage generated at site due to construction activities shall be removed from the site immediately & shall be disposed off by the contractor to the approved dumping site from local bodies shall be a sole responsibility of contractor.
 12. The contractor shall make his own arrangement to get permission with respect to trucks from the Traffic Police.
 13. The Bidder in its name should have an authorisation certificate from the manufacturer of the proposed product to bid for this specific work, without which their bids shall stand disqualified.
 14. The bidder should never ever be blacklisted or debarred by any Central Government department, State Government department, Public Sector undertaking in India.
 15. The contractor must provide vehicle for inspection of project site as an when required by Engineer-In-Charge.

बोलीदाता के हस्ताक्षर
(मय नाम पता एवं मोहर)

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

घोषणा

मैंने/हमने राजस्थान राज्य क्रीडा परिषद, जयपुर की ओर से भारत सरकार की खेलों इंडिया योजनान्तर्गत पीएम श्री नवीन सीनियर सैकेण्डरी स्कूल, अलवर में सिन्थेटिक हॉकी टर्फ मैदान निर्माण कार्य हेतु (मय सामग्री) की बोली के नियम एवं शर्तों को भली-भाँति पढ़ व समझ लिया है। मुझे/हमारी फर्म को किसी भी विभाग द्वारा ब्लेक-लिस्ट नहीं किया गया है। इन शर्तों एवं नियमों के अधीन मैं/हम उक्त निर्माण कार्य करने हेतु सहमत एवं वचनबद्ध हूँ/हैं। यदि मेरे/हमारे द्वारा की किसी बोली की शर्तों, नियमों अथवा आदेशों का उल्लंघन किया जावेगा तो सक्षम अधिकारी द्वारा मेरे/हमारे विरुद्ध बोली के नियम/शर्तों के उल्लंघन की कार्यवाही करने के लिए अधिकृत होगा। इस सम्बन्ध में मुझे/हमें सक्षम/अधिकृत अधिकारी द्वारा लिया गया निर्णय मान्य होगा तथा इसमें मुझे/हमको कोई आपत्ति/हस्तक्षेप नहीं है।

हस्ताक्षर बोलीदाता.....

नाम/पता

टेलीफोन नं.

दिनांक

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

General Instructions for Filling of Bid

The complete bidding document has been published on the website www.rssc.in, <http://sppp.raj.nic.in>, <http://eproc.raj.gov.in>, for the purpose of downloading.

1. Bidders who wish to participate in this bidding process must register on www.rssc.in & <http://sppp.raj.nic.in>,
2. To participate in online bidding process, Bidders must procure a Digital Signature Certificate (Type III) as per Information Technology Act-2000 using which they can digitally sign their electronic bids. Bidders can procure the same from any CCA approved certifying agency, i.e. TCS, safe crypt, Node etc. Bidders who already have a valid Digital Signature Certificate (DSC) need not procure a new DSC.
3. Bidder (authorized signatory) shall submit their offer on-line in electronic formats both for Technical and financial proposal. However, DD for Tender Fees, EMD payable in favor of SECRETARY RAJASTHAN STATE SPORTS COUNCIL, JAIPUR, payable at Jaipur and Processing Fees payable in favor of Managing Director, RAJCOMP Info Services Limited, payable at JAIPUR. **Tender fee, EMD and processing fee DD should be submitted physically at the office of RAJASTHAN STATE SPORTS COUNCIL, JAIPUR, and Scanned copy of same should also be uploaded along with the technical bid.**
4. RAJASTHAN STATE SPORTS COUNCIL, JAIPUR will not be responsible for delay in online submission due to any reason. For this, bidders are requested to upload the complete bid well advance in time so as to avoid Last hours issues like slow speed; choking of web site due to heavy load or any other unforeseen problems.
5. Bidders are also advised to refer "Bidders Manual Kit" available at e-Proc website for further details about the e-tendering process.
6. No contractual obligation, whatsoever shall arise from the bidding process unless and until a formal contract is signed and executed between the tendering authority and the successful Bidder.

SECRETARY

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

UNDERTAKING BY THE BIDDER

This is to certify that I/we before signing this tender have read and fully understood all the terms and conditions contained herein and undertake myself/ourselves to abide by them. I/We have signed all the pages in acceptance of the terms and conditions.

I/We also undertake that I/We will not adopt any malpractices at any stage of bidding/execution.

Signature of the Bidder with Seal

Name:

Designation:

Address:

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

BIDDER'S AUTHORIZATION CERTIFICATE {to be filled by the bidder}

To,
{Tendering Authority},

I/
We.....{Name/Designatio
n} hereby declare/ certify that

..... {Name/ Designation} is hereby authorized to sign relevant documents on behalf of the company/ firm in dealing with Tender with RAJASTHAN STATE SPORTS COUNCIL, JAIPUR.

He/ She is also authorized to attend meetings & submit technical & commercial information/ clarifications as may be required by you in the course of processing the Bid. For the purpose of validation, his/ her verified signatures are as under.

Thanking you,

Name of the Bidder: -
Authorized Signatory: -
Seal of the Organization: -
Date:
Place:

Verified Signature:

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

CHECKLIST OF DOCUMENTS SUBMITTED

S. No.	Documents to be submitted	Submitted	Not Submitted	Page No.
1.	Scanned Copies of tender document fee, EMD and processing fees			
2.	Copy of Registration of firms.			
3.	Copy of GST Registration			
4.	Copy of PAN Card			
5.	Proof of Work order and Satisfactory Completion of work should be as per tender document condition no. 11 (iii) in financial Year 2021-22 to 2025-26.			
6.	Certificate from Chartered Accountant having UDIN for the proof of average annual Turnover that must be equal/more than the cost of work (bid cost) in the last three Financial Years from 2021-22 to 2025-26			
7.	Annexure A to D duly signed in context to RTPP Rules-2013.			
8.	Authorization certificate If the tender is signed other than owners			
9.	Copy of GST paid certificate filed by March, 2026 Financial Year 2025-26 in GSTR-3B Performa			
10.	Tender document and Technical Bid and undertaking all three duly signed			
11.	Any other Document			

Note: -

1. Work means the work executed under Public Sector/Autonomous Bodies/ Development Authority/Municipal Corporation of Central/State Government.
2. For the purpose of evaluating similar work experience, repair, refurbishment, or relaying of existing hockey turf (including only replacement of top surfaces) shall not be considered. Only works involving complete supply and installation of new synthetic hockey turf including base and sub-base construction, will be treated as eligible experience.
3. The contractor should ensure that the Registration should be latest or updated.

Signature of Bidder Seal of Establishment
Full Name of Bidder with address and
date

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

PART-B (FINANCIAL BID)

Bill of Quantities

Name of Work :- Construction of Synthetic Hockey Turf Ground at PM Shree Naveen Senior Secondary School, Alwar, Rajasthan

Schedule "H"

S. No.	Quantity	Particular	Rate	Amount
1	6000.00	Supplying, laying, jointing and fixing of FIH-approved Water Based (Water Dressed) Global Category Synthetic Hockey Turf manufactured by an FIH Preferred Producer and installed by an FIH Certified Field Builder over prepared asphalt/bituminous base complete with approved elastic shockpad system of minimum 15 mm thickness, including all adhesives, joint tapes, seam materials, line markings, testing and commissioning. The turf shall comply with the latest FIH Global Category requirements for ball roll, ball rebound, shock absorption, vertical deformation, rotational resistance and surface drainage. The work shall include permanent inlaid game markings as per current FIH Rules of Hockey, complete in all respects and as directed by the Engineer-in-Charge.	P. Sqm	
2	2.00	Supplying and installation of aluminium Goal Post as per drawing and design including all fitting and net, as per FIH Specifications	Each	
3	1.00	Providing and installation of Gun type Sprinkler system comprising of 2 (Two) Nos. Sprinklers to be provided having radius of throw of 50 M with discharge of 17.0 LPS and operative pressure of 5.0 bar and 04 Nos. to be provided having radius of throw 25 meters with discharge of 2.5 LPS and operating pressure of 3.5 bar. The grid should contain 10 Nos. low pressured sprinkler hydrant of 32 mm and 2 Nos. high pressure sprinklers hydrants of 65mm dia. The Gun type sprinklers are to be located at a distance of 1.50 M off the edge of the Synthetic Hockey Surface. Layout and design of Sprinkler System along with details of products is got approved from RSSC/AGENCY. The System comprising all necessary connecting pipes, fittings, valves and other accessories along with regular Electric installation complete.	Per Job	
4	2.00	Supplying and fixing of Players bench (Dugout) 12 seater as per FIH standard drawing and design including all fittings.	Each	

Signature valid

Digitally signed by Rajkaj Meena
Designation: Secretary
Date: 2026.06.25/12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

Schedule "G"

S. No.	Quantity	Particular	Rate		Amount
1	2.88	Clearing grass and removal of rubbish up to a distance of 30 m outside the periphery of the area as per MoRTH Specification Clause 201.	7906.00	P.Hect	22761.37
2	23730.00	Supply & Stacking good soil of earth at site complete including loading unloading & Transportation etc. Good soil of earth	240.00	P.Cum.	5695200.00
3	23730.00	Construction of embankment with approved material obtained from borrow pits with a lift upto 1.5 m, transporting to site, spreading, grading to required slope and compacting to meet requirement of Tables 300-1 and 300-2 with a lead upto 50 m as per MoRTH Specification Clause 305.3	51.92	P.Cum.	1232061.60
4		Construction of granular sub-base by providing well graded material, spreading in uniform layers with Tractor Mount Grader on prepared surface, mixing by mix in place method with rotavator at OMC, and compacting with smooth wheel roller to achieve the desired density, complete as per MoRTH Specification Clause 401.			
a	990.00	For Grading II Material	516.84	P.Cum.	511671.60
5	990.00	Providing, laying, spreading and compacting graded stone aggregate to wet mix macadam specification including premixing the material with water at OMC in mechanical mixer (Pug Mill), carriage of mixed material by tipper to site, laying in uniform layers in sub-base/base course on a well prepared sub-base and compacting with smooth wheel roller of 80 to 100kN weight to achieve the desired density including lighting, barricading and maintenance of diversion, etc as per Tables 400-12 & 400-13 and MoRTH Specification Clause 406 By Mechanical Means with a lead of 1 Km. Beyond 20th Km	1312.16	P.Cum.	1299038.40
6	5950.00	Providing and applying primer coat with Bitumen emulsion (SS-1) on prepared surface of granular base (Stabilised soil baes/Crusher Run Macadam) using truck mounted sprayer including cleaning of road surface and spraying primer at the rate of 0.90- 1.2 kg/sqm using mechanical means as per MoRTH Specification Clause 502.	42.48	P.Sqm.	252756.00
7	5950.00	Providing and applying tack coat with Bitumen emulsion (RS-1) using emulsion distributor at the rate of 0.20 to 0.30 kg per sqm on the prepared bituminous surface cleaned with Hydraulic broom as per MoRTH Specification Clause 503.	10.33	P.Sqm.	61433.75
8		Providing and laying bituminous macadam with Drum type hot mix plant using crushed aggregates of grading as per Table 500-7 premixed with bituminous binder, transported to site with all leads laid over a previously prepared surface with paver finisher to the required grade, level and alignment and rolled to achieve the desired compaction as per MoRTH Specification Clause 504.			
a	300.00	Bitumen (VG-30)	7198.00	P.Cum.	2159400.00
9		Providing and laying bituminous concrete with 100-120 TPH batch type hot mix plant producing an average output of 75 tonnes per hour using crushed aggregates of specified grading, premixed with bituminous binder minimum @ 5.2 & 5.4 per cent of mix and filler, transporting the hot mix to work site, laying with a hydrostatic paver finisher with sensor control to the required grade, level and alignment, rolling			

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

		with smooth wheeled, vibratory and tandem rollers to achieve the desired compaction as per MoRTH Specifications Clause 507 complete in all respects			
a	180.00	for Grading-I(19 mm nominal size) Bitumen (VG-10)	8388.62	P.Cum.	1509951.60
10	2.00	SITC of Monoblock closed coupled motor pump set with TEFC motor, motor should be IP55-F class and IE2 efficiency for monobloc, with carbon steel /SS-410 shaft, Mechanical seal, Single/Three phase Including cost of hardware etc on existing platform complete. Pump shall have following HP Rating, phase, Head, minimum Discharge respectively and Dynamically balanced rotating parts to ensure min. vibration etc. complete in all respect.30.0 HP, 3-Ø, (42- 65)Mtr, (1840-1280) LPM, (Bronze impeller & CI Body)	200824.00	Each	401648.00
11	312.00	Earth work in excavation by mechanical means (Hydraulic Excavator)/ manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sum on plan) including dressing of sides and ramming of bottoms, lift upto 1.5 m, including taking out the excavated soil and depositing and refilling of jhiri with watering & ramming and disposal of surplus excavated soil as directed with in a lead of 50 meter. All kinds of soils	178.00	Cum	55536.00
12		Providing and laying in position cement concrete including curing, compaction etc. complete in specified grade excluding the cost of centering and shuttering - All work up to plinth level.			
a	54.00	1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40 mm nominal size).	3302.00	Cum	178308.00
13	130.00	Providing and laying in position specified grade of cement concrete for RCC structural elements upto floor five level including curing, compaction, finishing with rendering in cement sand mortar 1:3 (1 cement: 3 coarse sand) and making good the joints and cost of plastizers(if required) excluding the cost of centering, shuttering and reinforcement for Beams, suspended floors, roofs, grids having slopes up to 15°, landings, balconies, shelves, chajjas, lintels, bands, plain windows sills, staircases and spiral staircases etc. M20 grade Nominal Mix / Design Mix	5185.00	Cum	674050.00
14	1157.00	Centering and Shuttering with plywood or steel sheets including strutting, propping bracing both ways and removal of formwork for foundation , footings, strap beam, raft , bases of columns etc.	157.00	Sqm	181649.00
15		Providing and fabricating reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding (including cost of binding wire) all complete up to floor five level.			
a	10205.00	Thermo-mechanically Treated bars (Conforming of relevent IS code)	77.00	Kg.	785785.00
16		Plaster on new surface on wall in cement sand mortar 1:3 including racking of joints etc. complete fine finish :			
a	1160.00	12mm thick	164.00	Sqm	190240.00
b	1160.00	Finishing with neat cement (punning).	36.00	Sqm	41760.00
17	7920.00	Providing and fixing steel gate, grating , and grills made of angles, tees, square bars, flats,or black pipe with holdfast and fittings complete as per design and drawing including cutting welding and fabrication with priming coat of red oxide	105.60	Kg	836352.00
18	150.00	Painting with enamel paint of approved brand and manufacture to give an even shade Two or more coats on new work.	69.00	Sqm	10350.00
19		Providing, Laying & Jointing R.C.C. class NP-2 Non-Pressure pipes (IS : 458mark) of approved make with collars,			

Signature valid

Digitally signed by Rajkesh Meena
 Designation: Secretary
 Date: 2026.06.25 12:06:51 IST
 Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

		jointed with C.M. 1:2 or having Spigot and socket ends with flexible rubber rings joint including testing of joints etc. complete :			
a	50.00	300mm dia Internal	991.00	Mtr	49550.00
20		Construction of tube-well from ground levels and upto 100 Meter depth and above to accommodate housing and assembly pipe of following sizes in all types of alluvium strata by percussion/ rotary drilling method and with gravel as per IS:4097-1967 and packing as per IS:2800 (Part I -& II) 1979 as amended upto date (the work includes the cost of gravel & its primary packing and packing during development, lowering of housing & strainer assembly pipes, with supply and wrapping of coir-rope, wherever necessary, for arresting fine sand particles. The work will not include cost of housing pipe and strainer pipe assembly and development work, but work would be completed after obtaining sand free water).			
a	300.00	250mm –do-.	1863.00	P.Rmt.	558900.00
21	10.00	Development of tube well as per IS specification using suitable compressor to give sand free water for required yield of the gravel packed tube well.	600.00	Hrs.	6000.00
22		Supply of ERW M.S. black casing pipe ISI marked (IS:4270/1992) of grade Fe410 of following sizes at site of work.Nominal bore of pipe (mm)			
a	75.00	200	1728.00	P.Rmt.	129600.00
23		Supply of strainer pipes made of ERW M.S. black pipe ISI mark of following sizes at the site of work including required size of slotting as per IS:8110-1985.			
a	25.00	200mm-do-.	2031.00	P.Rmt.	50775.00
24		S & F tube well cover of M.S.sheet (6mm thick) with nuts and bolts complete for casing size:			
a	1.00	200mm dia	373.00	Each	373.00
b	1.00	S & F M.S. clamp, set of 50 ×6mm flat iron with nuts and bolts etc. for holding the riser pipe assembly of submersible pump set.	266.00	Each	266.00
25		Providing & lowering of G.I. Pipes, flange pipe including rubber washer and nuts of 8 mm dia complete in all respect I.S.1239 Marked.			
a	85.00	B Class 50 mm dia	498.00	P.Rmt.	42330.00

Signature valid

Digitally signed by Rajkesh Meena
 Designation: Secretary
 Date: 2026.06.25 12:06:51 IST
 Reason: Approved

RajKaj Ref No.:
 23047897

M e-Sign

26		SITC of Radial / mixed flow ISI marked water and anti-corrosive liquid filled submersible motor pump sets suitable for 100/150mm dia borewell. The size of adopter fixed on top of the motor should exceed the top of coupler , for safeguard the coupler. The construction material of motor and pump should match IS: 8034 : 2018 and IS: 9283 guideline. The radial flow pumpset should operate at 5 star energy efficiency level of BEE and mixed flow pump set should operate at 3 star energy level of BEE, accompanied by valid BEE certificate. Motor should be IE2 class as per IEC 60034-2-1: 2007, IEC 60034-30: 2008, & IS12615:2011 with required accessories including making connection suitable for Bore well. The job includes labour part of lowering of riser pipe G.I./ H.D.P.E. with rope, cables & pump, installation of complete fitting and accessories, jointing of electrical cables up to Starter. All labour for testing of submersible pumps set and supply of water to water mains, complete in all respect. OEM shall have submit NABL / CPRI / ERDA accredited lab type test certificate before execution. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
27	1.00	150 mm diameter Submersible pump shall have following HP Rating, phase, Head range, Discharge range respectively,10.0 HP, 3-Ø, (91 - 115)Mtr, (285-180) LPM	82408.00	Each	82408.00
28	1.00	P & F Full way Valve (IS: 778 Mark) or wheel valve of approved make Gun metal 50mm nominal bore)	1464.00	Each	1464.00
29	1.00	SITC of IP 54 OEM Fabricated DOL/Star-Delta Starter panel with switchgear selection as per Type-2 Coordination Chart and made out from 1.6 mm thick powder coated CRCA sheet, enclosure comprising of over load protection relay, short circuit & single phasing protection(for three phase pumps), Illuminated ON / OFF push buttons, ammeter, voltmeter, indicating lamps, 2P/4P MCB etc. suitable for following rating motors complete in all respect. For Three phase Submersible / Mono block pump 7.5 HP to 10.0 HP (Star / Delta starter)	19601.00	Each	19601.00
30		Providing & Laying P.V.C. / XLPE insulated & P.V.C. sheathed Un-Armoured Aluminium cable conforming to IS:1554 P-I / IS :7098 P - I of 1.1 KV with H4- Grade electrolytic aluminium conductor conforming to IS 8130 of purity >99.6 %, Inner / outer sheath conforming to IS:5831 in existing RCC / Hume / Stoneware / PVC pipe/ open duct/cable trench / Cable tray (with cable tie) including testing etc. as required of following size. OEM must have it's own in house NABL accredited Laboratory for testing procedure as per IS:10810. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
a	400.00	6 Sqmm 3 Core Unarmoured.	103.00	P.Rmt	41200.00
b	50.00	10 Sqmm 4 Core armoured.	163.00	P.Rmt	8150.00
31	190.00	Earth work in excavation by mechanical means (Hydraulic excavator)/ manual means over areas (exceeding 30cm in depth. 1.5m in width as well as 10 sum on plan) including disposal of excavated earth, lead upto 50m and lift upto 1.5 m , disposed earth to be levelled and neatly dressed: All kinds of soil	175.00	Cum	33250.00
32		Providing and laying in position cement concrete including curing, compaction etc. complete in specified grade excluding the cost of centering and shuttering - All work up to plinth level.			

Signature valid

Digitally signed by Rajkaj Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

a	10.10	1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40 mm nominal size).	3302.00	Cum	33350.20
33		Random Rubble stone masonry for with hard stone in foundation and plinth in Cement Sand mortar above 30 CM thick wall in:			
a	90.00	Cement Mortar 1:6 (1-Cement : 6-Sand).	2838.00	Cum	255420.00
34		Plaster on new surface on walls in cement sand mortar 1:4 including racking of joint etc. complete fine finish :			
a	120.00	25 mm thick	227.00	Sqm	27240.00
35		Cement concrete flooring 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate) finished with a floating coat of neat cement including cement slurry, making of lines or groove etc complete but excluding the cost of nosing of steps etc. complete.			
a	16.00	40mm thick with 20mm thick nominal size aggregate.	277.00	Sqm	4432.00
36	9.00	Providing and laying in position specified grade of cement concrete for RCC structural elements upto floor five level including curing, compaction, finishing with rendering in cement sand mortar 1:3 (1 cement: 3 coarse sand) and making good the joints and cost of plastizers(if required) excluding the cost of centering, shuttering and reinforcement for Beams, suspended floors, roofs, grids having slopes up to 15°, landings, balconies, shelves, chajjas, lintels, bands, plain windows sills, staircases and spiral staircases etc. M25 grade Nominal Mix / Design Mix	5254.00	Cum	47286.00
a		Centering & shuttering with plywood or steel sheets including strutting, propping bracing both ways with steel props and removal of formwork for upto floor five level for :			
37	49.30	Suspended floors, roofs, landings, staircases, balconies, girders, cantilevers, bands, coping bed plates, anchor blocks, sills, chhajjas, lintel, beam, plinth beam etc.	340.00	Sqm	16762.00
38		Providing and fabricating reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding (including cost of binding wire) all complete up to floor five level.			
a	706.50	Thermo-mechanically Treated bars (Conforming of relevent IS code)	77.00	Kg.	54400.50
39	71.24	Providing and laying pitching on slopes laid over prepared filter media as per drawing and MoRTH specifications Clause 2504.2.1Stone/Boulder For All Rajasthan except Bikaner, Hanumangarh and Sri Ganganagar	820.10	Cum	58422.90
40		Construction of Tube-well upto 100 Meter depth and above in all type of rocks by DTH system and over burden, to accommodate casing pipe of following sizes in all types of soils and over burden including lowering of casing pipes, but excluding cost of casing pipes as per IS : 2800 (Part I & II) 1979 specifications. The work would be completed after obtaining sand free water. The tube well should have a throughout bore as per nominal dia of casing pipe:			
a	120.00	200 mm dia Nominal bore.	999.00	Rmt	119880.00
41		Supply of ERW M.S. black casing pipe ISI marked (IS:4270/1992) of grade Fe410 of following sizes at site of work.Nominal bore of pipe (mm)			
a	120.00	200	1728.00	P.Rmt.	207360.00
42		P & F G.I. Pipes (External Work) with G.I. fittings excluding union (IS : 1239 Mark) including trenching & refilling earth etc.			

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

a	120.00	32mm dia nominal bore 'B' Class	342.00	P.Rmt.	41040.00
43	2.00	Supplying & Fixing Ferro Cement cover with CI frame for chamber & Manhole of size rectangular shape 600X450 mm to withstand 3 MT center point load & minimum unfractured load of 1 MT (light duty)	1357.00	Each	2714.00
44	147.00	Earth work in excavation by mechanical means (Hydraulic Excavator)/ manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sum on plan) including dressing of sides and ramming of bottoms, lift upto 1.5 m, including taking out the excavated soil and depositing and refilling of jhiri with watering & ramming and disposal of surplus excavated soil as directed with in a lead of 50 meter. All kinds of soils	178.00	Cum	26166.00
45		Providing and laying in position cement concrete including curing, compaction etc. complete in specified grade excluding the cost of centering and shuttering - All work up to plinth level.			
a	13.00	1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40 mm nominal size).	3302.00	Cum	42926.00
46	40.50	Providing and laying in position specified grade of cement concrete for RCC structural elements upto floor five level including curing, compaction, finishing with rendering in cement sand mortar 1:3 (1 cement: 3 coarse sand) and making good the joints and cost of plastizers(if required) excluding the cost of centering, shuttering and reinforcement for Beams, suspended floors, roofs, grids having slopes up to 15°, landings, balconies, shelves, chajjas, lintels, bands, plain windows sills, staircases and spiral staircases etc. M25 grade Nominal Mix / Design Mix	5254.00	Cum	212787.00
47	196.00	Centering and Shuttering with plywood or steel sheets including strutting, propping bracing both ways and removal of formwork for foundation , footings, strap beam, raft , bases of columns etc.	157.00	Sqm	30772.00
48		Providing and fabricating reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding (including cost of binding wire) all complete up to floor five level.			
a	3179.25	Thermo-mechanically Treated bars (Conforming of relevent IS code)	77.00	Kg.	244802.25
49		Plaster on new surface on wall in cement sand mortar 1:3 including racking of joints etc. complete fine finish :			
a	118.00	12mm thick	164.00	Sqm	19352.00
b	118.00	Finishing with neat cement (punning).	36.00	Sqm	4248.00
50	2.00	Supplying & Fixing Ferro Cement cover with CI frame for chamber & Manhole of size rectangular shape 600X450 mm to withstand 3 MT center point load & minimum unfractured load of 1 MT (light duty)	1357.00	Each	2714.00
51		P & F G.I. Pipes (External Work) with G.I. fittings excluding union (IS : 1239 Mark) including trenching & refilling earth etc.			
a	10.00	50mm dia nominal bore 'B' Class	491.00	P.Rmt	4910.00
52		P & F G.I. pipes (Internal Work) with G.I. Fittings excluding union (IS:1239 Mark) & MS clamps including cutting and making good the walls and floors:			
a	10.00	50mm dia nominal bore 'B' Class	673.00	P.Rmt	6730.00
53		P & F Ball Cock (IS :1703 Mark) with Rod & P.V.C. Ball complete :			

Signature valid

Digitally signed by Rajkesh Meena
 Designation: Secretary
 Date: 2026.06.25 12:06:51 IST
 Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

a	2.00	(-do-) wt. Not less than 1200 gm 50mm.	789.00	Each	1578.00
54		P & F Full-way Valve (IS:778 Mark) or wheel valve of approved make :			
a	2.00	Gun Metal 50mm nominal bore.	1464.00	Each	2928.00
55	2.00	P & F Gun metal Non return Valve or Check Valve (IS: Make) of approved make superior quality 50mm nominal bore Vertical	964.00	Each	1928.00
56	118.00	Providing and laying water proofing treatment to vertical and horizontal surfaces of depressed portions of W.C., kitchen and the like consisting of :(i) Ist course of applying cement slurry @ 4.4 Kg/sum mixed with\ water proofing compound conforming to IS 2645 in recommended proportions including rounding off junction of vertical and horizontal surface. (ii) IInd course of 20mm cement plaster 1:3 (1 cement: 3 coarse sand) mixed with water. proofing compound in recommended proportion including rounding off junction of vertical and horizontal surface.. (iii) IIIrd course of applying blown or residual bitumen applied hot at 1.7 Kg per sqm. of area. (iv) IVth course of 400 micron thick PVC sheet .(Overlaps at joints of with bitumen @ 1.7 Kg/sqm.)	513.00	Sqm	60534.00
57	121.00	Earth work in excavation by mechanical means (Hydraulic Excavator)/ manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sum on plan) including dressing of sides and ramming of bottoms, lift upto 1.5 m, including taking out the excavated soil and depositing and refilling of jhiri with watering & ramming and disposal of surplus excavated soil as directed with in a lead of 50 meter. All kinds of soils	178.00	Cum	21538.00
58		Providing and laying in position cement concrete including curing, compaction etc. complete in specified grade excluding the cost of centering and shuttering - All work up to plinth level.			
a	30.00	1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40 mm nominal size).	3302.00	Cum	99060.00
59		Random Rubble stone masonry for with hard stone in foundation and plinth in Cement Sand mortar above 30 CM thick wall in:			
a	91.00	Cement Mortar 1:6 (1-Cement : 6-Sand).	2838.00	Cum	258258.00
60		Random Rubble stone masonry with hard stone in superstructure above plinth level and upto five level above 30cm. thick walls in :			
a	158.00	Cement Mortar 1:6 (1-Cement : 6-Sand).	3479.00	Cum	549682.00
61		Add extra for Random Rubble stone masonry with hard stone in			
a	137.00	Wall upto 30cm. and less thickness.	186.00	Cum	25482.00
62	21.00	Add extra for Random Rubble stone pillar masonry with hard stone in	173.00	Cum	3633.00
63	154.00	Brick work with F.P.S. bricks of class designation 75 in superstructure above plinth level upto floor V level in all shapes and sizes in : Cement mortar 1 : 6 (1 cement : 6 coarse sand)	4990.00	Cum	768460.00
64		Plaster on new surface on walls in cement sand mortar 1:6 including racking of joint etc. complete fine finish :			
a	1123.00	25 mm thick	211.00	Sqm	236953.00
65		Yellow/pink colour wash with Khameera mixed with pigment including making gola garden, Kangoora and ornamental lining work as per approved Jaipur style and pattern complete in all respect as per direction of Engineer in Charge			

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

a	202.00	On New Surface (3 coats)	88.00	Sqm	17776.00
66	151.00	Providing & fixing precast cement concrete coping 1 : 2 : 4 mix 50mm thick complete as per specification :	367.00	Sqm	55417.00
a		Finishing wall with water proofing cement paint of approved brand and manufacture and or required shade to give an even shade including all scaffolding:			
67	1374.00	New work (Two or more coats applied @ 3.84 kg/10 sqm).	123.00	Sqm	169002.00
68	1500.00	Providing and fixing steel gate, grating , and grills made of angles, tees, square bars, flats, or black pipe with holdfast and fittings complete as per design and drawing including cutting welding and fabrication with priming coat of red oxide	105.60	Kg.	158400.00
69		Painting with synthetic enamel paint of approved brand and manufacture to give an even shade :			
a	60.00	Two or more coats on new work	69.00	Sqm	4140.00
70		Laying of lawns including ploughing levelling breaking of clods manuring & removal of stones etc.(Cost of manure or extra good earth to be paid separately) Maintenance of lawns for 30 days or more till the grass forms a thick lawns free from weeds & fit for moving in the duration of planting if lawn die some where the contractor will replant it at his own cost.			
a	300.00	In rows 5 Cms. apart in either direction	6600.00	P. 100 Sqm	19800.00
71		Providing and laying in position cement concrete including curing, compaction etc. complete in specified grade excluding the cost of centering and shuttering - All work up to plinth level.			
a	35.00	1:5:10 (1 cement : 5 coarse sand : 10 graded stone aggregate 40mm nominal size).	2956.00	Cum	103460.00
72	48.00	Providing and laying at or near ground level factory made kerb stone of M-25 grade cement in position to the required line, level and curvature jointed with cement mortar 1:3 (1 cement : 3 coarse sand) including making joints with without grooves (thickness of joints except at sharp curve shall not to more than 5mm) including making drainage opening wherever required complete including painting etc. as per direction of Engineer-in-charge (length of finished kerb edging shall be measured for payment). (Precast C.C. kerb stone shall be approved by Engineerin- charge).	6103.00	Cum	292944.00
73	7446.00	Providing and laying of paver block as per IS 15658 : 2006 (Indian standard for precast concrete block for paving specification) and IRC : SP:63-2004 (guidelines for the use of interlocking concrete block pavement) M-30, 60 mm thick to be used in non traffic areas like building premises, monument premises, land scapes, public gardens/ park, domestic drives, paths and patios, Embankment slopes, sand stabilization Area etc.(As per table 1 of IS 15658:2006 Category A Denated units to key into each other on four faces	816.00	Sqm	6075936.00
74	2236.80	Supplying and fixing of chain link fencing with angle iron posts 50x50x6mm placed at every 3 Mtr. apart 30cm in ground embedded in cement concrete 1:3:6 (30x30x45cm) corner and every tenth post to be strutted with (50 x 50 x 6cm) angle iron provided and fixed and fitted with posts including earth work in excavation etc. complete with chain link size.50mm x 50mm x 3.15mm	629.00	Sqm	1406947.20
75	8.00	Supply and erection of Galvanized Iron pole with galvanizing done in single dipping (Average coating thickness Minimum 65 Microns) Swaged tubular pole conforming to IS: 2713-1980 (part I to II) with galvanised	840.00	Cum	3097800.00

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

		base plate, The pole shall be made from steel tube & Pipe (IS:1141, Fe 410) including excavation of the pit and filling the same with C.C. of M-20 grade (1:1.5:3) from base plate to 50 cm above ground level, with the help of steel frame not less than 40 cm dia up to 114.3mm outer dia and 50 cm beyond 114.3mm outer dia around the pole. Duly finished with cement plaster, earthing terminals, cable entry with 32 mm dia. 'B' class GI cable sleeves complete as required. of following height & designation. (See Table P - 02 for specs.) All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .12 Mtr. (410 SP - 60)			
76	200.00	Add for supply and fixing of Pole OEM fabricated Galvanized Overhang of following size over the existing poles. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .88.9 mm OD x 3.25 mm thickness	2176.00	Mtr.	435200.00
77	48.00	Providing & Fixing of IK08 IP65 protected Top/Bottom mounted LED Post top Luminarie made of single piece construction powder coated die cast aluminium housing with UV stabalized Clear / frosted Polycarbonate diffuser and Aluminium anodised with sand blast reflector. The System level Luminous efficacy \geq 100 Lumen/W. SMD LEDs is to be used, System CRI>70, CCT: 3000/4000/6500 K. The integral electronic driver must be potted & has a unique BIS R number must be potted & has a unique BIS R number constant current and Internal/external surge protection device of min. 4KV(L-N) and efficiency > 85%, PF>0.9, THD<10% and input Voltage range of 140-270V AC at 50Hz. System life of 50000 Burning hours with 70% of Initial Lumens maintained . Driver current <750mA. Fixture must be in compliance with BIS Standards and Trade mark Certificate complete in all respect.OEM Must have its own in house NABL lab setup for all testing facilities for LED fixtures. (LM79/LM80) Certificate/ report with liable warranty of product/accessories from OEM shall be submitted. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .Minimum lumen output 4000 lm Post top Luminarie	7481.00	Each	359088.00
78	700.00	Providing & Laying P.V.C. / XLPE insulated & P.V.C. sheathed Un-Armoured Aluminium cable confirming to IS:1554 P-I / IS :7098 P - I of 1.1 KV with H4- Grade electrolytic aluminium conductor confirming to IS 8130 of purity >99.6 %, Inner / outer sheath confirming to IS:5831 in existing RCC / Hume / Stoneware / PVC pipe/ open duct/cable trench / Cable tray (with cable tie) including testing etc. as required of following size. OEM must have it's own in house NABL accredited Laboratory for testing procedure as per IS:10810. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR16.0 Sq. mm 4 core	206.00	Mtr	144200.00
79	100.00	Providing & Laying P.V.C. / XLPE insulated & P.V.C. sheathed Armoured Aluminium cable confirming to IS:1554 P-I / IS :7098 P - I of 1.1 KV with H4- Grade electrolytic aluminium conductor confirming to IS 8130 of purity >99.6 %, round / flat strip armouring of cables, Inner / outer sheath confirming to IS:5831 in existing RCC / Hume / Stoneware / PVC pipe/ open duct/cable trench / Cable tray(with cable tie) including testing etc. as required of following size. OEM must have it's own in house NABL	2491.00	Mtr	249100.00

Signature valid

Digitally signed by Rajkesh Meena
 Designation: Secretary
 Date: 2026.06.25 12:06:51 IST
 Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

		accredited Laboratory for testing procedure as per IS:10810.For additional technical parameters of product / work refer Annexure 'A' attached with this BSR 35 Sq. mm 4Core			
80	8.00	SITC of Bus Rising Main OEM manufactured following capacity End Feed Unit Confirming to ANSI C37.23 standard & IS 8623 P-II suitable for Sandwich / Compact Air Insulated type for use on 3 phase 4 wire 415 volts, 50Hz A.C. supply made with 1.5 mm thick steel sheet enclosure duly powder coated with provision of MCCB/ACB (but without MCCB/ACB), Interlocking feature complete with necessary joints including clamping brackets, angle iron bracket, steel fasteners, connecting to earthing system etc. as required. . 63 amps (Suitable for MCCB) without MCCB	9460.00	Each	75680.00
81	4.00	Providing & Fixing of Recessed/surface mounting heavy duty Vertical TPN Distribution board with Metal end box with provision of incomer suitable for 3/4 pole MCCB and SP / TP MCB as outgoing ,made out from Galvanized steel / CRCA sheet not less then 1.2 mm thick conforming to IS-8623-1 & 3 / IEC 61439- 1 & 3. powder painted with reversibile door (for double door DB only) complete with insulated 160 (upto 160 A Incomer) / 250 Amp. copper bus bar, neutral bars with shrouds, earth bar , color coded interconnecting wire set of suitable rating and din bar,masking sheet, making internal DB terminations with copper lugs, ferrules, detachable gland plate, including making connections, testing etc. as required. OEM shall have submit NABL / CPRI / ERDA accredited lab type test reports & All as per pre approved by Engineer in charge.For additional technical parameters of product / work refer Annexure 'A' attached with this BSRDouble door IP-43 & IK-09 with Provision of Incomer MCCB 250 A Rating with Metal end box 8 Way	18760.00	Each	75040.00
82	2.00	Plate Earthing as per IS:3043 with copper Earth plate of purity >95% of size 600mm x 600mm x 3.0mm by embodying 3 mtr. below the ground level with 20 mm dia. G.I. 'B' class watering Pipe ,including all accessories like nut, bolts, reducer, nipple, wire meshed funnel, and Heavy duty weather proof poly-propylene earth pit chamber with lockable Jam free lid suitable for safe working load 5000 Kg or more of size Top Dia. 225 to 260 mm, Bottom Dia 300 to 350 mm. and Height 250 to 300 mm. and embodying the pipe complete with alternate layers salt and coke/ charcoal, testing of earth resistance for value of 5 ohms or less as required & must record by engineer in charge during site visit and ensure to enter in measurment book. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .	18604.00	Set	37208.00
83	32.00	Providing & Fixing of 240/415 V AC MCB with positive isolation of 10 kA breaking capacity (B/ C/D tripping characteristic as per type of load and site requirement) 4 KV impulse withstand voltage, ISI marked IS 8828(1996) / conforming to IEC 60898-1 2002, IEC 60947-2, low watt losses, trip free mechanism , energy limiting of class 3 as per IEC, minimum phase termination capacity of 25 sq.mm., conductor line load reversibility , IP 20 contact protection and fitted in existing distribution board/sheets, minimum electrical operation 20,000 upto 20 A rating, 10,000 upto 63 A, 5000 for 80 A & above rating including making connections, testing etc. as required. Four pole MCB (With B / C curve tripping characteristics) 50/63 A rating	2050.00	Each	65600.00
		Construction of Toilet Block			

Signature valid

Digitally signed by Rajkaj Meena
 Designation: Secretary
 Date: 2026.06.25 12:06:51 IST
 Reason: Approved

RajKaj Ref No.:
 23047897

M e-Sign

84	25.00	Surface dressing of the ground including removing vegetation and inequalities not exceeding 15cm deep and disposal of rubbish lead up to 50 Mtr. and lift up to 1.5 Mtr. : All kinds of soil	9.00	Sqm	225.00
85	178.71	Earth work in excavation by mechanical means (HydraulicExcavator)/ manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan) includingdressing of sides and ramming of bottoms, lift upto 1.5 m,including taking out the excavated soil and depositing andrefilling of jhiri with watering & ramming and disposal of surplus excavated soil as directed with in a lead of 50 meter. All kinds of soils	178.00	Cum	31810.91
86	67.33	Filling available excavated earth (excluding rock) in trenches,plinth side of foundation etc. in layers not exceeding 20 cm. indepth, consolidating each deposited layer by ramming and watering including lead up to 50 meter and with all lift.	64.00	cum	4308.85
87	18.40	Supplying and Filling in plinth with river sand under floorsincluding watering ramming consolidating and dressing complete including cost of sand	1024.00	Cum	18838.66
88	86.27	Providing and laying in position cement concrete including curing, compaction etc. complete in specified grade excluding the cost of centering and shuttering - All work up to plinth level. 1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40 mm nominal size).	3302.00	Cum	284860.65
89	10.68	Providing and laying in position cement concrete including curing, compaction etc. complete in specified grade excluding the cost of centering and shuttering - All work up to plinth level. M10 grade Nominal Mix 1: 3: 6 (1 cement : 3 coarse sand : 6 graded stone aggregate 20mm nominal size).	3847.00	Cum	41085.79
90	10.68	Random rubble dry stone Kharanja under floor.	932.00	Cum	9953.72
91	45.79	Random Rubble stone masonry for with hard stone in foundation and plinth in Cement Sand mortar above 30 CM thick wall in:Cement Mortar 1:6 (1-Cement : 6-Sand).	2838.00	Cum	129938.54
92	34.27	Providing and laying in position specified grade of cement concrete for all RCC structural elements upto plinth level including curing, compaction, finishing with rendering in cement sand mortar 1:3 (1 cement: 3 coarse sand) and making good the joints and cost of plastizers(if required) excluding the cost of centering, shuttering and reinforcement. M20 grade Nominal Mix / Design Mix	4934.00	Cum	169083.99
93	24.62	Providing and laying in position specified grade of cement concrete for RCC structural elements upto floor five level including curing, compaction, finishing with rendering in cement sand mortar 1:3 (1 cement: 3 coarse sand) and making good the joints and cost of plastizers(if required) excluding the cost of centering, shuttering and reinforcement for Beams, suspended floors, roofs, grids having slopes up to 15°, landings, balconies, shelves, chajjas, lintels, bands, plain windows sills, staircases and spiral staircases etc. M20 grade Nominal Mix / Design Mix	5185.00	Cum	127650.24
94	58.89	Add extra for providing richer mixes respectively at all floor levelsProviding M-25 grade concrete by using cement as per codal provision instead of M-20 grade design mix.	69.00	Cum	4063.29

Signature valid

Digitally signed by Rajkesh Meena
 Designation: Secretary
 Date: 2026.06.25 12:06:51 IST
 Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

95	42.02	Centering and Shuttering with plywood or steel sheets including strutting, propping bracing both ways and removal of formwork for foundation , footings, strap beam, raft , bases of columns etc.	157.00	Sqm	6597.14
96	136.25	Centering & shuttering with plywood or steel sheets including strutting, propping bracing both ways with steel props and removal of formwork for upto floor five level for :Suspended floors, roofs, landings, staircases, balconies, girders, cantilevers, bands, coping bed plates, anchor blocks, sills, chhajjas, lintel, beam, plinth beam etc.	340.00	Sqm	46325.03
97	75.00	Centering & shuttering with plywood or steel sheets including strutting, propping bracing both ways with steel props and removal of formwork for upto floor five level for :Columns, pillars, posts and struts etc.	375.00	Sqm	28125.00
98	5105.88	Providing and fabricating reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding (including cost of binding wire) all complete up to floor five level. (Original producers' who manufacture billet directly from iron ores and roll the billets to produce steel conforming to IS:1786)Thermo-mechanically Treated bars (Conforming of relevent IS code)	77.00	Kg	393152.87
99	28.25	Brick work with clay flyash F.P.S. brick (IS 13757- 1993) of class designation 75 in superstructure above plinth level upto floor five level in : Cement mortar 1 : 6 (1 cement : 6 coarse sand)	4832.00	Cum	136498.90
100	127.10	Half Brick work with mechanised autoclaved flyash lime bricks conforming to IS: 12894 :2002 of class designation 75 in superstructure above plinth level upto floor V level in. Cement mortar 1 : 6 (1 cement : 6 coarse sand)	536.00	Sqm	68124.53
101	5.00	Cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size)	4483.00	Cum	22415.00
102	50.46	Providing gola 75x75 mm in cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 stone aggregate 10mm and down gauge) including finishing with cement mortar 1:3 (1 cement : 3 fine sand) as per standard design :	111.00	Mtr.	5601.06
103	73.44	Providing and fixing 1st quality standard white, grey, ivory,fume red brown, light green, light blue and other light shadesglazed tiles confirming to code IS : 15622 of size 200mm x300mm in walls, floors, steps, pillars etc. laid on a bed of neatcement slurry finished with flush pointing in the white cementmixed with pigment to match the shade of the tile complete(excluding the cost of cement plaster on walls and pillar).	674.00	Sqm	49498.56
104	71.20	Providing and fixing 1st quality MAT finished ceramic tilesize 300x300mm confirming to code IS : 15622 colour suchas white, grey, ivory, fume red brown, light green, light blueand other light shades in floors, steps, pillars etc. laid on a bed of neat cement slurry finished with flush pointing in the whitecement mixed with pigment to match the shade of the tilecomplete (including the cost of cement mortar bed 1:4).	748.00	Sqm	53257.38
105	73.44	Extra for using size above 200x300mm in glazed tiles andfor using 400mm x 400mm MAT finished tiles in place of300mm x 300mm size	74.80	Sqm	5493.31

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

106	104.76	Providing and fixing T-iron frames for doors, windows and ventilators of mild steel Tee-sections, joints mitred and welded with 15x3 mm lugs 10cm long embedded in cement concrete blocks 15x10x10 cm of 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 20 mm nominal size) or with wooden plugs and screws or rawl plugs and screws or with fixing clips or with bolts and nuts as require including fixing of necessary butt hinges and screws and applying a priming coat of approved steel primer	83.00	Kg	8695.08
107	22.05	Providing and fixing to existing door frames 24mm thick factory made PVC door shutters made of stiles and rails of a uPVC hollow section of size 59x24 mm and wall thickness 2mm +/- 0.2 mm with built edging on both sides. The stiles and rails mitred and joined at the corners by means of M.S. galvanized/plastic brackets of size 75x220mm having wall thickness 1.0mm +/- 0.1mm and stainless steel screws. The stiles of the shutter reinforced by inserting galvanized M.S. tube of size 20x20mm and 1mm +/- 0.1mm wall thickness. The lock rail made up of „H“ section, a uPVC hollow section of size 100x24mm and 2mm +/- 0.2mm wall thickness fixed to the shutter stiles by means of plastic/galvanized M.S. „U“ cleats. The shutter frame fitted with a uPVC multi-shambered single panel of size not less than 610mm, having overall thickness of 20mm and 1mm +/- 0.1mm wall thickness. The panels fitted vertically and tie bar at two places by inserting horizontally 6mm galvanized M.S. rod and fastened with nuts and washers, complete as per manufacturer's specification and direction of Engineer-in-charge (For W.C. and bathroom door shutter).	1761.00	Sqm	38830.05
108	10.50	Providing and fixing pressed steel mitred door frames manufactured from commercial mild steel sheet of 1.25mm (16 gauge) thickness including hinges jamb, lock jamb, head and if required angle threshold of mild steel angle of section 50x25mm, or base ties of 1.25mm pressed mild steel welded or rigidly fixed together by mechanical means, adjustable lugs with split end tail to each jamb including steel butt hinges 2.5mm thick with mortar guards, lock strike-plate and shock absorbers as specified and applying a coat of approved steel primer after pre-treatment of the surface including filling with C.C 1:2:4 (M-15 Grade) complete in all respect as directed by Engineer-in-charge: Profile B	429.00	Mtr.	4504.50
109	4.41	Providing and fixing external grade board solid core single leaf flush door shutters ISI 2202-67 marked using Phenol formal dehyderesin in glue both sides with approved steel fittings complete as per annexure 'A' : complete as per annexure 'A' : 30 mm thick .commercial veneer both side	1841.00	sqm	8118.81
110	4.41	Extra for providing external lipping with 2nd class teak wood battens 6 mm minimum depth on all edges of shutters (over all area of door shutter to be measured) Over item no. 8.13.	141.00	sqm	621.81
111	4.41	Extra for providing other type of fittings as mention in annexure A (as approved by EI) :Stainless steel fittings	184.10	sqm	811.88
112	549.82	Plaster on new surface on walls in cement sand mortar 1:4 including raking of joints etc. complete fine finish: 20 mm thick.	202.00	sqm	111064.23
113	108.37	6mm cement plaster to ceiling of mix 1:3 (1 Cement : 3 fine sand)	139.00	sqm	15063.79
114	25.00	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade : Two or more coats on new work	69.00	sqm	1725.00

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

115	204.65	Painting exterior surface of wall with 100% acrylic exterior paint of approved brand and manufacture to give an even shade including preparation of base with sand papering, primer, putty etc complete in all respect. New work	123.00	sqm	25171.65
116	80.63	Finishing walls with textured exterior paint of required shade as per approved colour complete as per manufacturers specifications including primer coat and protecting coat including scaffolding and safety provision Trowel Finish av. thickness 1500 to 2000 microns.	404.00	sqm	32574.10
117	20.00	Extra for making Ornamental design like Kangooras Gola etc. as per Jaipur practice in cement plaster	101.00	Sqm	2020.00
118	20.00	Making grooves as per design in plaster 10mm to 20mm wide.	7.00	Mtr.	140.00
119	2.00	P & F Indian type white glazed vitreous china 1st quality W.C. orissa pan (IS :2556 Mark) with 100 mm vitreous china P or S trap including cutting and making good the wall and floor: Size 580x440mm.	3080.00	Each	6160.00
120	4.00	P & F European type white glazed vitreous china 1st quality Double syphonic W.C (IS :2556 Mark) with P or S trap including cutting and making good the wall and floor	5198.00	Each	20792.00
121	4.00	P & F water closet Seat Covers with brass hinges complete : Solid PVC (IS 2548 marked) grade-I White for EWC.	402.00	Each	1608.00
122	4.00	P & F C.P. lugs for toilet seat cover.	79.00	Pair	316.00
123	4.00	P & F 1st quality WVC Urinal (IS:2556 mark) with 25mm dia G.I. waste pipe, dome waste couplings, concealed iron brackets or screws etc complete. Flat Back (large) or half stall size 610x400x80mm.	4637.00	Each	18548.00
124	3.00	P & F W.V.C. Urinal Partition Plate of approved standard make of size 630x315mm including making good the wall.	994.00	Each	2982.00
125		P & F Low level Flushing Cistern of 10 litres capacity (IS : 2556 mark) of approved make with complete fittings C.I. brackets duly painted, brass ball cock with ball (IS: 1703 mark) complete including cutting and making good the wall:			
a	6.00	PVC with PVC bend as per IS : 7231 .	1291.00	Each	7746.00
b	4.00	P & F C.P. brass Urinal Spreader for stall urinal of approved make.	363.00	Each	1452.00
c	4.00	P & F C.P. brass Doom Waste Coupling 32 mm dia.	152.00	Each	608.00
126	6.00	P & F WVC Wash basin (1st quality IS:2556 Mark) of approved make with C.I. brackets duly painted 1 No. 15 mm C.P. Pillar cock (IS:8934 Mark) & 32 mm C.P. brass waste coupling of approved make 25 mm G.I. waste pipe complete including cutting & making good the wall : Size 630 mm x 500 mm dia for counter top	3265.00	Each	19590.00
127		P & F Bottle Trap of approved make :			
a	6.00	C.P. Brass 40 mm	633.00	Each	3798.00
128		P & F Bevelled edge Mirror/mirror with teak wood lipping around of special glass of approved make as per direction of Engineer-in-charge complete with 6mm thick commercial ply base fixed to wooden screws & washers.			
a	2.00	Other sizes	1538.00	sqm	3076.00
129	2.00	Providing and fixing Superior quality CP Brass fittings of approved make as per direction of Engineer-in-charge Swan neck pillar cock 15 mm nominal size	1580.00	Each	3160.00
b	6.00	Bib Cock with long thread 15 mm nominal size	823.00	Each	4938.00
c	6.00	Angular stop cock with long thread 15 mm nominal size	766.00	Each	4596.00
d	5.00	Concealed stop cock 15 mm nominal size	1162.00	Each	5810.00

Signature valid

Digitally signed by Rajkaj Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

e	4.00	600 mm long towel rail	1801.00	Each	7204.00
f	4.00	Revolving type towel ring	1101.00	Each	4404.00
g	2.00	Soap dish (MCH/IVC)	1071.00	Each	2142.00
h	2.00	Double Coat hook(MCH/IVC)	823.00	Each	1646.00
i	2.00	Paper holder (MCH/IVC)	1125.00	Each	2250.00
130		P & F Extension Pipe for bib cocks of approved quality/make.			
a	2.00	C.P. brass of Heavy & Superior quality 50x15mm	85.00	Each	170.00
b	2.00	C.P. brass of Heavy & Superior quality 100x15mm	119.00	Each	238.00
131	4.00	P & F C.P. Health Faucet with 1Mtr. Long Tube & Hook of approved make and heavy as per direction of Engineer-in-Charge	605.00	Each	2420.00
a	12.00	Providing & fixing C.P.flange for 15mm dia taps.	18.00	Each	216.00
b	12.00	P&F Grating of approved quality/ makeStainless steel sheet size 125mm dia	62.00	Each	744.00
132		Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes (IS 15778 : 2007 code) having thermal stability for hot & cold water supply including all CPVC plain & brass threaded fittings i/c fixing the pipe with clamps at 1 metre spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge. (Internal work Exposed on wall)			
a	20.00	(i) 20mm dia	222.00	Mtr.	4440.00
b	15.00	(ii) 25mm dia	282.00	Mtr.	4230.00
c	10.00	(v) 50mm dia	802.00	Mtr.	8020.00
133		Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes (IS 15778 : 2007 code) having thermal stability for hot & cold water supply including all CPVC plain & brass threaded fittings i/c fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge. (Concealed work including cutting chases and making good the walls etc.,)			
a	12.00	20mm dia	289.00	Mtr.	3468.00
b	10.00	25mm dia	376.00	Mtr.	3760.00
134		Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes (IS 15778 : 2007 code) having thermal stability for hot & cold water supply including all CPVC plain & brass threaded fittings, this included jointing of pipes & fittings with one step CPVC solvent cement , trenching refilling & testing of joints complete as per direction of Engineer in Charge. (External work).			
a	10.00	50mm nominal outer dia pipes	757.00	Mtr.	7570.00
135		P & F Ball Cock (IS :1703 Mark) with Rod & P.V.C. Ball complete :			
a	4.00	(-do-) wt.Not less than 600 gm, 25mm.	440.00	Each	1760.00
b	0.00	P & F 15 mm. Dia Connection Pipe of approved quality/make :			
c	4.00	PVC pipe with C.P. Brass nuts upto length, 300mm	73.00	Each	292.00
d	4.00	PVC pipe with C.P. Brass nuts upto length 600mm.	116.00	Each	464.00
136		P & F Full-way Valve (IS:778 Mark) or wheel valve of approved make :			

Signature valid

Digitally signed by Rajkaj Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

a	2.00	Gun-metal 15mm nominal bore.	227.00	Each	454.00
b	2.00	Gun-metal 25 mm nominal bore.	529.00	Each	1058.00
c	1.00	Gun-metal 50mm nominal bore.	1464.00	Each	1464.00
137	4.00	P & F Inlet Connection (Angle Valves) Superior quality, of approved make, for Wash basin, Gyser etc.C.P. Inlet connection 15mm.Brass (IS : 8931 marked)	501.00	Each	2004.00
138		P & F PVC Storage Tank ISI Marked (IS : 12701) indicating the BIS license No), of approved make with cover, 25mm dia 1M long G.I. over-flow pipe & 25 Cm. long wash out pipe with plug & socket, including making connection etc., complete of approved design:			
a	2.00	1000 litres capacity.	7841.00	Each	15682.00
139		Hoisting Charges for each floor :			
a	2.00	For items 2.26.5 to 2.26.8	157.00	Each	314.00
140	9.00	Providing Laying & jointing glazed S.W. pipes grade `A` (IS:651 marked) of approved make with spun yarn & stiff mixture of cement mortar 1.1 excavation & refilling of earth in all types of soil upto 1.2m depth, S.W. fittings, including testing of joints etc, complete.150mm dia	406.00	Mtr.	3654.00
141		Providing & Laying C.C. 1:5:10 (Stone aggregate 40mm nominal size) upto haunches of S.W. pipes including 150 mm thick bed concrete (Width W= Dia of pipe in Cm+ 30Cm.) concrete width to be reduced from width W at center of pipe to `0` at top of pipe. (Excluding cost of pipe)			
a	9.00	150 mm dia . SW pipe	353.00	Mtr.	3177.00
142	6.00	P & F Square-mouth gully trap `A` grade (IS 651-1992 :marked) of approved make complete with C.I. grating, frame & Cover masonry chamber in C.M. 1:6, 100mm thick C.C. 1:5:10 base concrete, 40mm thick C.C.M-15 grade coping, 12mm thick cement plaster in CM 1:3 complete as per approved design & type.Trap size 150 X 100mm, ferrow cement cover with frame, Internal Chamber size 300 X 300mm.	1150.00	Each	6900.00
143		Providing Laying & Jointing R.C.C. class NP-2 Non-Pressure pipes (IS:458 mark) of approved make with collars, jointed with C.M. 1 : 2 or having Spigot and socket ends with flexible rubber rings joint including testing of joints etc. complete			
a	3.00	250mm dia Internal	891.00	Mtr.	2673.00
144		P&F rigid PVC Pipe (IS:4985 mark) class II/ (4 Kg. /Cm2.) approved quality /make including joining the pipe with solvent cement rubber ring and lubricant.			
a	10.00	75 mm dia	177.00	Mtr.	1770.00
b	6.00	110 mm dia	282.00	Mtr.	1692.00
145		P&F rigid PVC pipe fittings (IS: 4985 mark) of approved quality /make including joining the pipe with solvent cement rubber ring and lubricant:			
a		Coupler (socket)			
i	6.00	75mm dia	87.00	Each	522.00
ii	6.00	110mm dia	108.00	Each	648.00
b		Door tee			
i	3.00	75mm dia	177.00	Each	531.00

Signature valid

Digitally signed by Rajkesh Meena
 Designation: Secretary
 Date: 2026.06.25 12:06:51 IST
 Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

ii	4.00	110mm dia	213.00	Each	852.00
c		Bend 45			
i	4.00	75mm dia	80.00	Each	320.00
ii	4.00	110mm dia	128.00	Each	512.00
d		Bend 87 .5			
i	2.00	75mm dia	97.00	Each	194.00
ii	2.00	110mm dia	161.00	Each	322.00
e		Vent Cowel			
i	2.00	75mm dia	43.00	Each	86.00
ii	2.00	110mm dia	56.00	Each	112.00
f		Pipe clip			
i	6.00	75mm dia	24.00	Each	144.00
ii	6.00	110mm dia	36.00	Each	216.00
g		P- trap.			
i	2.00	110 mm dia	382.00	Each	764.00
146	1.00	Construction of manhole in all type of soil inner size 90 X 60 Cm. 300 mm thick masonry in CM 1:6, 10 Cm. thick cement concrete 1:5:10 in foundation, 20 mm thick inside plaster in CM 1:6, finished with floating neat cement, 50mm thick M-15 grade C.C. flooring, making channels, 80mm thick stone slab covering with 40mm thick M-15 grade C.C. flooring, Cement cover with frame of 450mm dia, earthwork etc. complete as per design including disposal of surplus earth within 50 mtr. lead. Depth up to 0.5 M	5489.00	Each	5489.00
147	1.00	Construction of chamber in all type of soil with 300 mm thick masonry in CM 1:6 m,10 cm thick C.C. 1:5:10 in foundation, 20mm thick insider plaster in Cm 1:6, finished with floating neat cement, 50mm thick M-15 grade C.C. flooring , earthwork etc. complete as per design including disposal of surplus earth within a lead of 50 mtr. Inside size 300 X 300 mm depth upto 0.5 m & 5kg. C.I. cover with frame	1049.00	Each	1049.00
148	1.00	Construction of septic Tank in all types of soil with 40 Cm .thick masonry in CM 1:6, 15 Cm thick C.C bed of 1:5:10, M-15 grade C.C floor & RCC slab covering with M15 grade c.c. floor, 50 mm thick stone slab partition walls, 20 mm thick plaster in CM 1:6 finished with neat floating cement, 4 Nos stone foot rests of approved design ,two No. 450 mm dia each Ferro cement cover with frame, earth work etc. complete as per approved drawing including disposal of surplus earth within a lead of 50 mtr:- Size 230 x110 x150 cm.(for 20 users) with 115 mm thick RCC (M-20) slab with Tor steel reinforcement 10mm ϕ @15 cm c/c bothways including shuttering complete in all respect.	38499.00	Each	38499.00

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

149		Wiring of light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper conductor 1.1 kV grade and 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper earth conductor 1.1 kV grade (IS:694) in recessed ISI marked MMS (IS:9537 P - III) virgin material PVC conduit & it's ISI marked (IS:3419-1988) accessories, round tiles, 1.2 mm thick Hot Dipped Galvanized Modular Box with earth terminal, 10A Modular switch, Modular face plate with grid plate, 3 pin ceiling rose / Holder /3 way connector, screws, making connections, testing etc. as required. For specification of copper Conductor, Phenolic Laminated sheet's & Electrical/ Wiring accessories refer Chapter E - 04, E - 05 & E - 07 For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
a	10.00	Short point (up to 3 mtr.)	343.00	Each	3430.00
b	6.00	Medium point (up to 6 mtr.)	601.00	Each	3606.00
c	4.00	Long point (up to 10 mtr.)	825.00	Each	3300.00
150	0.00	Wiring of 3/5 pin 6 amp. Light plug point with 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper conductor 1.1 kV grade and 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper earth conductor 1.1 kV grade (IS:694) in recessed ISI marked MMS (IS:9537 P - III) PVC conduit & it's ISI marked (IS:3419-1988) accessories, Hot Dipped Galvanized Modular box of 1.2 mm thick with earth terminal, 10 A modular switch, 3/5 pin 6 A modular socket, Modular face plate with grid plate, screws, making connections, testing etc. as required. For specification of copper Conductor, Phenolic Laminated sheet's & Electrical/ Wiring accessories refer Chapter E - 04, E - 05 & E - 07 For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
a	4.00	On board	382.00	P. point	1528.00
b	2.00	Short point (up to 3 mtr.)	551.00	P. point	1102.00
151		S&F following sizes (dia.) of ISI marked virgin material MMS (IS:9537 P - III) PVC conduit along with ISI marked (IS:3419-1988) accessories as required in recess including cutting the wall, covering conduit and making good the same as required. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
a	40.00	20 mm	39.00	R. mtr.	1560.00
b	60.00	25 mm	55.00	R. mtr.	3300.00
152		Supplying and drawing FR PVC insulated & unsheathed flexible copper conductor as per PWD specification for electrical Works with ISI marked (IS:694) and as per IS 8130 : 2013 of 1.1 kV grade . Wire should be made from 99.90 % purity copper, class 5 stranding in acc. to IS:8130/IEC 60228 for lower watt loss , oxygen free for less chances of oxidization, insulation PVC type A/C/D , flame retardant as per IS 10810-53, better amperage rating as per IS:3961 part 5, in existing surface or recessed PVC/ MS conduit/casing capping making connections with Copper Lugs of suitable size, Ferrules, testing etc. as required. OEM Must have its own in house NABL lab setup for all testing facilities for wires. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
a	270.00	3x 1.5 sq.mm	760.00	Mtr.	207000.00

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

b	90.00	2 x 2.5 sq. mm. + 1x1.5sqmm	106.00	Mtr.	9540.00
153		Providing & Laying P.V.C. / XLPE insulated & P.V.C. sheathed Armoured Aluminium cable conforming to IS:1554 P-I / IS :7098 P - I of 1.1 KV with H4- Grade electrolytic aluminium conductor conforming to IS 8130 of purity >99.6 %, round / flat strip armouring of cables, Inner / outer sheath conforming to IS:5831 in existing RCC / Hume / Stoneware / PVC pipe/ open duct/cable trench / Cable tray(with cable tie) including testing etc. as required of following size. OEM must have it's own in house NABL accredited Laboratory for testing procedure as per IS:10810.For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
a		16.0 Sq. mm			
i	40.00	4 core	256.00	Mtr	10240.00
154		Providing & Fixing of modular type switch/ bell push dully ISI marked (IS :3854) with CM/L no. printed and made out of unbreakable and fire retardant vergin UV Stabilized Polycarbonate with brass terminals and captive screws & silver alloy contact tip with IP-20 rating ,minimum width of switch toggle(PUSH PART) should not less then 20mm, including all as per pre approved by Engineer in charge,making connections, testing etc. as required. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
a	20.00	10 A one way switch	55.00	Each	1100.00
b	8.00	16 A one way switch With Led Indicator	132.00	Each	1056.00
155		Providing & Fixing of modular type lockable feature socket dully made out of unbreakable and fire retardant vergin poly carbonate with brass terminals and captive screws & silver alloy contact tip with IP-20 rating , including all as per pre approved by Engineer in charge,making connections, testing etc. as required. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
a	6.00	6 A 3/5 pin shuttered socket	99.00	Each	594.00
b	4.00	6/16 A shuttered socket	170.00	Each	680.00
156		Providing & Fixing of following size mounting grid plates with cover plates made from fire retardent UV established high performance engineering plastic suitable for all universal metal boxes for front installation & removal direct fit type complete in all respect.All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
a	8.00	4 Module	107.00	Each	856.00
b	6.00	8 Module	202.00	Each	1212.00
157		Providing & Fixing of Wiring Accessories OEM fabricated following size virgin material UPVC modular boxes on surface suitable for modular accessories as required.All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
a	4.00	4-5 Module	155.00	Each	620.00
b	2.00	6-8 Module	248.00	Each	496.00

Signature valid

Digitally signed by Rajkesh Meena
 Designation: Secretary
 Date: 2026.06.25 12:06:51 IST
 Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

158		Providing & Fixing of 240/415 V AC MCB with positive isolation of 10 kA breaking capacity (B/ C/D tripping characteristic as per type of load and site requirement) 4 KV impulse withstand voltage, ISI marked IS 8828(1996) / conforming to IEC 60898-1 2002, IEC 60947-2, low watt losses, trip free mechanism , energy limiting of class 3 as per IEC, minimum phase termination capacity of 35sq.mm. , conductor line load reversibility , IP 20 contact protection and fitted in existing distribution board/sheets, minimum electrical operation 20,000 upto 20 A rating and 10,000 upto 63 A, 5000 for 80 A & above rating including making connections, testing etc. as required. OEM shall have submit NABL / CPRI / ERDA accredited lab type test reports & All as per pre approved by Engineer in charge. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
a		Single pole MCB (With B/C curve tripping Characteristics)			
i	8.00	6 A to 32 A rating	199.00	Each	1592.00
159		Providing & Fixing of 240/415 V isolator ISI marked IS:13947-III/conforming to IEC 60947-3, suitable for AC22A utilization category, 4KV impulse withstand voltage, true contact indication, Red colour dolly / lever shall have single mould covering over all poles for operation , two position din rail mounting, minimum phase termination capacity of 35sq.mm. IP 20 contact protection and fitted in existing distribution board / sheet including making connections, testing etc. as required. OEM shall have submit NABL / CPRI / ERDA accredited lab type test reports & All as per pre approved by Engineer in charge.For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
a		Double pole isolator			
i	2.00	63 A rating	551.00	each	1102.00
160		Providing & Fixing of Heavy duty capacitor start, copper wound Double ball bearing 900/1400 RPM single phase Exhaust fan conforming to IS:2312 ISI marked in existing opening including making connections testing etc. as required. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
i	6.00	300 mm sweep(900 RPM)	3487.00	Each	20922.00
161		Providing & Fixing of IP20 SMD Mid Power LED batten type integrated light fixture made from Powder coated Extruded aluminium housing with in built driver , System lumen efficacy ≥ 110 lm/Watt output, internal surge protection ,THD < 10% , P. F. ≥ 0.95 , CRI >80 , life time of minimum 50000 Burning Hours with , 70% of intial Lumen maintained till life ends , CCT 3000°K / 4000°K / 5700°K /6000°K/6500°K (As per ANSI Bin) , Maximum power consumption should not more than the specified rating and Fixture shall be of BIS standard and trade mark certificate (T.C.). Manufactures Word Mark/ Name Engraved/ Embossing/ Screen printing on housing. OEM must have its own in house NABL lab setup for all testing facilities for LED fixtures. (LM79 & LM80) certificate / Report from OEM shall be submitted. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign

a	4.00	1170mm(+/-10%) LED batten with min. lumen output 2200 lm	467.00	Each	1868.00
b	4.00	570mm (+/-10%) batten with min. lumen output 1000 lm	380.00	Each	1520.00
162		Providing & Fixing of Recessed/surface mounting heavy duty horizontal type Double Door (Metal / Glazed)Distribution board with Metal end box made out from Galvanized steel / CRCA sheet not less than 1.2 mm thick conforming to IS-8623-1 & 3 / IEC 61439- 1 & 3, powder painted complete with reversible door (for double door DB only)100 amp. insulated copper bus bar/shorting link , copper neutral link, copper earth link , color coded interconnecting wire set of suitable rating and din bar,masking sheet, making internal DB terminations with copper lugs, Ferrules, detachable gland plate, including making connections, testing etc. as required. OEM shall have submit NABL / CPRI / ERDA accredited lab type test reports & All as per pre approved by Engineer in charge. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
a		Metal door (single phase) IK-09 and IP-43 with Metal end box			
i	1.00	8 Way (8+2)	2728.00	Each	2728.00

Secretary
Rajasthan State Sports Council
Jaipur

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.06.25 12:06:51 IST
Reason: Approved

RajKaj Ref No.:
23047897

M e-Sign